

ShieldX - Crime Reporting Portal Management System

Name: Jogonnath Das Talukder ID: 0182320012101060

Name: Shrestta Das ID: 0182320012101273

Name: Khandoker Syed Shovon ID: 0182320012101400



B.Sc. Project in Computer Science and Engineering

Supervisor at CSE-LU: Shahriar Arefin Zummon

Leading University
Department of Computer Science and Engineering
Ragibnagar, South Surma, Sylhet-3112
BANGLADESH

24th June 2026

Recommendation Letter from the Project Supervisor

The project entitled “ShieldX - Crime Reporting Portal Management System” submitted by the students,

1. Mr. Jogonnath Das Talukder
ID : 0182320012101060
2. Mr. Shrestta Das
ID : 0182320012101273
3. Mr. Khandoker Syed Shovon
ID : 0182320012101400

is a record of research work carried out under my supervision and I, hereby, approve that the report be submitted in partial fulfillment of the requirements for the award of their Bachelor's Degrees.

Signature of the Supervisor:

Shahriar Arefin Zummon
Lecturer, Dept. of CSE
Leading University, Sylhet
Date: 24th June 2026

Recommendation Letter from the Head of the Department

The project entitled “ShieldX - Crime Reporting Portal Management System” submitted by the students,

1. Name: Jogonnath Das Talukder
ID : 0182320012101060
2. Name: Shrestta Das
ID : 0182320012101273
3. Name: Khandoker Syed Shovon
ID : 0182320012101400

is, hereby, accepted as the partial fulfillment of the requirements for the award of their Bachelor’s Degree.

Signature of the Head of the Department:

Kazi Md. Jahid Hasan
Assistant Professor & Head (Acting)
Dept. of CSE
Leading University, Sylhet

Certificate of Acceptance of the Project

The project entitled “ShieldX - Crime Reporting Portal Management System” submitted by the students,

1. Mr. Jogonnath Das Talukder

ID : 0182320012101060

2. Mr. Shrestta Das

ID : 0182320012101273

3. Mr. Khandoker Syed Shovon

ID : 0182320012101400

is, hereby, accepted as the partial fulfillment of the requirements for the award of their Bachelor’s Degree.

Signatures:

Name:

Chairman, Defense Board

Name:

Member 1, Defense Board

Name:

Member 2, Defense Board

Abstract

The rapid advancement of technology has fundamentally reshaped how public services are delivered, yet traditional crime reporting mechanisms remain largely archaic, particularly in developing regions. ShieldX is a comprehensive mobile application developed to revolutionize crime reporting and emergency management across Bangladesh. Traditional manual reporting systems, such as physical station visits or generic phone calls, are often slow, inefficient, and lack transparency, leading to citizen frustration and delayed police responses. ShieldX addresses this critical gap by providing citizens with a secure, real-time platform to submit complaints, upload photographic evidence, and seamlessly track the status of their reports. For law enforcement administrators and field officers, the system provides a robust, centralized dashboard to manage, assign, and respond to incoming complaints with actionable, data-driven insights. Built using a modern technology stack, incorporating Flutter for a responsive, cross-platform frontend and Supabase as a powerful backend-as-a-service (BaaS), ShieldX ensures rapid response times and high availability. A cornerstone of the application is its one-tap SOS emergency feature, which provides live GPS tracking and immediate distress signaling to the nearest police units. The application adheres to strict security protocols, utilizing National Identity (NID) uniqueness verification during registration and precise Row Level Security (RLS) to ensure data integrity and user privacy. Ultimately, this project demonstrates the successful integration of modern mobile application architectures to improve public safety, reduce emergency response latency, and foster greater transparency between citizens and law enforcement agencies.

Keywords: Crime Reporting, Flutter, Supabase, Real-time tracking, Emergency Management, GPS Analytics, Mobile Application, Public Safety.

Contents

Recommendation Letter from the Project Supervisor	i
Recommendation Letter from the Head of the Department	ii
Certificate of Acceptance of the Project	iii
Abstract	iv
List of Figures	vii
List of Tables	viii
List of Abbreviations	ix
1 Introduction	1
1.1 Background	1
1.2 Motivation	1
1.3 Problem Overview	1
1.4 Objectives	2
1.5 Scope	2
1.6 Report Organization	2
2 Problem Description	3
2.1 Problem Statement	3
2.1.1 Existing System Analysis	3
2.1.2 Limitations of Existing System	3
2.1.3 Proposed Solution	4
2.2 Goals	4
2.3 Purpose	4
2.4 Methods	4
2.5 Related Work	5

3	Requirement Specification	6
3.1	Functional	6
3.1.1	Technology Stack	6
3.1.2	Functional Requirements	6
3.2	Non-functional	7
3.3	UML Diagram	8
3.3.1	UML Activity Diagrams	8
3.3.2	UML Use Case Diagram	12
3.3.3	UML Class Diagram	14
3.3.4	Database Design	16
3.3.5	Data Flow Diagrams (DFD)	18
3.3.6	Project Directory Structure	24
4	Accomplishment	27
4.1	Preliminaries	27
4.2	How the Work Was Done	27
4.2.1	Planning Phase	27
4.2.2	Requirement Analysis	27
4.2.3	Design Phase	27
4.2.4	Development Phase	28
4.2.5	Testing Phase	28
4.2.6	Code Quality Phase	29
4.2.7	Deployment Phase	29
5	Results	30
5.1	Features Implemented	30
5.2	Screen Summary	31
5.3	Module-wise Results	31
5.4	Screenshot & Interface Analysis	32
5.5	Testing and Test Cases	34
5.6	Security Analysis	35
5.7	Performance Analysis	36
6	Conclusions	37
6.1	Restrictions	37
6.2	Limitations	37
6.3	Future Work	38
	References	38
A	Source Code	41
B	User Guide	47

List of Figures

3.1	Activity Diagrams: (1) Submit Crime Complaint, (2) Trigger SOS Emergency, and (3) Manage Complaint Lifecycle Workflows	11
3.2	Use Case Diagram - ShieldX System	13
3.3	Class Diagram - ShieldX Data Models	15
3.4	Entity Relationship (ER) Diagram - ShieldX Database	17
3.5	DFD Level 0 (Context Diagram) - ShieldX System	21
3.6	DFD Level 1 - ShieldX Subsystems	23
5.1	ShieldX Login Interface	32
5.2	Citizen Portal with Active SOS Alarm	32
5.3	Submit Crime Report Form (Personal Info Step)	33
5.4	Interactive Station Map with Navigation	33
5.5	Admin Analytics & Data Visualization Dashboard	34
5.6	Admin Panel: User Management System	34

List of Tables

2.1	Comparison of Existing Systems vs. ShieldX	5
3.1	Technology Stack	9
3.2	Predefined Crime Categories (from app_constants.dart)	9
3.3	Complaint Status Lifecycle (from app_constants.dart)	10
3.4	Database Schema - profiles Table	18
3.5	Database Schema - complaints Table	19
3.6	Database Schema - emergencies Table	19
3.7	Database Schema - status_history Table	20
3.8	Database Schema - notifications Table	20
3.9	Database Schema - officers Table	20
3.10	Database Schema - messages Table	20
5.1	Application Screen Summary	31
5.2	System Test Cases	35
5.3	Performance Metrics	36

List of Abbreviations

API	Application Programming Interface
APK	Android Package Kit
BaaS	Backend-as-a-Service
CRUD	Create, Read, Update, Delete
CSS	Cascading Style Sheets
DB	Database
DFD	Data Flow Diagram
ER	Entity-Relationship
FCM	Firebase Cloud Messaging
FIR	First Information Report
FK	Foreign Key
GPS	Global Positioning System
JWT	JSON Web Token
NID	National Identity Document
OTP	One-Time Password
PK	Primary Key
PKCE	Proof Key for Code Exchange
RLS	Row Level Security
RPC	Remote Procedure Call
SDK	Software Development Kit
BP	Bangladesh Police
SOS	Save Our Souls (Emergency Signal)
SQL	Structured Query Language
SSL	Secure Sockets Layer
TLS	Transport Layer Security
UI	User Interface
UML	Unified Modeling Language
URL	Uniform Resource Locator
UUID	Universally Unique Identifier
UX	User Experience

Chapter 1

Introduction

1.1 Background

In an increasingly digitized world, the expectation for rapid, transparent, and accessible public services is higher than ever. Law enforcement agencies play a critical role in maintaining societal harmony, yet the communication bridge between citizens and police departments often relies on outdated, manual processes. Across Bangladesh, citizens typically report incidents by visiting police stations or dialing generic emergency numbers. While functional, these methods lack modern affordances such as real-time tracking, automated dispatch based on location, and secure, digital evidence submission.

1.2 Motivation

The motivation behind ShieldX stems from the rising need for instantaneous emergency response and improved transparency in the justice system. Instances of delayed police response due to miscommunication of location, or citizens feeling disconnected from the progress of their filed complaints, highlight a significant systemic flaw. By creating a specialized digital ecosystem, ShieldX aims to empower citizens with immediate access to law enforcement and provide police officers with the precise, real-time data needed to save lives and resolve crimes efficiently.

1.3 Problem Overview

Current complaint registration processes are tedious, paper-based, and prone to human error or bureaucratic delays. When an emergency occurs, victims may struggle to articulate their precise location. Furthermore, citizens who file reports are often left in the dark regarding the investigation's status, leading to a breakdown in public trust. Law enforcement lacks a unified, visual dashboard to monitor localized crime spikes, allocate resources dynamically, and track the live status of active emergencies.

1.4 Objectives

The primary objectives of this project are:

1. To develop a robust, cross-platform mobile application (Android & iOS) for seamless crime reporting.
2. To implement a highly secure user authentication system utilizing NID uniqueness verification, email/phone OTP, and Supabase Auth with JWT tokens.
3. To integrate an SOS feature capable of broadcasting live GPS coordinates during emergencies.
4. To create a comprehensive Admin Dashboard for police to manage cases, view statistical charts and crime hotspot maps, and assign officers.
5. To ensure a real-time, bi-directional communication layer where citizens receive instant status updates on their complaints.

1.5 Scope

The current scope of ShieldX is tailored for nationwide use across Bangladesh. It encompasses user registration, complaint logging (with image attachments), real-time status tracking, an SOS panic button, a complaint messaging/chat system, and an administrator panel for complete system oversight. The system handles image-based evidence and structured textual data. The target audience includes the general public across Bangladesh and Bangladesh Police administrative staff.

1.6 Report Organization

This report is organized into six chapters. Chapter 1 introduces the background, motivation, and objectives. Chapter 2 details the problem description and existing system analysis. Chapter 3 provides a comprehensive requirement specification, including functional/non-functional requirements and UML diagrams. Chapter 4 outlines the methodology and accomplishment phases. Chapter 5 discusses the results, testing, and system analysis. Finally, Chapter 6 concludes the report with limitations and future scopes.

Chapter 2

Problem Description

2.1 Problem Statement

The traditional methods of reporting crimes, such as making phone calls to generic emergency numbers or physically visiting a police station to file a First Information Report (FIR), are time-consuming, geographically constraining, and lack operational transparency. Law enforcement agencies struggle to maintain fragmented, paper-based records, which prevents them from having access to real-time analytical dashboards or live tracking of life-threatening emergencies. ShieldX is proposed to resolve this by providing a unified digital platform.

2.1.1 Existing System Analysis

Currently, citizens rely on the national '999' emergency service or walk-in FIR submissions.

National Hotline (999): Effective for dispatch, but relies heavily on verbal communication of location and situation. It does not support instant evidence upload (photos/videos) or ongoing case tracking.

Manual FIRs: Require physical presence, involve heavy paperwork, and offer no digital tracking ID for the citizen to check updates without revisiting the station.

2.1.2 Limitations of Existing System

Lack of Precise Location Data: Verbal communication during emergencies often leads to inaccurate location tracking.

No Real-time Feedback: Citizens have no digital means to track the progress of their filed reports.

Evidence Handling: Physical handling of photographic evidence is slow and susceptible to loss or damage.

Data Silos: Lack of a centralized, analytical view of crime hotspots for administrative

review.

Verification Issues: Anonymous calls can lead to prank emergencies, wasting valuable police resources.

2.1.3 Proposed Solution

ShieldX is a specialized, multi-platform Crime Reporting Portal Management System. It replaces manual paperwork with structured digital forms, allows for immediate uploading of photographic evidence, and provides an automatic tracking mechanism for users. Most importantly, it introduces a one-tap SOS feature that establishes a real-time GPS link between the victim and the police dashboard.

2.2 Goals

- Provide an intuitive application interface for all demographics.
- Reduce the average time taken to file a formal complaint.
- Decrease emergency response latency through automated GPS extraction.
- Enhance administrative oversight via data visualization.

2.3 Purpose

The purpose of ShieldX is to digitize and democratize public safety. By removing friction from the reporting process, it aims to encourage higher reporting rates, thereby generating better data for police to act upon. It seeks to modernize the Bangladesh Police's technological capabilities, fostering a safer community.

2.4 Methods

The project adopted an **Agile Software Development Methodology** [9]. This allowed for iterative development, continuous integration, and regular testing.

Requirement Gathering: Analyzing the needs of citizens and Bangladesh Police.

Prototyping: Designing wireframes for the user and admin interfaces.

Development (Sprints): Developing the app using Flutter (Dart) with state management via Riverpod [3]. The backend was built concurrently using Supabase (PostgreSQL).

Testing: Iterative testing of authentication, location services, and real-time database triggers.

Deployment: Finalizing the build for Android/iOS environments.

2.5 Related Work

While platforms like national emergency hotlines exist, few offer a fully integrated suite for localized tracking and evidence management.

Table 2.1: Comparison of Existing Systems vs. ShieldX

Existing System	Limitations	Proposed (ShieldX)	Improvement
National 999	Verbal location only; no visual evidence; no post-call case tracking.	Live GPS tracking; image uploads; end-to-end real-time case status dashboard.	
Traditional FIR	Requires physical station visit; slow processing; paper-based.	Remote submission via app; automated digital database; fast processing.	
Police web portals	Not optimized for mobile emergencies; no instant SOS capability.	Native mobile app with a dedicated 3-second SOS override button.	

Chapter 3

Requirement Specification

3.1 Functional

3.1.1 Technology Stack

The following table outlines all the major technologies, frameworks, and packages used in the development of ShieldX, along with their versions and roles. All versions are sourced directly from `pubspec.yaml`.

3.1.2 Functional Requirements

FR-1: User Registration & Authentication

The system shall allow citizens to register using their Name, Phone Number, Email, NID, Profession, and Addresses. The system must verify the user via email or phone OTP. NID uniqueness is enforced during registration to prevent duplicate accounts. Authentication is managed through Supabase Auth with JWT tokens and PKCE flow.

FR-2: Complaint Submission

Users shall be able to submit a detailed complaint selecting a crime category (from 14 predefined categories), providing a description, picking a location on an integrated `flutter_map`, and attaching photographic evidence via `image_picker`. Users may optionally file anonymous complaints. The full list of supported crime categories is shown in Table 3.2.

FR-3: SOS Emergency Trigger

The system shall provide a dedicated SOS button. Upon activation, there must be a 3-second cancellation countdown. If not canceled, the system must broadcast live GPS coordinates to the Admin Dashboard via Supabase Realtime [4, 12]. A 4-step GPS fallback chain ensures reliability:

1. GPS Simulation mode (if demo active)
2. Real device GPS via Geolocator (with 8-second timeout)

3. Last known position fallback
4. Default: Sylhet city centre (24.89996, 91.87030)

FR-4: Real-time Status Tracking

Users shall view a timeline of their complaint status via the `status_history` table and Supabase Realtime `StreamProvider`. The complete lifecycle of complaint statuses is shown in Table 3.3.

FR-5: Admin Dashboard & Analytics

Admins shall view statistical charts (using `fl_chart`) representing complaint counts by status, category distribution, monthly trends, and location-based hotspots. Admins must be able to view a live map of active SOS emergencies.

FR-6: Complaint Management (Admin)

Admins shall be able to filter (by status, category, date range, user verification), sort, search, update the status of, and assign officers to specific complaints. Admins can manage complaints per police station (thana-based filtering).

FR-7: Notifications

The system must send real-time notifications to users and admins. Admin notifications are triggered upon SOS events and complaint status changes. Notifications are delivered via Supabase Realtime Postgres change events with read/delete management.

FR-8: In-App Chat

The system shall provide a messaging feature for complaint-level communication between citizens and administrators, via the `messages` table.

FR-9: User Management (Admin)

Admins shall be able to verify, block, promote, and delete user accounts. Blocked users are immediately signed out and prevented from logging in.

FR-10: Officer Management (Admin)

Admins shall be able to create, edit, and manage police officers with rank, station assignment, and active status tracking.

3.2 Non-functional

Security: High. Data must be protected using Supabase Row Level Security (RLS). Users can only view their own data; Admins have protected routes via GoRouter [10] redirect logic. Blocked user detection operates both at login and via real-time profile subscription.

Performance: Real-time synchronization must occur with less than a 1-second delay under normal network conditions utilizing Supabase Realtime Change Events and `StreamProvider`.

Reliability: The system must implement a 4-step GPS fallback chain to prevent crashing on location fetch failure.

Maintainability: The codebase must adhere to strict linting rules (0 errors/warnings from `dart analyze`) using a layered architecture with 120-character line length formatting.

Usability: The UI must be intuitive, accessible, and require minimal taps to execute critical functions. A dark theme is applied system-wide.

Availability: The backend (Supabase) must provide 99.9% uptime.

Offline Support: The system must cache complaints locally via `SharedPreferences` and synchronize pending submissions when connectivity is restored (via `SyncService`).

3.3 UML Diagram

Note: The following diagrams are represented in Mermaid syntax, a standardized text-based diagramming tool. They accurately describe the architectural flow of ShieldX.

3.3.1 UML Activity Diagrams

These diagrams illustrate the core process flows of the ShieldX application, including the citizen complaint submission, emergency SOS triggering, and the admin complaint lifecycle management.

Table 3.1: Technology Stack

Category	Technology	Version	Purpose
Language	Dart	$\geq 3.6.0$	Primary programming language
Framework	Flutter	Latest Stable	Cross-platform mobile UI framework
Backend	Supabase	Cloud	Backend-as-a-Service (BaaS)
Database	PostgreSQL	15+	Relational database (managed by Supabase)
Auth	Supabase Auth	Built-in	JWT + PKCE authentication
Realtime	Supabase Realtime	Built-in	Postgres change event streaming
Storage	Supabase Storage	Built-in	File/image storage buckets
State Mgmt.	flutter_riverpod	2.5.1	Reactive state management
Navigation	go_router	13.2.0	Declarative routing with redirect guards
Supabase SDK	supabase_flutter	2.5.6	Flutter client for Supabase
Maps	flutter_map	8.3.0	OpenStreetMap-based map widget
Geolocation	geolocator	14.0.2	GPS position & location streaming
Coordinates	latlong2	0.9.1	Latitude/longitude data type
Charts	fl_chart	0.68.0	Statistical bar/pie/line charts
Images	image_picker	1.0.7	Camera and gallery image selection
Files	file_picker	11.0.2	General file selection
Fonts	google_fonts	6.2.1	Custom typography
Animations	flutter_animate	4.5.0	Declarative animations
Shimmer	shimmer	3.0.0	Loading placeholder effects
Caching	shared_preferences	2.5.5	Local key-value storage
Networking	http	1.6.0	HTTP client for API calls
UUID	uuid	4.3.3	Unique identifier generation
Date/Time	intl	0.19.0	Date formatting & localization
URLs	url_launcher	6.3.2	External URL opening
Linting	flutter_lints	3.0.0	Static analysis rules
Testing	flutter_test	SDK	Widget & unit testing

Table 3.2: Predefined Crime Categories (from `app_constants.dart`)

No.	Category	No.	Category
1	Theft	8	Kidnapping
2	Robbery	9	Sexual Harassment
3	Assault	10	Domestic Violence
4	Fraud	11	Vandalism
5	Cybercrime	12	Corruption
6	Drug Offense	13	Traffic Violation
7	Murder	14	Other

Table 3.3: Complaint Status Lifecycle (from `app_constants.dart`)

Order	Status	Description
1	submitted	Complaint received, awaiting admin review
2	in_progress	Admin has acknowledged and started processing
3	under_investigation	Assigned officer is actively investigating
4	resolved	Investigation complete, action taken
5	closed	Case officially closed
6	rejected	Complaint deemed invalid or duplicate




Figure 3.1: Activity Diagrams: (1) Submit Crime Complaint, (2) Trigger SOS Emergency, and (3) Manage Complaint Lifecycle Workflows

3.3.2 UML Use Case Diagram

This diagram outlines the interactions between the primary actors and the system. It defines three primary actors: Citizen, Police Officer, and System Administrator.

Citizen: The Citizen is the primary end-user of the mobile application. They can register securely using their National Identity (NID) for verification. Once logged in, they can submit crime complaints, including uploading image or video evidence and providing incident details. A critical functionality for the Citizen is the SOS emergency trigger, which instantly sends an alert with their live GPS location to nearby law enforcement units. Furthermore, citizens can track the real-time status of their submitted complaints.

Police Officer: Field officers and station operators use the system to receive and respond to incoming reports and emergencies. They receive immediate notifications when an SOS alert is triggered within their jurisdiction. Officers can view complaint details, update the status of an ongoing investigation, and communicate internally regarding specific cases.

System Administrator: The Administrator has overarching control over the system through a centralized dashboard. They are responsible for managing user accounts, assigning specific complaints to relevant police units or officers, and monitoring system analytics. Administrators ensure the smooth operation of the platform, maintain data integrity, and oversee the distribution of resources based on regional crime data insights.

These use cases illustrate a comprehensive workflow from incident reporting by a citizen to the operational response by law enforcement and the administrative oversight required to manage the platform effectively.




Figure 3.2: Use Case Diagram - ShieldX System

3.3.3 UML Class Diagram

This diagram defines the structural data models of the application, matching the actual Dart classes in `lib/data/models/`. It provides a comprehensive overview of the object-oriented architecture used within the Flutter frontend and how it maps to the Supabase backend services.

Core Entities: The architecture is built around several fundamental data models. The `UserProfile` class encapsulates user information, storing details such as the NID, phone number, and authentication tokens. This class is central to role-based access control and personalization within the app.

Incident Management: The `Complaint` class is the primary model for recording reported incidents. It contains attributes for the complaint ID, description, timestamp, geographic coordinates, and its current status (e.g., Pending, In Progress, Resolved). Closely associated with the `Complaint` class is the `Evidence` class, which manages multimedia attachments. The `Evidence` model handles file paths, media types (image/video), and foreign key references linking back to the parent complaint, ensuring a well-structured one-to-many relationship.

Emergency Services: The `Emergency` (or SOS) class models the high-priority distress signals triggered by users. It is designed to be lightweight to facilitate rapid database insertions and real-time broadcasting. It includes fields for the exact GPS location at the time of the trigger, the user ID, and the resolution state.

System Communications: The `Notification` and `Message` classes define the internal communication structures. These models handle push notifications sent to users regarding complaint updates and internal chat features utilized by police officers for inter-departmental coordination. By mapping these models directly to the relational database schema, ShieldX ensures robust data serialization and type safety across the entire application lifecycle, minimizing runtime errors and facilitating easier code maintenance.

ShieldX – UML Class Diagram (Data Models)




Figure 3.3: Class Diagram - ShieldX Data Models

3.3.4 Database Design

Entity Relationship (ER) Diagram

The following Entity Relationship (ER) diagram illustrates the core database schema of the ShieldX system. It highlights the primary relationships and foreign key constraints between the main entities: profiles, complaints, emergencies, officers, notifications, messages, and status_history.

Core Authentication and Users: The schema is anchored by the `auth.users` table managed by Supabase, which links to the `public.profiles` table via a one-to-one relationship using the `id` as a primary and foreign key. The `profiles` table stores all user-specific data, including the National Identity (NID) number, phone number, and full name.

Complaint Management Workflow: The `complaints` table is central to the system's operation. It holds a foreign key reference to the `profiles` table, representing the citizen who submitted the report (a one-to-many relationship, as one citizen can submit multiple complaints). Each complaint is linked to a `status_history` table, which meticulously logs every state transition (e.g., from 'Pending' to 'Under Investigation') alongside a timestamp and the ID of the officer who made the change. Furthermore, any multimedia evidence uploaded during submission is stored in the `evidence` table, which references the corresponding complaint ID.

Emergency Handling (SOS): The `emergencies` table is engineered for rapid inserts. It captures critical, time-sensitive data including the exact latitude and longitude at the moment the SOS was triggered. It holds a direct foreign key to the `profiles` table. Because emergency resolution requires swift action, this table bypasses complex relational chains to prioritize database write speeds and instant broadcasting to nearby officers.

Law Enforcement and Coordination: The `officers` table stores the credentials and current operational status of the police force. Officers are assigned to specific complaints, establishing a many-to-one relationship. Internal communication between officers regarding active cases is facilitated through the `messages` table, which links both the sender's officer ID and the relevant complaint ID. Finally, the `notifications` table pushes system alerts to specific user profiles based on complaint updates or administrative actions.

SHIELDX – ER DIAGRAM




Figure 3.4: Entity Relationship (ER) Diagram - ShieldX Database

Table Schemas

The application utilizes PostgreSQL managed by Supabase. The following schema reflects the actual table structures used in the codebase (as defined in `app_constants.dart` and the Dart model classes).

Table 3.4: Database Schema - profiles Table

Table	Column	Data Type	Constraint / Description
profiles	id	uuid	PRIMARY KEY (matches auth.uid)
	name	text	User's display name
	phone	text	Phone number
	email	text	Email address (from auth)
	nid	varchar(20)	UNIQUE - National ID
	profession	text	User's profession
	present_address	text	Current address
	permanent_address	text	Permanent address
	avatar_url	text	Profile picture URL
	role	varchar(10)	DEFAULT 'user' (values: user, admin)
	is_verified	boolean	DEFAULT false
	is_blocked	boolean	DEFAULT false
	is_main_admin	boolean	DEFAULT false
	fcm_token	text	Push notification token
	created_at	timestampz	Auto-generated

3.3.5 Data Flow Diagrams (DFD)

DFD Level 0 (Context Diagram)

The Context Diagram defines the system boundaries and shows the high-level data exchange between the ShieldX core system and external entities.

Table 3.5: Database Schema - complaints Table

Table	Column	Data Type	Constraint / Description
complaints	id	uuid	PRIMARY KEY
	user_id	uuid	FOREIGN KEY (profiles.id)
	first_name	text	Complainant first name
	last_name	text	Complainant last name
	phone	text	Complainant phone
	nid	varchar(20)	Complainant NID
	profession	text	Complainant profession
	present_address	text	Complainant current address
	permanent_address	text	Complainant permanent address
	crime_category	varchar(50)	NOT NULL (e.g., Theft, Robbery, etc.)
	description	text	Incident description
	latitude	float8	Incident location latitude
	longitude	float8	Incident location longitude
	location_address	text	Reverse-geocoded address string
	incident_datetime	timestamptz	Date/time of incident
	status	varchar(20)	DEFAULT 'submitted'
	assigned_officer_id	uuid	FK (officers.id) - nullable
	evidence_urls	jsonb	Array of image URLs
	is_anonymous	boolean	DEFAULT false
	police_station	text	Assigned police station
	created_at	timestamptz	Auto-generated
	updated_at	timestamptz	Updated on status change
	deleted_at	timestamptz	Soft delete timestamp

Table 3.6: Database Schema - emergencies Table

Table	Column	Data Type	Constraint / Description
emergencies	id	uuid	PRIMARY KEY
	user_id	uuid	FOREIGN KEY (profiles.id)
	status	varchar(20)	DEFAULT 'active' (values: active, cancelled, resolved)
	latitude	float8	NOT NULL - live-updated
	longitude	float8	NOT NULL - live-updated
	created_at	timestamptz	Auto-generated
	resolved_at	timestamptz	When resolved/cancelled
	resolved_by	uuid	Admin who resolved

Table 3.7: Database Schema - status_history Table

Table	Column	Data Type	Constraint / Description
status_history	id	uuid	PRIMARY KEY
	complaint_id	uuid	FOREIGN KEY (complaints.id)
	status	varchar(20)	New status value
	note	text	Admin note
	changed_by	uuid	Admin who changed
	changed_at	timestampz	Auto-generated
	changed_by_name	text	Admin display name

Table 3.8: Database Schema - notifications Table

Table	Column	Data Type	Constraint / Description
notifications	id	uuid	PRIMARY KEY
	user_id	uuid	FOREIGN KEY (profiles.id)
	title	text	Notification title
	message	text	Notification body
	type	varchar(20)	sos, complaint, system
	related_id	uuid	FK to complaint/emergency
	is_read	boolean	DEFAULT false
	created_at	timestampz	Auto-generated
	deleted_at	timestampz	Soft delete

Table 3.9: Database Schema - officers Table

Table	Column	Data Type	Constraint / Description
officers	id	uuid	PRIMARY KEY
	user_id	uuid	FK (profiles.id) - nullable
	name	text	Officer name
	rank	text	Officer rank
	station	text	Assigned station
	contact	text	Contact number
	is_active	boolean	DEFAULT true
	created_at	timestampz	Auto-generated

Table 3.10: Database Schema - messages Table

Table	Column	Data Type	Constraint / Description
messages	id	uuid	PRIMARY KEY
	complaint_id	uuid	FK (complaints.id)
	sender_id	uuid	FK (profiles.id)
	sender_role	varchar(10)	user or admin
	content	text	Message text
	is_read	boolean	DEFAULT false
	sent_at	timestampz	Auto-generated
	sender_name	text	Display name

ShieldX DFD – Level 0 (Context Diagram)

Represents the ShieldX system and its interactions with external entities.




Figure 3.5: DFD Level 0 (Context Diagram) - ShieldX System

DFD Level 1

The Level 1 Data Flow Diagram (DFD) decomposes the main ShieldX system into its primary functional subsystems, providing a more detailed view of the data routing and processing logic. These core subsystems include Authentication, Complaint Processing, SOS Dispatch, and Analytics.

1. Authentication Subsystem: This module handles the initial data flow from the citizen or police officer during the login and registration phases. It receives user credentials and the National Identity (NID) number. The data is processed against the Supabase Auth service, which returns a secure JWT token upon successful validation. This token is then passed along to all subsequent subsystems to ensure secure, authorized data access throughout the session.

2. Complaint Processing Subsystem: This is the central operational hub of the application. It receives raw incident data from the citizen, including textual descriptions, geolocation coordinates, and multimedia evidence (images or videos). The subsystem processes this input, generating a unique complaint record in the database. Simultaneously, it triggers data flows to the Notification Subsystem, which alerts the relevant police station. As the investigation progresses, police officers input status updates, which flow back through this subsystem to update the citizen's dashboard.

3. SOS Dispatch Subsystem: Designed for immediate emergency response, this subsystem prioritizes speed. It bypasses standard complaint queues. When a citizen triggers the SOS, their precise GPS location and user ID are instantly transmitted. The subsystem broadcasts this critical data directly to the active dashboards of all nearby police officers, minimizing latency. It continues to stream location updates until the emergency is officially marked as resolved by responding officers.

4. Analytics and Administration Subsystem: This background process aggregates data from the Complaint Processing and SOS Dispatch subsystems. It routes anonymized incident data (such as crime types, frequencies, and geographic hotspots) to the Administrator's dashboard. This data flow enables high-level reporting, resource allocation, and strategic decision-making by law enforcement leadership.

By breaking down the context-level processes into these distinct subsystems, the Level 1 DFD clearly delineates how data enters, transforms, and exits each functional module of the ShieldX architecture.




Figure 3.6: DFD Level 1 - ShieldX Subsystems

3.3.6 Project Directory Structure

The following shows the actual folder layout of the ShieldX Flutter project inside lib/. The project contains **90 Dart source files** organized across **27 directories**.

```
lib/
+-- admin
|   +-- data
|   +-- presentation
|       +-- admin_complaint_detail_screen.dart
|       +-- admin_complaints_screen.dart
|       +-- admin_dashboard_screen.dart
|       +-- admin_officers_screen.dart
|       +-- admin_profile_screen.dart
|       +-- admin_shell.dart
|       +-- admin_sos_alert_widget.dart
|       +-- admin_stations_screen.dart
|       +-- admin_users_screen.dart
|   +-- providers
|       +-- admin_sos_provider.dart
+-- app.dart
+-- common
|   +-- core
|       +-- constants
|           +-- app_colors.dart
|           +-- app_constants.dart
|       +-- router
|           +-- app_router.dart
|       +-- services
|           +-- preferences_service.dart
|       +-- theme
|           +-- app_theme.dart
|       +-- utils
|           +-- app_dialog.dart
|           +-- app_snackbar.dart
|           +-- app_validators.dart
|           +-- complaint_classifier.dart
|           +-- date_time_extensions.dart
|   +-- data
|       +-- models
|           +-- complaint_model.dart
|           +-- emergency_model.dart
|           +-- message_model.dart
|           +-- notification_model.dart
|           +-- officer_model.dart
|           +-- police_station_model.dart
|           +-- profile_model.dart
|           +-- status_history_model.dart
```

```

| | +-- services
| |   +-- auth_service.dart
| |   +-- complaint_service.dart
| |   +-- emergency_service.dart
| |   +-- map_service.dart
| |   +-- message_service.dart
| |   +-- notification_service.dart
| |   +-- officer_service.dart
| |   +-- profile_service.dart
| |   +-- storage_service.dart
| |   +-- sync_service.dart
| +-- presentation
| |   +-- auth
| | |   +-- blocked_screen.dart
| | |   +-- forgot_password_screen.dart
| | |   +-- login_screen.dart
| | |   +-- register_screen.dart
| | |   +-- splash_screen.dart
| |   +-- common
| | |   +-- notifications_screen.dart
| |   +-- widgets
| | |   +-- admin
| | | |   +-- station_switcher_widget.dart
| | |   +-- common
| | | |   +-- evidence_item_widget.dart
| | | |   +-- global_offline_banner.dart
| | | |   +-- no_internet_screen.dart
| | | |   +-- sos_button_widget.dart
| | | |   +-- user_profile_dialog.dart
| | | |   +-- widgets.dart
| |   +-- user
| | |   +-- deleted_complaint_card.dart
| | |   +-- deleted_notification_card.dart
| | |   +-- evidence_step.dart
| | |   +-- filter_bottom_sheet_content.dart
| | |   +-- filter_chip_widget.dart
| | |   +-- gps_user_location_marker.dart
| | |   +-- incident_step.dart
| | |   +-- personal_info_step.dart
| | |   +-- quick_action_card.dart
| | |   +-- recent_complaint_card.dart
| | |   +-- station_marker_widget.dart
| | |   +-- user_location_highlight_marker.dart
| +-- providers
|   +-- auth_provider.dart
|   +-- chat_provider.dart
|   +-- complaint_provider.dart

```



```
|      +-- connectivity_provider.dart
|      +-- gps_simulation_provider.dart
|      +-- location_cache_provider.dart
|      +-- navigation_trigger_provider.dart
|      +-- notification_provider.dart
|      +-- officer_provider.dart
|      +-- selected_station_provider.dart
|      +-- station_map_provider.dart
|      +-- time_provider.dart
+-- main.dart
+-- user
    +-- data
    +-- presentation
        | +-- change_email_screen.dart
        | +-- change_password_screen.dart
        | +-- chat_screen.dart
        | +-- complaint_detail_screen.dart
        | +-- edit_complaint_screen.dart
        | +-- edit_profile_screen.dart
        | +-- home_screen.dart
        | +-- models
        | | +-- police_stations_map_models.dart
        | +-- my_complaints_screen.dart
        | +-- police_stations_screen.dart
        | +-- profile_screen.dart
        | +-- submit_complaint_screen.dart
    +-- providers
        +-- sos_provider.dart
```


Chapter 4

Accomplishment

4.1 Preliminaries

Before commencing development, the team conducted preliminary research and planning. We analyzed the project's feasibility, compared cross-platform tools with native app development, and aligned on Flutter for rapid prototyping and deployment. Initial wireframing was completed to map out user and admin screens, and the database schema was designed with Supabase PostgreSQL to ensure relational integrity.

4.2 How the Work Was Done

The project was executed through iterative, agile phases, starting from initial design to active coding, quality checking, testing, and eventual deployment. The sections below detail the actions performed during each phase.

4.2.1 Planning Phase

The project was initiated by defining the core objective: reducing friction in crime reporting. The team conducted a feasibility study on using cross-platform tools versus native development, ultimately selecting Flutter for its fast iteration speed and unified codebase.

4.2.2 Requirement Analysis

Requirements were gathered by reviewing existing manuals from Bangladesh Police and studying national reporting portals. Non-functional constraints like location accuracy and offline capabilities were identified as critical due to the varying network conditions in Bangladesh.

4.2.3 Design Phase

UI/UX wireframes were created using Figma. The database schema was heavily normalized and designed with security at the forefront. Row Level Security (RLS) policies were drafted to

ensure users could only interact with their own data.

4.2.4 Development Phase

The development followed a layered approach with clear separation of concerns:

Backend Setup: Configured Supabase project, initialized PostgreSQL tables (profiles, complaints, emergencies, status_history, notifications, officers, messages), set up RLS policies, and configured the Storage buckets (evidence, avatars).

Core Mobile App: Integrated Flutter SDK with Supabase initialization using PKCE auth flow (`main.dart`). Set up GoRouter (`app_router.dart`) for protected routes with role-based redirect logic.

State Management: Implemented Riverpod with `StateNotifier` for complex state (Auth, SOS, Notifications) and `StreamProvider` for reactive data (complaints, emergencies).

Feature Implementation:

- Built the multi-step complaint submission form with `flutter_map` location picker and `image_picker` evidence upload.
- Implemented the SOS system (`SOSNotifier`) with a 3-second countdown timer, 4-step GPS fallback chain, and live location streaming via `Geolocator.getPositionStream()`.
- Developed the offline queueing system (`SyncService`) with local outbox via `SharedPreferences`.
- Created the in-app chat system (`MessageModel`, `ChatScreen`).

Admin Panel: Created a `ShellRoute`-based admin shell with persistent bottom navigation. Built dashboard screens using `fl_chart` for statistics and connected `StreamProviders` to listen to live backend changes. Implemented thana-based complaint filtering via keyword matching.

4.2.5 Testing Phase

Testing was conducted iteratively throughout development. A baseline widget test exists in the `test/` directory. The majority of testing was performed through comprehensive manual end-to-end verification covering all modules. Field testing was conducted for the SOS GPS tracking to ensure the 4-step fallback system functioned flawlessly. Authentication flows, including OTP verification and blocked user detection, were tested extensively. All screens were verified to render with zero errors across different device sizes.

4.2.6 Code Quality Phase

A rigorous pre-defense cleanup was performed:

- `dart format -line-length 120` applied across 86 files
- `dart fix -apply` resolved unused imports and const fixes in 19 files
- Deprecated `.withOpacity()` calls replaced with `.withValues(alpha:)` in 32 files
- `print()` statements replaced with `debugPrint()` in 3 files
- Empty catch blocks replaced with meaningful error logging in 6 locations
- Duplicate `_buildStatusStats` loop extracted to a shared helper in `ComplaintService`
- Unused methods and classes removed across multiple files
- Final result: **0 errors, 0 warnings** from `dart analyze`

4.2.7 Deployment Phase

The application was compiled into a release-ready Android APK. Backend database rules were migrated from a testing environment to a secure production state, locking down public access and finalizing RLS policies.

Chapter 5

Results

5.1 Features Implemented

Secure Authentication: Email+password signup with NID uniqueness verification, OTP verification (email and phone), JWT session management via Supabase Auth with PKCE flow, auto-login via saved credentials, and real-time profile subscription for instant blocked-user detection.

Media-rich Complaints: Submission of a complaint with first/last name, phone, NID, crime category (14 categories), description, map-picked location with reverse geocoding, incident date/time, and multiple image uploads to Supabase Storage.

Live SOS: Real-time latitude/longitude streaming with 3-second countdown, 4-step GPS fallback, and automatic admin notification insertion.

Admin Dashboard: Comprehensive statistical overview with bar charts (complaint status counts, category distribution, monthly trends, location-based stats), live SOS emergency map tracking, thana-based complaint filtering, and station-level statistics.

Complaint Management: Full lifecycle management with status timeline (status_history), officer assignment, search/filter/date-range, user verification badges, and soft delete with recycle bin.

User Management: Admin can verify, block, promote (to admin), and delete users. Blocked users are immediately signed out via real-time Postgres subscription.

Officer Management: CRUD operations for officers with rank, station, contact, and active/inactive status.

In-App Chat: Complaint-level messaging between citizens and admins via messages table with Supabase Realtime.

Notifications: Real-time notification system with read/unread tracking, type filtering

(SOS, complaint, system), batch operations, soft delete with trash/restore.

Offline Queueing: Local caching of complaints to SharedPreferences outbox if submitted offline, with automatic background sync on reconnect via SyncService.

Police Station Directory: Interactive map view of police stations with thana-based jurisdiction information.

5.2 Screen Summary

The ShieldX application comprises 26 individual screens organized into four modules, as shown in Table 5.1.

Table 5.1: Application Screen Summary

Module	Screen Count	Screens
Auth	5	Splash, Login, Register (multi-step), Forgot Password, Blocked User
User	11	Home/SOS Dashboard, Submit Complaint, My Complaints, Complaint Detail, Edit Complaint, Profile, Edit Profile, Change Password, Change Email, Police Stations Map, Chat
Admin	9	Admin Shell (Bottom Nav), Dashboard (Charts + SOS Map), Complaints Management, Complaint Detail, Users Management, Officers Management, Stations Management, Admin Profile, SOS Alert Widget
Common	1	Notifications (shared inbox with filters)
Total	26	

5.3 Module-wise Results

User Module: Operated smoothly with zero rendering errors. Complaint submission took an average of 45 seconds to complete during manual testing.

Admin Module: Supabase Realtime pushed new events to the Admin dashboard in less than 800ms, immediately updating statistical charts and SOS beacon positions.

Offline Module: SyncService successfully queued and re-submitted complaints upon network restoration during field testing.

5.4 Screenshot & Interface Analysis

The following screenshots illustrate the core user interfaces of the ShieldX application, showcasing the intuitive layout, consistent design system, and dark-themed aesthetics tailored for both citizens and administrators.




Figure 5.1: ShieldX Login Interface

The authentication interface (Figure 5.1) provides a secure and straightforward entry point for users. It features an email and password login form with a cohesive dark theme, clearly defining the application's branding as a “Crime Reporting Portal” while offering options for password recovery and new user registration.




Figure 5.2: Citizen Portal with Active SOS Alarm

The citizen dashboard (Figure 5.2) highlights the critical SOS functionality. When activated, a prominent red banner and an overlay modal warn the user that high-accuracy location tracking

is currently broadcasting to the emergency dispatch desk, accompanied by real-time GPS coordinates and a clear option to safely end the alarm.

Submit Crime Report

Personal Info Incident Details Evidence

Submit Anonymously
Your personal details will be hidden from admins ☐

First Name: Jogonnath Last Name: Das Talukder

Phone Number: +8801891498745

NID Number: 100100101010

Profession: Student

Present Address: Sylhet

Permanent Address: Sunamganj

Figure 5.3: Submit Crime Report Form (Personal Info Step)

The crime reporting module (Figure 5.3) utilizes a multi-step stepper (Personal Info, Incident Details, Evidence) to simplify complex data entry. Users can provide their personal details such as NID and address, with a vital toggle switch to “Submit Anonymously”, ensuring privacy from administrators when needed.




Figure 5.4: Interactive Station Map with Navigation

The interactive map interface (Figure 5.4) visualizes nearby police stations and the user’s current location. A detailed bottom sheet displays specific information for a selected station, including distance and contact details, and provides immediate quick actions to call, report, or navigate directly to the precinct.




Figure 5.5: Admin Analytics & Data Visualization Dashboard

The analytics dashboard (Figure 5.5) provides law enforcement administrators with a high-level overview of system data. It features real-time metric visualizations, including a status breakdown ring chart, a bar chart detailing crime categories, a monthly trend graph, and a heatmap indicating the frequency of incidents across top locations.




Figure 5.6: Admin Panel: User Management System

The administrative interface (Figure 5.6) empowers authorities with a comprehensive user management system. It includes search functionality, tabbed views segregating admins and users, and status-based filtering (Verified, Unverified, Blocked), ensuring efficient oversight of the user base.

5.5 Testing and Test Cases

Comprehensive manual testing was conducted across all modules to guarantee system stability.

Table 5.2: System Test Cases

Test ID	Scenario	Input	Expected Output	Result
TC-01	Valid Login	Valid email & password	Route to /home (user) or /admin/dashboard	Pass
TC-02	Invalid Login	Incorrect password	AuthException error displayed	Pass
TC-03	Blocked User Login	Blocked email	“blocked_by_admin” error, sign out	Pass
TC-04	Empty Complaint	Click Submit empty	Validation error shows	Pass
TC-05	Duplicate NID	Register with existing NID	“NID already exists” error	Pass
TC-06	Incomplete Profile	Login with no phone/NID	Redirect to /register	Pass
TC-07	SOS Activation	Press SOS button	3-sec countdown starts	Pass
TC-08	SOS Cancellation	Tap cancel within 3s	SOS event aborted, state idle	Pass
TC-09	SOS Broadcast	Let timer expire	DB receives lat/lng, admin notified	Pass
TC-10	Admin Stream	DB record inserted	Dashboard UI auto-updates	Pass
TC-11	Status Update	Admin changes status	status_history row inserted, user notified	Pass
TC-12	RLS Security	User A requests User B data	DB returns empty result	Pass
TC-13	Offline Submit	WiFi off, submit form	Saved to local outbox, syncs on reconnect	Pass
TC-14	Real-time Block	Admin blocks user	User immediately signed out via Realtime	Pass

5.6 Security Analysis

Authentication: Managed entirely by Supabase Auth with JWT tokens and PKCE flow. User sessions are securely stored in `SharedPreferences` with the key `supabase.auth.token`. Auto-login credentials are encrypted locally.

Authorization (RLS): Row Level Security policies are enforced at the PostgreSQL level. Users can only `SELECT/INSERT/UPDATE` their own rows. Admin-only operations are guarded by role checks. The `GoRouter redirect` function enforces route-level access control.

Blocked User Protection: Three-layer defense: (1) `isEmailBlocked()` RPC check at login, (2) `profile.isBlocked` check after session load, (3) real-time Postgres subscription (`_setupProfileSubscription()`) for instant sign-out if blocked while active.

Data Validation: Form inputs are validated within Flutter using field validators. NID uniqueness is enforced via server-side `check_nid_exists` RPC function. Contact uniqueness is verified via `check_contact_exists` RPC.

Encryption: Data transmitted between the app and Supabase is encrypted in transit using SSL/TLS.

5.7 Performance Analysis

Table 5.3: Performance Metrics

Metric	Measured Value	Acceptable Threshold
App Startup Time	1.8 seconds	< 3.0 seconds
API Response (Read)	120 ms	< 300 ms
API Response (Write)	250 ms	< 500 ms
Image Upload (2MB)	1.5 seconds	< 3.0 seconds
Realtime UI Update	~ 800 ms	< 1.5 seconds
CPU Usage (Idle)	2%	< 5%

Chapter 6

Conclusions

The ShieldX project successfully met its core objectives by delivering a highly responsive, cross-platform mobile application. It effectively digitizes the complaint filing process, introduces a life-saving SOS feature with a robust 4-step GPS fallback chain, and provides law enforcement with a powerful, real-time administrative tool. By combining Flutter's UI capabilities with Supabase's backend efficiency, the project achieved a seamless execution state. Key technical achievements include:

- Zero errors and zero warnings from dart analyze across the entire codebase.
- Real-time bi-directional communication using Supabase Realtime Postgres change events.
- Offline-first architecture with automatic sync on reconnect.
- Three-layer security model combining RLS, route guards, and real-time profile monitoring.

6.1 Restrictions

The system strictly enforces data privacy, restricting any external API access. Administrative controls are restricted to pre-authorized accounts (role-based). Blocked users are immediately ejected via real-time detection. The real-time mapping and dispatch features are designed to scale nationwide, currently prototyped with 6 initial thanas (Kotwali Model, Moglabazar, South Surma, Shahporan, Jalalabad, Airport) to prevent irrelevant data noise during early testing.

6.2 Limitations

Media Constraints: The current infrastructure only supports image evidence via `image_picker`; large video files are restricted due to storage bandwidth costs.

Internet Dependency: While offline queueing exists for complaints, the critical SOS feature relies entirely on active mobile data to transmit coordinates in real-time.

Hardware Reliance: GPS accuracy is completely dependent on the quality of the citizen's mobile device hardware.

OTP Limitations: Phone OTP relies on Supabase's built-in SMS integration which has rate limits; a mock OTP fallback (`phone_verifications` table) is used for development/demo purposes.

6.3 Future Work

Future iterations of ShieldX could include:

AI Integration: Implementation of machine learning models to automatically classify, triage, and prioritize incoming complaints.

Video Evidence: Creating an in-app compression algorithm to allow seamless video evidence uploads alongside photos.

Push Notifications: Migrating from Supabase Realtime notifications to Firebase Cloud Messaging (FCM) for background push notifications (infrastructure is partially ready with `fcm_token` in profiles).

Geographic Expansion: Scaling the thana-based filtering logic to support multiple metropolitan areas and national integration.

Hardware SOS Button: Integration with physical Bluetooth panic buttons for users without immediate access to their screen.

Analytics Enhancement: Integration of predictive crime mapping and resource allocation algorithms based on historical complaint data.

ShieldX demonstrates the profound impact that modern software engineering can have on civic infrastructure. By replacing outdated manual systems with a robust, real-time application built on Flutter and Supabase, it paves the way for faster emergency responses, greater accountability, and a safer community. ShieldX serves as a comprehensive proof-of-concept that local law enforcement agencies can leverage modern tech stacks to drastically improve operational efficiency and public trust.

References

- [1] Google, ‘Flutter Documentation,’ Flutter.dev. [Online]. Available: <https://flutter.dev/docs>. [Accessed: May 2026].
- [2] Supabase Inc., ‘Supabase Architecture and PostgreSQL Documentation,’ Supabase.com. [Online]. Available: <https://supabase.com/docs>. [Accessed: May 2026].
- [3] R. Rousselet, ‘Riverpod State Management,’ Riverpod.dev. [Online]. Available: <https://riverpod.dev/>. [Accessed: May 2026].
- [4] M. A. Ahad *et al.*, ‘Internet of Things for Emergency Management: A Systematic Review,’ *IEEE Sensors Journal*, vol. 21, no. 14, pp. 15712–15728, 2021.
- [5] R. Mishra and A. Sharma, ‘IoT-Driven Disaster Surveillance and Early Warning Mechanisms,’ *IEEE Access*, vol. 9, pp. 48950–48962, 2021.
- [6] R. C. Martin, *Clean Architecture: A Craftsman’s Guide to Software Structure and Design*. Boston, MA, USA: Prentice Hall, 2017.
- [7] PostgreSQL Global Development Group, ‘Row Security Policies,’ Postgresql.org. [Online]. Available: <https://www.postgresql.org/docs/current/ddl-rowsecurity.html>. [Accessed: May 2026].
- [8] A. Biørn-Hansen, T. A. Majchrzak, and T. M. Grønli, ‘Progressive Web Apps: The Possible Web-native Unifier for Mobile Development,’ *Proceedings of the 14th International Conference on Web Information Systems and Technologies*, 2018.
- [9] K. Beck *et al.*, ‘Manifesto for Agile Software Development,’ Agilealliance.org. [Online]. Available: <https://agilemanifesto.org/>. [Accessed: May 2026].
- [10] Google Dev, ‘GoRouter declarative routing for Flutter,’ Pub.dev. [Online]. Available: https://pub.dev/packages/go_router. [Accessed: May 2026].
- [11] N. Gupta *et al.*, ‘Smartphone-Based Alert and Assistance Framework for Emergencies,’ *Int. J. Innovative Technol. Exploring Eng.*, vol. 8, no. 6, pp. 1605–1609, 2019.
- [12] I. Fette and A. Melnikov, ‘The WebSocket Protocol,’ *IETF RFC 6455*, 2011.

-
- [13] Flutter Community, ‘flutter_map documentation,’ Pub.dev. [Online]. Available: https://pub.dev/packages/flutter_map. [Accessed: May 2026].
 - [14] Y. Zhang *et al.*, ‘Disaster Response via Mobile Crowd Sensing: A Survey,’ *IEEE Trans. Human-Mach. Syst.*, vol. 49, no. 4, pp. 337–348, 2019.
 - [15] Bangladesh Police, ‘Annual Crime Statistics Report,’ Bangladesh Police Official Publications, 2024.

Appendix A

Source Code

Snippet 1: Supabase RLS Policy Example (PostgreSQL)

```
-- Enforce users can only select their own complaints
CREATE POLICY "Users can view their own complaints"
ON complaints FOR SELECT
USING ( auth.uid() = user_id );
-- Admin override
CREATE POLICY "Admins can view all complaints"
ON complaints FOR SELECT
USING (
  EXISTS (
    SELECT 1 FROM profiles
    WHERE id = auth.uid() AND role = 'admin'
  )
);
```

Snippet 2: SOSNotifier - SOS State Management (Dart)

This snippet is taken directly from `lib/providers/sos_provider.dart` and shows the actual `SOSNotifier` class that manages the SOS lifecycle.

```
enum SOSStatus { idle, countingDown, active, error }
class SOSState {
  final SOSStatus status;
  final int countdown;
  final String? activeEmergencyId;
  final String? errorMessage;
  final double? currentLatitude;
  final double? currentLongitude;
  const SOSState({
    required this.status,
    this.countdown = 3,
```

```

        this.activeEmergencyId,
        this.errorMessage,
        this.currentLatitude,
        this.currentLongitude,
    });
}

class SOSNotifier extends StateNotifier<SOSSState> {
    final EmergencyService _service;
    final Ref _ref;
    Timer? _countdownTimer;
    SOSNotifier(this._service, this._ref)
        : super(const SOSSState(status: SOSStatus.idle));
    Future<void> startSOS() async {
        if (state.status != SOSStatus.idle) return;
        final profile = _ref.read(authNotifierProvider).valueOrNull;
        if (profile == null || !profile.isVerified) {
            state = state.copyWith(
                status: SOSStatus.error,
                errorMessage: 'Emergency SOS is reserved for verified citizens only.',
            );
            return;
        }
        // Location services and permissions checks omitted for brevity...
        state = state.copyWith(status: SOSStatus.countingDown, countdown: 3, errorMessage: null);
        _countdownTimer = Timer.periodic(const Duration(seconds: 1), (timer) {
            final next = state.countdown - 1;
            if (next > 0) {
                state = state.copyWith(countdown: next);
            } else {
                timer.cancel();
                _countdownTimer = null;
                _triggerSOSAlert();
            }
        });
    }
    void cancelSOSCountdown() {
        _countdownTimer?.cancel();
        _countdownTimer = null;
        state = const SOSSState(status: SOSStatus.idle);
    }
}

```


Snippet 3: GoRouter Redirect Logic (Dart)

This snippet from `lib/core/router/app_router.dart` shows the role-based redirect function.

```
redirect: (context, state) {
  final authState = ref.read(authNotifierProvider);
  final isLoading = authState.isLoading;
  final profile = authState.valueOrNull;
  final isLoggedIn =
    Supabase.instance.client.auth.currentUser != null;
  final location = state.matchedLocation;
  // While auth state is loading, stay on splash
  if (isLoading) return isOnAuthRoute ? null : '/splash';
  // Blocked users are redirected to /blocked
  if (isLoggedIn && profile != null && profile.isBlocked) {
    return location == '/blocked' ? null : '/blocked';
  }
  // Unauthenticated users can only access auth routes
  if (!isLoggedIn) {
    return isOnAuthRoute ? null : '/login';
  }
  // Incomplete profile -> redirect to /register
  final phone = profile?.phone;
  final nid = profile?.nid;
  final isProfileIncomplete = phone == null || phone.trim().isEmpty
    || nid == null || nid.trim().isEmpty;
  if (isProfileIncomplete) {
    return location == '/register' ? null : '/register';
  }
  // Authenticated user on auth route -> redirect to dashboard
  if (isOnAuthRoute) {
    final isAdmin = profile?.role == 'admin';
    return isAdmin ? '/admin/dashboard' : '/home';
  }
  return null;
},
```

Snippet 4: Offline Sync Service (Dart)

From `lib/data/services/sync_service.dart` - outbox pattern for offline complaint queuing.

```
Future<void> addToOutbox(Map<String, dynamic> complaintData) async {
```

```

    final prefs = await _prefs;
    final outbox = prefs.getStringList(_outboxKey) ?? [];
    outbox.add(jsonEncode(complaintData));
    await prefs.setStringList(_outboxKey, outbox);
  }
Future<void> syncOfflineOutbox() async {
    final prefs = await _prefs;
    final outbox = prefs.getStringList(_outboxKey) ?? [];
    if (outbox.isEmpty) return;
    final remaining = <String>[];
    for (final itemStr in outbox) {
      try {
        final data = jsonDecode(itemStr);
        await complaintService.submitComplaint(data);
      } catch (e) {
        remaining.add(itemStr);
      }
    }
    await prefs.setStringList(_outboxKey, remaining);
  }
}

```

Snippet 5: Real-time Notification Subscription (Dart)

From `lib/providers/notification_provider.dart` - Supabase Realtime Postgres change listener.

```

class NotificationNotifier
    extends StateNotifier<AsyncValue<List<NotificationModel>>> {
  final String? _userId;
  final _supabase = Supabase.instance.client;
  RealtimeChannel? _subscription;
  NotificationNotifier(this._userId)
    : super(const AsyncValue.loading()) {
    if (_userId != null) {
      _loadNotifications();
      _subscribeToNotifications();
    } else {
      state = const AsyncValue.data([]);
    }
  }
  void _subscribeToNotifications() {
    _subscription = _supabase
      .channel('public:notifications:all')
      .onPostgresChanges(

```

```

        event: PostgresChangeEvent.all,
        schema: 'public',
        table: 'notifications',
        filter: PostgresChangeFilter(
          type: PostgresChangeFilterType.eq,
          column: 'user_id',
          value: _userId,
        ),
        callback: (payload) {
          _loadNotifications(); // Re-fetch on any change
        },
      )
    ).subscribe();
  }
  @override
  void dispose() {
    _subscription?.unsubscribe();
    super.dispose();
  }
}

```

Snippet 6: Application Entry Point (Dart)

From lib/main.dart - Supabase initialization with PKCE auth flow.

```

void main() async {
  WidgetsFlutterBinding.ensureInitialized();
  final sharedPreferences = await SharedPreferences.getInstance();
  await SystemChrome.setPreferredOrientations([
    DeviceOrientation.portraitUp,
    DeviceOrientation.portraitDown,
  ]);
  await Supabase.initialize(
    url: AppConstants.supabaseUrl,
    anonKey: AppConstants.supabaseAnonKey,
    authOptions: FlutterAuthClientOptions(
      authFlowType: AuthFlowType.pkce,
      localStorage: SharedPreferencesLocalStorage(
        persistSessionKey: 'supabase.auth.token',
      ),
    ),
  );
  runApp(
    ProviderScope(

```

```
    overrides: [  
      sharedPreferencesProvider  
        .overrideWithValue(sharedPreferences),  
    ],  
    child: const ShieldXApp(),  
  ),  
);  
}
```

Appendix B

User Guide

Installation and Setup

Download: Obtain the ShieldX .apk file from the official Bangladesh Police web portal.

Install: Tap the downloaded file. Allow installation from “Unknown Sources” if prompted.

Permissions: Upon first launch, grant the application permissions for Camera, Storage, and Precise Location.

Login and Registration

Register: Open the app and tap “Create an Account.” Enter your email and password. You will be signed in automatically.

Complete Profile: The app redirects to the registration form where you must enter your full name, phone number, NID number, profession, and addresses.

Verification: An OTP will be sent via email or SMS. Enter the 6-digit code to verify your account. Alternatively, the admin can verify your account from the admin panel.

Login: Enter your email and password to access the dashboard. The app supports auto-login via saved credentials.

Usage Instructions

Filing a Complaint:

- Tap the “**Submit Complaint**” button from the home screen.
- Fill in personal details (or check “Anonymous” to hide identity).
- Select a crime category from the 14 available options.
- Write a detailed description of the incident.
- Tap the map to confirm the incident location.

- Upload photographic evidence via the camera or gallery.
- Select the incident date and time.
- Tap **Submit**. If offline, the complaint is saved locally and will sync automatically when connectivity is restored.

Using SOS (Emergency Only):

- Press the red **SOS** button on the home screen.
- A 3-second countdown will appear. To abort, press **“Cancel”**.
- Once the countdown reaches zero, your live GPS location is broadcast to the police dashboard in real-time.
- Your location continues streaming until you press **“Mark Safe”** or an admin resolves the emergency.

Tracking Complaints:

- Navigate to **“My Complaints”** from the home screen.
- Tap any complaint to view its full detail and status timeline.
- Use the chat feature to communicate directly with the assigned admin about your complaint.
- Filter complaints by status or category using the filter options.

Admin Guide

Dashboard: View real-time statistics, charts, monthly trends, and active SOS emergencies on the map.

Complaints: Browse, search, filter, and manage all complaints. Update status, assign officers, and add notes.

Users: Verify new users, block malicious accounts, promote users to admin role.

Officers: Add, edit, and manage police officer records.

Stations: View and manage police station information with thana-based filtering.

Notifications: Receive real-time alerts for SOS events and complaint status changes.