
October 11, 2026

Vulnerability Scan Report



HostedScan Security

hostedscan.com

Table of Contents

1.0 Executive Summary 3

2.0 Trends 4

3.0 Vulnerabilities By Target 6

4.0 Passive Web Application Vulnerabilities 9

5.0 SSL/TLS Security 21

6.0 Open TCP Ports 22

7.0 Open UDP Ports 25

8.0 Nuclei Vulnerabilities 26

9.0 Glossary 27

1.0 Executive Summary

Vulnerability scans were conducted on select servers, networks, websites, and applications. This report contains the discovered potential vulnerabilities from these scans. Vulnerabilities have been classified by severity. Higher severity indicates a greater risk of a data breach, loss of integrity, or availability of the targets.

1.1 Total Vulnerabilities

Below are the total number of vulnerabilities found by severity. Critical vulnerabilities are the most severe and should be evaluated first. An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive detection or an intentional part of the system's architecture.

Critical	High	Medium	Low	Accepted
0	1	5	6	0



1.2 Report Coverage


This report includes findings for **1 target** scanned. Each target is a single URL, IP address, or fully qualified domain name (FQDN).

1 Total Targets	10 Passive Web Application Vulnerabilities	0 SSL/TLS Security	2 Open TCP Ports
0 Open UDP Ports	0 Nuclei Vulnerabilities		

2.0 Trends


2.1 Open Risks

Total number of vulnerabilities grouped by severity level.




2.2 Exposure Window

Total number of unresolved vulnerabilities grouped by age (time since first detection).



2.3 Health Score

Total score based on the cumulated risks for all targets.



3.0 Vulnerabilities By Target

This section contains the vulnerability findings for each scanned target. Prioritization should be given to the targets with the highest severity vulnerabilities. However, it is important to take into account the purpose of each system and consider the potential impact a breach or an outage would have for the particular target.

3.1 Targets Summary (1)

The number of potential vulnerabilities found for each target by severity.

Target	Critical	High	Medium	Low	Accepted
https://1441pizzeria.dotpe.in/store/6/delivery	0	1	5	6	0

3.2 Target Breakdowns

Details for the potential vulnerabilities found for each target by scan type.

B https://1441pizzeria.dotpe.in/store/6/delivery

Scans run: Nmap | Nuclei | Nmap UDP | ZAP Passive | SSLyze

Total Risks

0	1	5	6	0



Passive Web Application Vulnerabilities Last scanned: 10/11/2026	Severity	First Detected
Vulnerable JS Library: swiper 8.4.4	High	10/11/2026
Sub Resource Integrity Attribute Missing	Medium	10/11/2026
CSP: Failure to Define Directive with No Fallback	Medium	10/11/2026
CSP: Wildcard Directive	Medium	10/11/2026
CSP: script-src unsafe-inline	Medium	10/11/2026
CSP: style-src unsafe-inline	Medium	10/11/2026
Cross-Domain JavaScript Source File Inclusion	Low	10/11/2026
X-Content-Type-Options Header Missing	Low	10/11/2026
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Low	10/11/2026
Strict-Transport-Security Header Not Set	Low	10/11/2026
Open TCP Ports Last scanned: 10/11/2026	Severity	First Detected
Open TCP Port: 80	Low	10/11/2026
Open TCP Port: 443	Low	10/11/2026

Nuclei Vulnerabilities
Last scanned: 10/11/2026

Severity	First Detected
No vulnerabilities found.	

Open UDP Ports
Last scanned: 10/11/2026

Severity	First Detected
No vulnerabilities found.	

SSL/TLS Security
Last scanned: 10/11/2026

Severity	First Detected
No vulnerabilities found.	

HostedScan Free Trial Report

4.0 Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

4.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

4.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	1	5	4	0



4.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
Vulnerable JS Library: swiper 8.4.4	High	1	0
Sub Resource Integrity Attribute Missing	Medium	1	0
CSP: Failure to Define Directive with No Fallback	Medium	1	0
CSP: Wildcard Directive	Medium	1	0
CSP: script-src unsafe-inline	Medium	1	0
CSP: style-src unsafe-inline	Medium	1	0
Cross-Domain JavaScript Source File Inclusion	Low	1	0
X-Content-Type-Options Header Missing	Low	1	0
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Low	1	0
Strict-Transport-Security Header Not Set	Low	1	0

4.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

Vulnerable JS Library: swiper 8.4.4

SEVERITY	AFFECTED TARGETS	LAST DETECTED
High	1 target	15 minutes ago

Description

The identified library appears to be vulnerable.

Solution

Upgrade to the latest version of the affected library.

Instances (1 of 1)

uri: https://cdn.dotpe.in/static/assets/js/swiper/swiper-bundle.min.js
method: GET
evidence: * Swiper 8.4.4
otherinfo: The identified library swiper, version 8.4.4 is vulnerable. CVE-2026-27212
https://github.com/nolimits4web/swiper/security/advisories/GHSA-hmx5-qpq5-p643
https://github.com/nolimits4web/swiper/commit/d3e663322a13043ca63aaba235d8cf3900e0c8cf
https://github.com/nolimits4web/swiper/releases/tag/v12.1.2

References

https://owasp.org/Top10/2021/A06_2021-Vulnerable_and_Outdated_Components/

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

Sub Resource Integrity Attribute Missing

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	15 minutes ago

Description

The integrity attribute is missing on a script or link tag served by an external server. The integrity tag prevents an attacker who have gained access to this server from injecting a malicious content.

Solution

Provide a valid integrity attribute to the tag.

Instances (1 of 5)

uri: https://1441pizzeria.dotpe.in/store/6/delivery
method: GET
evidence: <link href="https://fonts.googleapis.com/css?family=Encode+Sans:400,500,600,700&display=swap" rel="preload">

References

https://developer.mozilla.org/en-US/docs/Web/Security/Defenses/Subresource_Integrity

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

CSP: Failure to Define Directive with No Fallback

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	15 minutes ago

Description

The Content Security Policy fails to define one of the directives that has no fallback. Missing/excluding them is the same as allowing anything.

Solution

Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/order
method: GET
param: Content-Security-Policy
evidence: frame-ancestors 'self' https://showroom.dotpe.in https://showroom.digitaldukaan.app;
otherinfo: The directive(s): form-action is/are among the directives that do not fallback to default-src.

References

https://www.w3.org/TR/CSP/
https://caniuse.com/#search=content+security+policy
https://content-security-policy.com/
https://github.com/HtmlUnit/htmlunit-csp
https://web.dev/articles/csp#resource-options

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

CSP: Wildcard Directive

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	15 minutes ago

Description

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

Solution

Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/order
method: GET
param: Content-Security-Policy
evidence: frame-ancestors 'self' https://showroom.dotpe.in https://showroom.digitaldukaan.app;
otherinfo: The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: script-src, style-src, img-src, connect-src, frame-src, font-src, media-src, object-src, manifest-src, worker-src

References

https://www.w3.org/TR/CSP/
https://caniuse.com/#search=content+security+policy
https://content-security-policy.com/
https://github.com/HtmlUnit/htmlunit-csp
https://web.dev/articles/csp#resource-options

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

CSP: script-src unsafe-inline

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	15 minutes ago

Description

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

Solution

Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/order
method: GET
param: Content-Security-Policy
evidence: frame-ancestors 'self' https://showroom.dotpe.in https://showroom.digitaldukaan.app;
otherinfo: script-src includes unsafe-inline.

References

https://www.w3.org/TR/CSP/
https://caniuse.com/#search=content+security+policy
https://content-security-policy.com/
https://github.com/HtmlUnit/htmlunit-csp
https://web.dev/articles/csp#resource-options

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

CSP: style-src unsafe-inline

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	15 minutes ago

Description

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

Solution

Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/order
method: GET
param: Content-Security-Policy
evidence: frame-ancestors 'self' https://showroom.dotpe.in https://showroom.digitaldukaan.app;
otherinfo: style-src includes unsafe-inline.

References

https://www.w3.org/TR/CSP/
https://caniuse.com/#search=content+security+policy
https://content-security-policy.com/
https://github.com/HtmlUnit/htmlunit-csp
https://web.dev/articles/csp#resource-options

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

Cross-Domain JavaScript Source File Inclusion

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

The page includes one or more script files from a third-party domain.

Solution

Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.

Instances (1 of 5)

uri: https://1441pizzeria.dotpe.in/sitemap.xml
method: GET
param: https://cdn.dotpe.in/static/assets/js/swiper/swiper-bundle.min.js
evidence: <script src="https://cdn.dotpe.in/static/assets/js/swiper/swiper-bundle.min.js"></script>

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

X-Content-Type-Options Header Missing

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.

Solution

Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages.

If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application/web server to not perform MIME-sniffing.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/manifest.json
method: GET
param: x-content-type-options
otherinfo: This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.

References

https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)
https://owasp.org/www-community/Security_Headers

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

The web/application server is leaking information via one or more "X-Powered-By" HTTP response headers. Access to such information may facilitate attackers identifying other frameworks/components your web application is reliant upon and the vulnerabilities such components may be subject to.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to suppress "X-Powered-By" headers.

Instances (1 of 5)

uri: https://1441pizzeria.dotpe.in/favicon.ico
method: GET
evidence: X-Powered-By: Express

References

https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework
https://www.troyhunt.com/shhh-dont-let-your-response-headers/

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

Strict-Transport-Security Header Not Set

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

HTTP Strict Transport Security (HSTS) is a web security policy mechanism whereby a web server declares that complying user agents (such as a web browser) are to interact with it using only secure HTTPS connections (i.e. HTTP layered over TLS/SSL). HSTS is an IETF standards track protocol and is specified in RFC 6797.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.

Instances (1 of 3)

uri: https://1441pizzeria.dotpe.in/manifest.json
method: GET

References

https://cheatsheetseries.owasp.org/cheatsheets/HTTP_Strict_Transport_Security_Cheat_Sheet.html
https://owasp.org/www-community/Security_Headers
https://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security
https://caniuse.com/stricttransportsecurity
https://datatracker.ietf.org/doc/html/rfc6797

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

5.0 SSL/TLS Security

The SSLyze security scan tests for misconfigured SSL/TLS certificates, expired certificates, weak ciphers, and SSL/TLS vulnerabilities such as Heartbleed.

5.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

5.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	0	0

5.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
No vulnerabilities detected			

6.0 Open TCP Ports

The NMAP TCP port scan discovers open TCP ports with a complete scan of ports 0 to 65535.

6.1 Scan Coverage

Shows how recently the included targets were last scanned.

0	0	0	1
Never scanned	More than 90 days ago	Last 90 days	Last 30 days

6.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	2	0

100%

6.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
Open TCP Port: 80	Low	1	0
Open TCP Port: 443	Low	1	0

6.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

Open TCP Port: 80

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

An open port may be an expected configuration. For example, web servers use port 80 to serve websites over http and port 443 to serve websites over https. For a list of commonly used ports see https://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers.

An unexpected open port could give unintended access to applications, data, and private networks. Open ports can also be dangerous when expected services are out of date and exploited through security vulnerabilities.

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

Open TCP Port: 443

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	15 minutes ago

Description

An open port may be an expected configuration. For example, web servers use port 80 to serve websites over http and port 443 to serve websites over https. For a list of commonly used ports see https://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers.

An unexpected open port could give unintended access to applications, data, and private networks. Open ports can also be dangerous when expected services are out of date and exploited through security vulnerabilities.

Vulnerable Target	First Detected	Last Detected
https://1441pizzeria.dotpe.in/store/6/delivery	10/11/2026	10/11/2026

7.0 Open UDP Ports

The NMAP UDP port scan discovers open ports of common UDP services

7.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

7.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	0	0

7.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
No vulnerabilities detected			

8.0 Nuclei Vulnerabilities

Fast vulnerability scanner powered by the community-driven template engine. Detects CVEs, misconfigurations, and security issues across web applications and infrastructure.

8.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

8.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	0	0

8.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
No vulnerabilities detected			

9.0 Glossary

Accepted Vulnerability

An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive scan result or an intentional part of the system's architecture.

Active Web Application Vulnerabilities

The OWASP ZAP Active Web Application scan crawls the pages of a website or web application testing for vulnerabilities and configuration weaknesses. The active scan includes all of the passive scan tests and additionally makes requests and submits forms to actively test an application for more vulnerabilities. The active scan tests for vulnerabilities such as SQL injection, remote command execution, XSS, and more.

Fully Qualified Domain Name (FQDN)

A fully qualified domain name is a complete domain name for a specific website or service on the internet. This includes not only the website or service name, but also the top-level domain name, such as .com, .org, .net, etc. For example, 'www.example.com' is an FQDN.

Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

Network Vulnerabilities

The OpenVAS network vulnerability scan tests servers and internet connected devices for over 150,000 vulnerabilities. OpenVAS uses the Common Vulnerability Scoring System (CVSS) to quantify the severity of findings. 0.0 is the lowest severity and 10.0 is the highest.

Open TCP Ports

The NMAP TCP port scan discovers open TCP ports with a complete scan of ports 0 to 65535.

Open UDP Ports

The NMAP UDP port scan discovers open ports of common UDP services

Vulnerability

A weakness in the computational logic (e.g., code) found in software and hardware components that, when exploited, results in a negative impact to confidentiality, integrity, or availability. Mitigation of the vulnerabilities in this context typically involves coding changes, but could also include specification changes or even specification deprecations (e.g., removal of affected protocols or functionality in their entirety).

SSL/TLS Security

The SSLyze security scan tests for misconfigured SSL/TLS certificates, expired certificates, weak ciphers, and SSL/TLS vulnerabilities such as Heartbleed.

Target

A target represents target is a single URL, IP address, or fully qualified domain name (FQDN) that was scanned.

Severity

Severity represents the estimated impact potential of a particular vulnerability. Severity is divided into 5 categories: Critical, High, Medium, Low and Accepted.

CVSS Score

The CVSS 3.0 score is a global standard for evaluating vulnerabilities with a 0 to 10 scale. CVSS maps to threat levels:
0.1 - 3.9 = Low
4.0 - 6.9 = Medium
7.0 - 8.9 = High
9.0 - 10.0 = Critical

EPSS Score

The EPSS score is the estimated probability that a given vulnerability will be exploited in the wild within the next 30 days, on a 0% to 100% scale.



This report was prepared using

HostedScan Security®

For more information, visit hostedscan.com

Founded in Seattle, Washington in 2019, HostedScan, LLC. is dedicated to making continuous vulnerability scanning and risk management much more easily accessible to more businesses.

HostedScan, LLC.

2212 Queen Anne Ave N
Suite #521
Seattle, WA 98109

Terms & Policies
hello@hostedscan.com