Project Proposal

Numerical Simulation of Manufacturing Processes

Axel Fritz, You Ming

Dept. of Mechanical Engineering

2026 年 4 月 13 日

1. Background
2. title
3. References

1 Background
TPMS
Numerical simulations

2 title

3 References

1 Background
TPMS
Numerical simulations

2 title

3 References

Triply Periodic Minimal Surface (TPMS)

TMPS are surfaces with the following mathematical properties [Wik25]:

- Nearly all studied TPMS are free of self-intersections (i.e. embedded in $\mathbb{R}^3$).
- All connected TPMS have genus ≥ 3, and in every lattice there exist orientable embedded TPMS of every genus ≥ 3.
- Embedded TPMS are orientable and divide space into two disjoint sub-volumes (labyrinths).

The mathematical background of TPMS is not particularly relevant for this project, but we will make use of the last property.

Gyroid-TPMS

Discovered by NASA scientist Alan Schoen in 1970, proved to be embedded by Grosse-Brauckmann and Wohlgemuth in 1996 [Wik26]. It is the structure that we will be treating in this project.

- Embedded; divides space into two *disjoint* sub-volumes.
- Can be approximated a the relatively simple equation

$$\sin x \cos y + \sin y \cos z + \sin z \cos x = 0$$





Advantages

TPMS provides a compelling alternative to traditional fin-based heat exchangers.

- High surface-to-volume ratio improves heat exchange.
- Continous TPMS walls generally provide good structural integrity (high stiffness).
- Geometry can be fine by function-based parameters.

The Problem

Dead zones appear in the structure. This causes poor flow utilization, which negatively affects the performance of the heat exchanger.



1 Background
TPMS
Numerical simulations

2 title

3 References

The Solution: Topology Optimization



The Solution: Topology Optimization



Current Methods

There are several ways to evaluate the performance of a given heat exchanger geometry.

- *Body-fitted Mesh* is the 'traditional' method which involves meshing of the structure, and evaluation in a FVM framework.
  - Well documented but computationally expensive for solving and re-meshing.
- *Equivalent porous medium* replaces the TMPS with averaged porous material.
  - Very efficient but relatively poor performance [PBE25]
- *Brinkman penalization* is the method of choice as it can provide sufficient precision in combination with relatively fast results.

1 Background

2 title

3 References

1 Background

2 title

3 References

[PBE25] A.I. Popov, D.M. Bragin, and A.V. Eremin.
Heat and mass transfer in tpms-based porous media: Two-medium approach.
International Journal of Heat and Mass Transfer, 253:127553, 2025.

[Wik25] Wikipedia contributors.
Triply periodic minimal surface — Wikipedia, the free encyclopedia, 2025.
[Online; accessed 13-April-2026].

[Wik26] Wikipedia contributors.
Gyroid — Wikipedia, the free encyclopedia, 2026.
[Online; accessed 13-April-2026].