

Bringing together simulations, physics insight, and machine learning to constrain new physics

Johann Brehmer

New York University

Brandeis University, Dark Universe Seminar

February 28, 2019



Kyle Cranmer



Gilles Louppe



Juan Pavez



Felix Kling



Irina Espejo



Zubair Bhatti




Markus Stoye




Sid Mishra-Sharma



Tilman Plehn




Sally Dawson




Sam Homiller



Josh Rudermann



Duccio Pappadopulo



Marco Farina



The SCAILFIN Project
scailfin.github.io





1. The problem of
likelihood-free inference

2. Existing solutions


3. “Mining gold”: a new approach

4. Learning optimal summary statistics

5. Particle physics example





The problem of “likelihood-free” inference

The Galton board




[galtonboard.com]

The Galton board



[F. Galton 1889]

Probabilities from integrating trajectories



Probability of ending in bin x : $p(x) = \int dz p(x, z)$

Sum over
all trajectories
("latent variables")

Probability of
each path z
from start to x

The generalized Galton board

What if probability to go left at a nail is not always 0.5, but some (known) function of some parameters θ ?

- **Prediction:** given θ , generate samples of observations $\{x_i\}$.

Simple: just drop balls!

The generalized Galton board

What if probability to go left at a nail is not always 0.5, but some (known) function of some parameters θ ?

- **Prediction:** given θ , generate samples of observations $\{x_i\}$.

Simple: just drop balls!


- **Inference:** given observations $\{x_i\}$, what are the most likely values for θ ?

Usually we solve this with the likelihood

$$p(x|\theta) = \int dz \ p(x, z|\theta).$$

But the number of possible **paths** z can be huge, and it becomes impossible to calculate the integral!


“Likelihood-free inference”




Prediction:

- Well-understood mechanistic model
- Simulator can generate samples

“Likelihood-free inference”




“Likelihood-free inference”



Prediction:

- Well-understood mechanistic model
- Simulator can generate samples

“Likelihood-free inference”




Prediction:

- Well-understood mechanistic model
- Simulator can generate samples


Inference:

- Likelihood function $p(x|\theta)$ is intractable
- Inference needs estimator $\hat{p}(x|\theta)$

Galton board: metaphor for simulator-based science



[F. Galton 1889]



[HBO 2018]

Galton board device




Computer simulation

Parameters θ



Model parameters θ

Bins x



Observables x

Path z




Latent variables z

(stochastic execution trace through simulator)

Cosmological N-body simulations




Parameters

θ





Observables

x



[Illustris 1405.2921]


Epidemiology



[D. Brockmann, D. Helbing 2013]

Particle physics



Parameters

 θ


Observables

 x

$$S = \int d^4x \left[\mathcal{L}_{\text{SM}} + \frac{f_{\phi,2}}{\Lambda^2} \frac{1}{2} \partial_\mu (\phi^\dagger \phi) \partial^\mu (\phi^\dagger \phi) + \frac{f_{\phi,3}}{\Lambda^2} \frac{1}{3} (\phi^\dagger \phi)^3 \right. \\ + \frac{f_{GG}}{\Lambda^2} (\phi^\dagger \phi) G_{\mu\nu}^a G^{\mu\nu a} - \frac{f_{BB}}{\Lambda^2} \frac{g'^2}{4} (\phi^\dagger \phi) B_{\mu\nu} B^{\mu\nu} - \frac{f_{WW}}{\Lambda^2} \frac{g^2}{4} (\phi^\dagger \phi) W_{\mu\nu}^a W^{\mu\nu a} \\ + \frac{f_B}{\Lambda^2} \frac{ig'}{2} (D^\mu \phi)^\dagger D^\nu \phi B_{\mu\nu} + \frac{f_W}{\Lambda^2} \frac{ig}{2} (D^\mu \phi)^\dagger \sigma^a D^\nu \phi W_{\mu\nu}^a \\ + \frac{f_\ell}{\Lambda^2} (\phi^\dagger \phi) \bar{L}_L \phi \ell_R + \frac{f_u}{\Lambda^2} (\phi^\dagger \phi) \bar{Q}_L \tilde{\phi} u_R + \frac{f_d}{\Lambda^2} (\phi^\dagger \phi) \bar{Q}_L \phi d_R \\ \left. + \frac{f_{G\widetilde{G}}}{\Lambda^2} (\phi^\dagger \phi) G_{\mu\nu}^a \widetilde{G}^{\mu\nu a} - \frac{f_{B\widetilde{B}}}{\Lambda^2} \frac{g'^2}{4} (\phi^\dagger \phi) B_{\mu\nu} \widetilde{B}^{\mu\nu} - \frac{f_{W\widetilde{W}}}{\Lambda^2} \frac{g^2}{4} (\phi^\dagger \phi) W_{\mu\nu}^a \widetilde{W}^{\mu\nu a} \right]$$



Why has that not stopped us before?


Solve it by histogramming summary statistics

- Typical particle physicists' solution:




Solve it by histogramming summary statistics

- Typical particle physicists' solution:



Solve it by histogramming summary statistics

- Typical particle physicists' solution:




- How to choose x' ? Standard variables often lose information

[JB, K. Cranmer, F. Kling, T. Plehn 1612.05261; JB, F. Kling, T. Plehn, T. Tait 1712.02350]

- “Curse of dimensionality”: Histograms don't scale to high-dimensional x


Solve it with Approximate Bayesian Computation (ABC)

[D. Rubin 1984]




Solve it with Approximate Bayesian Computation (ABC)

[D. Rubin 1984]




Solve it with Approximate Bayesian Computation (ABC)

[D. Rubin 1984]




Solve it with Approximate Bayesian Computation (ABC)

[D. Rubin 1984]



Solve it with Approximate Bayesian Computation (ABC)

[D. Rubin 1984]



- How to choose x' ?
- How to choose ε ?
- No tractable posterior
- Need to run new simulations for new data or new prior

"Curse of dimensionality"
Precision vs efficiency tradeoff

Solve it with machine learning classifiers

[K. Cranmer, J. Pavez, G. Louppe 1506.02169]

Solve it with machine learning classifiers

[K. Cranmer, J. Pavez, G. Louppe 1506.02169]




[M. Yao, idea for analogy: K. Cranmer]

Solve it with machine learning classifiers

[K. Cranmer, J. Pavez, G. Louppe 1506.02169]

- Train neural network (BDT, ...) to tell $x \sim p(x|\theta_0)$ from $x \sim p(x|\theta_1)$
 - Classifier output $\hat{s}(x)$ is closer to 0 for θ_0 -like events (closer to 1 for θ_1 -like events)



Solve it with machine learning classifiers

[K. Cranmer, J. Pavez, G. Louppe 1506.02169]

- Train neural network (BDT, ...) to tell $x \sim p(x|\theta_0)$ from $x \sim p(x|\theta_1)$

- Classifier output $\hat{s}(x)$ is closer to 0 for θ_0 -like events
(closer to 1 for θ_1 -like events)


- Optimal classifier (i.e. minimizing the cross-entropy) converges to

$$s(x) = \frac{p(x|\theta_1)}{p(x|\theta_0) + p(x|\theta_1)} = \frac{1}{1 + \frac{p(x|\theta_0)}{p(x|\theta_1)}} \equiv \frac{1}{1 + r(x|\theta)}$$

- CARL: Turn (calibrated) classifier output $\hat{s}(x)$ into estimator for the likelihood ratio $r(x) \equiv p(x|\theta_0)/p(x|\theta_1)$:

$$\hat{r}(x) = \frac{1 - \hat{s}(x)}{\hat{s}(x)}$$


⇒ No summary statistics necessary, very fast evaluation... but may require large training samples



An incomplete list of likelihood-free inference methods

Treat simulator as black box:


- Histograms of observables,
Approximate Bayesian Computation
Rely on summary statistics
- Machine learning techniques
Density networks, CARL, autoregressive models,
normalizing flows, ...



An incomplete list of likelihood-free inference methods


Treat simulator as black box:

- Histograms of observables,
Approximate Bayesian Computation
Rely on summary statistics
- Machine learning techniques
Density networks, CARL, autoregressive models,
normalizing flows, ...



Use latent structure:


- Matrix Element Method, Optimal Observables,
Shower Deconstruction, Event Deconstruction
Specific to particle physics: approximate integrand, explicitly
calculate z integral



An incomplete list of likelihood-free inference methods


Treat simulator as black box:

- Histograms of observables,
Approximate Bayesian Computation
Rely on summary statistics
- Machine learning techniques
Density networks, CARL, autoregressive models,
normalizing flows, ...




Use latent structure:

- Matrix Element Method, Optimal Observables,
Shower Deconstruction, Event Deconstruction
Specific to particle physics: approximate integrand, explicitly
calculate z integral
- Mining gold from the simulator
Leverage physics insight + machine learning




**A new approach:
Mining gold from the simulator**

Bird's-eye view



“Mining gold”: Extract additional information from simulator


Bird's-eye view



“Mining gold”: Extract additional information from simulator

Use this information to train estimator for likelihood ratio


Bird's-eye view




“Mining gold”: Extract additional information from simulator

Use this information to train estimator for likelihood ratio

Limit setting with standard hypothesis tests



Back to the Galton board



- Remember: the likelihood

$$p(x|\theta) = \int dz p(x, z|\theta)$$

is intractable because of the integral over all possible paths z

- But: we can calculate the probability of each individual path


$$p(x, z|\theta) = \prod_{\text{nails } i} p_i(x, z|\theta)$$

and the "joint likelihood ratio" conditional on a particular path

$$r(x, z|\theta_0, \theta_1) \equiv \frac{p(x, z|\theta_0)}{p(x, z|\theta_1)}$$

Generalizing this idea


- Computer simulation typically evolve along a tree-like structure of successive random branchings



Generalizing this idea

- Computer simulation typically evolve along a tree-like structure of successive random branchings
- The probabilities of each branching $p_i(z_i|z_{i-1}, \theta)$ are often clearly defined in the code:

```
if random() > 0.1 + 2.5 * model_parameter:  
    do_one_thing()  
else:  
    do_another_thing()
```




Generalizing this idea


- Computer simulation typically evolve along a tree-like structure of successive random branchings
- The probabilities of each branching $p_i(z_i|z_{i-1}, \theta)$ are often clearly defined in the code:

```
if random() > 0.1 + 2.5 * model_parameter:  
    do_one_thing()  
else:  
    do_another_thing()
```

- For each run of the simulator, we can calculate the probability **of the chosen path** for different values of the parameters, and the “**joint likelihood ratio**”:

$$r(x, z|\theta_0, \theta_1) = \frac{p(x, z|\theta_0)}{p(x, z|\theta_1)} = \prod_i \frac{p(z_i|z_{i-1}, \theta_0)}{p(z_i|z_{i-1}, \theta_1)}$$





The value of gold

We can calculate the joint likelihood ratio

$$r(x, z | \theta_0, \theta_1) \equiv \frac{p(x, z_d, z_s, z_p | \theta_0)}{p(x, z_d, z_s, z_p | \theta_1)}$$



We want the likelihood ratio function

$$r(x | \theta_0, \theta_1) \equiv \frac{p(x | \theta_0)}{p(x | \theta_1)}$$

The value of gold

We can calculate the joint likelihood ratio


$$r(x, z | \theta_0, \theta_1) \equiv \frac{p(x, z_d, z_s, z_p | \theta_0)}{p(x, z_d, z_s, z_p | \theta_1)}$$



$r(x, z | \theta_0, \theta_1)$ are scattered around $r(x | \theta_0, \theta_1)$

We want the likelihood ratio function

$$r(x | \theta_0, \theta_1) \equiv \frac{p(x | \theta_0)}{p(x | \theta_1)}$$



The value of gold

We can calculate the joint likelihood ratio

$$r(x, z | \theta_0, \theta_1) \equiv \frac{p(x, z_d, z_s, z_p | \theta_0)}{p(x, z_d, z_s, z_p | \theta_1)}$$



$$\begin{aligned}\mathbb{E}_{z \sim p(z|x, \theta_1)} [r(x, z | \theta_0, \theta_1)] &= \int dz p(z|x, \theta_1) \frac{p(x, z | \theta_0)}{p(x, z | \theta_1)} \\ &= \int dz \frac{p(x, z | \theta_1)}{p(x | \theta_1)} \frac{p(x, z | \theta_0)}{p(x, z | \theta_1)} \\ &= r(x | \theta_0, \theta_1)\end{aligned}$$

We want the likelihood ratio function

$$r(x | \theta_0, \theta_1) \equiv \frac{p(x | \theta_0)}{p(x | \theta_1)}$$

The value of gold

We can calculate the joint likelihood ratio

$$r(x, z|\theta_0, \theta_1) \equiv \frac{p(x, z_d, z_s, z_p|\theta_0)}{p(x, z_d, z_s, z_p|\theta_1)}$$

With $r(x, z|\theta_0, \theta_1)$, we define a functional like

$$L_r[\hat{r}(x|\theta_0, \theta_1)] = \int dx \int dz p(x, z|\theta_1) \left[(\hat{r}(x|\theta_0, \theta_1) - r(x, z|\theta_0, \theta_1))^2 \right].$$

It is minimized by

$$r(x|\theta_0, \theta_1) = \arg \min_{\hat{r}(x|\theta_0, \theta_1)} L_r[\hat{r}(x|\theta_0, \theta_1)]!$$

(And we can sample from $p(x, z|\theta)$ by running the simulator.)

We want the likelihood ratio function

$$r(x|\theta_0, \theta_1) \equiv \frac{p(x|\theta_0)}{p(x|\theta_1)}$$

Machine learning = applied calculus of variations

We can get a precise estimator of the likelihood ratio by numerically minimizing a functional:

$$\hat{r}(x|\theta_0, \theta_1) = \underbrace{\arg \min_{\hat{r}(x|\theta_0, \theta_1)} \int dx \int dz p(x, z|\theta_1) \left[\hat{r}(x|\theta_0, \theta_1) - r(x, z|\theta_0, \theta_1) \right]^2}_{L_r[\hat{r}(x|\theta_0, \theta_1)]}$$

Machine learning = applied calculus of variations

We can get a precise estimator of the likelihood ratio by numerically minimizing a functional:

$$\hat{r}(x|\theta_0, \theta_1) = \arg \min_{\hat{r}(x|\theta_0, \theta_1)} \underbrace{\int dx \int dz p(x, z|\theta_1) [\hat{r}(x|\theta_0, \theta_1) - r(x, z|\theta_0, \theta_1)]^2}_{L_r[\hat{r}(x|\theta_0, \theta_1)]}$$

We do this through machine learning:


- Functional L_r → Loss function

$$\hat{L}_r[\hat{r}(x|\theta_0, \theta_1)] = \frac{1}{N} \sum_{(x_i, z_i) \sim p(x, z|\theta_1)} [\hat{r}(x_i|\theta_0, \theta_1) - r(x_i, z_i|\theta_0, \theta_1)]^2$$


- Variational family $\hat{r}(x|\theta_0, \theta_1)$ → Flexible parametric function (e.g. neural network)
- Exact minimization → Numerical optimization algorithm (e.g. stochastic gradient descent)

A sufficiently expressive neural network efficiently trained in this way with enough data will learn the likelihood ratio function $r(x|\theta_0, \theta_1)$!

Neural networks = universal function approximators





Neural networks = universal function approximators



$$h_i^{(n)} = f \left(\sum_k w_{ik}^{(n)} h_k^{(n-1)} + b_i^{(n)} \right)$$



where the weights $w_{ik}^{(n)}, b_i^{(n)}$ are parameters “trained” by the optimizer







One more piece: the score

- Knowing derivative often helps fitting:



One more piece: the score

- Knowing derivative often helps fitting:



- In our case, the relevant quantity is the **score** $t(x|\theta_0) \equiv \nabla_{\theta} \log p(x|\theta) \Big|_{\theta_0}$.
- The score itself is intractable. But...

Learning the score

Similar to the joint likelihood ratio, from the simulator we can extract the **joint score**

$$t(x, z|\theta_0) \equiv \nabla_{\theta} \log p(x, z_d, z_s, z_p|\theta) \Big|_{\theta_0}$$



We want the **score**

$$t(x|\theta_0) \equiv \nabla_{\theta} \log p(x|\theta) \Big|_{\theta_0}$$

Learning the score

Similar to the joint likelihood ratio, from the simulator we can extract the **joint score**

$$t(x, z|\theta_0) \equiv \nabla_{\theta} \log p(x, z_d, z_s, z_p|\theta) \Big|_{\theta_0}$$



We want the **score**

$$t(x|\theta_0) \equiv \nabla_{\theta} \log p(x|\theta) \Big|_{\theta_0}$$

Given $t(x, z|\theta_0)$,
we define the functional


$$L_t[\hat{t}(x|\theta_0)] = \int dx \int dz \ p(x, z|\theta_0) \left[(\hat{t}(x|\theta_0) - t(x, z|\theta_0))^2 \right].$$

One can show it is minimized by


$$t(x|\theta_0) = \arg \min_{\hat{t}(x|\theta_0)} L_t[\hat{t}(x|\theta_0)].$$

Again, we implement this minimization through machine learning.


Putting the pieces together: RASCAL (Ratio and score approximate likelihood ratio)



Putting the pieces together: RASCAL (Ratio and score approximate likelihood ratio)



Putting the pieces together: RASCAL (Ratio and score approximate likelihood ratio)



A simpler variation:


Learning optimal summary statistics

The local model

[see also J. Alsing, B. Wandelt 1712.00012;
J. Alsing, B. Wandelt, S. Freeney 1801.01497]

- Taylor expansion of $\log p(x|\theta)$ around θ_{ref} :

$$\begin{aligned}\log p(x|\theta) &= \log p(x|\theta_{\text{ref}}) \\ &+ \underbrace{\nabla_{\theta} \log p(x|\theta) \Big|_{\theta_{\text{ref}}}}_{\equiv t(x|\theta_{\text{ref}})} \cdot (\theta - \theta_{\text{ref}}) \\ &+ \mathcal{O}((\theta - \theta_{\text{ref}})^2)\end{aligned}$$



The local model

[see also J. Alsing, B. Wandelt 1712.00012;
J. Alsing, B. Wandelt, S. Freeney 1801.01497]


- Taylor expansion of $\log p(x|\theta)$ around θ_{ref} :

$$\begin{aligned}\log p(x|\theta) &= \log p(x|\theta_{\text{ref}}) \\ &+ \underbrace{\nabla_{\theta} \log p(x|\theta) \Big|_{\theta_{\text{ref}}}}_{\equiv t(x|\theta_{\text{ref}})} \cdot (\theta - \theta_{\text{ref}}) \\ &+ \mathcal{O}((\theta - \theta_{\text{ref}})^2)\end{aligned}$$


⇒ In the neighborhood of θ_{ref} (e.g. close to the SM),
the **score vector** $t(x|\theta_{\text{ref}})$ is the sufficient statistics:
it contains all information on θ

In this part of parameter space, knowing $t(x|\theta_{\text{ref}})$ is
just as powerful as knowing the full function $\log p(x|\theta)$


$t(x|\theta_{\text{ref}})$ does not depend on θ — it's (locally) the most
powerful observable




SALLY (Score approximates likelihood locally)




SALLY (Score approximates likelihood locally)



SALLY (Score approximates likelihood locally)



SALLY (Score approximates likelihood locally)



“The machine learning version of Optimal Observables”:

- Simpler & more robust than RASCAL
- Just as powerful close to θ_{ref} , but can lead to suboptimal limits further away

A family of new inference techniques

Method	Simulate	Extract		NN estimates	Asympt. exact	Generative
		$r(x, z)$	$t(x, z)$			
ROLR	$\theta_0 \sim \pi(\theta), \theta_1$	✓		$\hat{r}(x \theta_0, \theta_1)$	✓	
CASCAL	$\theta_0 \sim \pi(\theta), \theta_1$		✓	$\hat{r}(x \theta_0, \theta_1)$	✓	
ALICE	$\theta_0 \sim \pi(\theta), \theta_1$		✓	$\hat{r}(x \theta_0, \theta_1)$	✓	
RASCAL	$\theta_0 \sim \pi(\theta), \theta_1$	✓	✓	$\hat{r}(x \theta_0, \theta_1)$	✓	
ALICES	$\theta_0 \sim \pi(\theta), \theta_1$	✓	✓	$\hat{r}(x \theta_0, \theta_1)$	✓	
SCANDAL	$\theta \sim \pi(\theta)$		✓	$\hat{p}(x \theta)$	✓	✓
SALLY	θ_{ref}		✓	$\hat{t}(x \theta_{\text{ref}})$	in local approx.	
SALLINO	θ_{ref}		✓	$\hat{t}(x \theta_{\text{ref}})$	in local approx.	




Particle physics example

The legacy of the LHC

- LHC: so far, not so good at discovering unexpected new particles...
but great at making Higgs bosons!

The legacy of the LHC

- LHC: so far, not so good at discovering unexpected new particles...
but great at making Higgs bosons!



[National Geographic]

The legacy of the LHC

- LHC: so far, not so good at discovering unexpected new particles...
but great at making Higgs bosons!
- Precision measurements of Higgs properties & electroweak interactions ~~might~~ will help us understand...
 - the hierarchy problem (why is gravity so weak?)
 - fermion masses (why is the electron so light?)
 - matter dominance (why are we?)
 - vacuum stability (why is anything like it is?)

The legacy of the LHC

- LHC: so far, not so good at discovering unexpected new particles...
but great at making Higgs bosons!
- Precision measurements of Higgs properties & electroweak interactions ~~might~~ will help us understand...
 - the hierarchy problem (why is gravity so weak?)
 - fermion masses (why is the electron so light?)
 - matter dominance (why are we?)
 - vacuum stability (why is anything like it is?)
- These measurements are difficult!
 - Many parameters
 - Many observables
 - Subtle kinematic effects
 - Intractable likelihood


Particle physics processes

Theory
parameters
 θ




Evolution


Particle physics processes





Particle physics processes



Particle physics processes



Particle physics processes




[M. Cacciari, G. Salam, G. Soyez 0802.1189]




Evolution


Particle physics processes




Particle physics processes



Particle physics processes



Mining gold from LHC simulations




⇒ For each generated event, we can calculate the **joint likelihood ratio** conditional on its specific evolution:

$$r(x, z | \theta_0, \theta_1) \equiv \frac{p(x, z_d, z_s, z_p | \theta_0)}{p(x, z_d, z_s, z_p | \theta_1)} = \frac{p(x|z_d)}{p(x|z_d)} \frac{p(z_d|z_s)}{p(z_d|z_s)} \frac{p(z_s|z_p)}{p(z_s|z_p)}$$

$$\frac{p(z_p|\theta_0)}{p(z_p|\theta_1)} \sim \frac{|\mathcal{M}(z_p|\theta_0)|^2}{|\mathcal{M}(z_p|\theta_1)|^2}$$

Automation

We have developed **MadMiner**, which makes it straightforward to apply the new techniques to LHC problems



- “Mining gold” from LHC simulations
- Likelihood / ratio / score / Fisher info estimation
- Supports most aspects of real-life analyses:
 - Almost any theory model
 - Parameter morphing
 - Hard process, shower, detector simulation
 - Reducible + irreducible backgrounds
 - Systematic uncertainties
- Well-documented Python module

MadGraph, Pythia, Delphes...

RASCAL, SALLY & co

UFO standard

for EFT-like situations

Currently only LO


from PDF variation or scale variation

github.com/johannbrehmer/madminer

madminer.readthedocs.io

`pip install madminer`

Proof of concept: Higgs production in weak boson fusion




Exciting new physics might hide here!

We parameterize it with two EFT coefficients:

$$\mathcal{L} = \mathcal{L}_{\text{SM}} + \underbrace{\left[\frac{f_W}{\Lambda^2} \frac{i g}{2} (D^\mu \phi)^\dagger \sigma^a D^\nu \phi W_{\mu\nu}^a \right]}_{\mathcal{O}_W} - \underbrace{\left[\frac{f_{WW}}{\Lambda^2} \frac{g^2}{4} (\phi^\dagger \phi) W_{\mu\nu}^a W^{\mu\nu a} \right]}_{\mathcal{O}_{WW}}$$

Proof of concept: Higgs production in weak boson fusion



Exciting new physics might hide here!
We parameterize it with two EFT coefficients:

$$\mathcal{L} = \mathcal{L}_{\text{SM}} + \underbrace{\frac{f_W}{\Lambda^2} \frac{ig}{2} (D^\mu \phi)^\dagger \sigma^a D^\nu \phi W_{\mu\nu}^a}_{\mathcal{O}_W} - \underbrace{\frac{f_{WW}}{\Lambda^2} \frac{g^2}{4} (\phi^\dagger \phi) W_{\mu\nu}^a W^{\mu\nu a}}_{\mathcal{O}_{WW}}$$


Goal: constrain the two EFT parameters

- new inference methods
- baseline: 2d histogram analysis of jet momenta & angular correlations



Two scenarios:

- Simplified setup in which we can compare to true likelihood
- “Realistic” simulation with approximate detector effects



Stronger constraints with less training data




Stronger constraints with less training data



Stronger constraints with less training data




A new approach to simulator-based inference




- Many problems in modern science are based on simulations, “likelihood-free”

A new approach to simulator-based inference




- Many problems in modern science are based on simulations, “likelihood-free”




- New inference techniques:
Leverage insight into simulated process
+ power of machine learning


A new approach to simulator-based inference



- Many problems in modern science are based on simulations, “likelihood-free”




- New inference techniques:
Leverage insight into simulated process
+ power of machine learning
- First application to LHC measurements:
Stronger constraints with less simulations,
automation with new tool MadMiner



References



Kyle Cranmer



Gilles Louppe



Juan Pavez



Markus Stoye



Felix Kling



Irina Espejo

JB, KC, **GL**, **JP**:

Constraining Effective Field Theories with Machine Learning

[PRL, 1805.00013]

JB, KC, **GL**, **JP**:

A Guide to Constraining Effective Field Theories with Machine Learning

[PRD, 1805.00020]

JB, **GL**, **JP**, KC:

Mining gold from implicit models to improve likelihood-free inference

[1805.12244]

MS, **JB**, **GL**, **JP**, KC:

Likelihood-free inference with an improved cross-entropy estimator

[1808.00973]

JB, **FK**, **IE**, KC:

MadMiner

[doi: 10.5281/zenodo.1489147]

Thanks to Kyle and **Gilles** for inspiring many slides!

Bonus material

Variational calculus

$$\begin{aligned} L[\hat{g}(x)] &= \int dx dz \textcolor{red}{p}(x, z|\theta) |g(x, z) - \hat{g}(x)|^2 \\ &= \underbrace{\int dx \left[\hat{g}^2(x) \int dz \textcolor{red}{p}(x, z|\theta) - 2\hat{g}(x) \int dz \textcolor{red}{p}(x, z|\theta) g(x, z) + \int dz \textcolor{red}{p}(x, z|\theta) g^2(x, z) \right]}_{F(x)} \end{aligned}$$


$$0 = \frac{\delta F}{\delta \hat{g}} \Big|_{g^*} = 2\hat{g} \underbrace{\int dz \textcolor{red}{p}(x, z|\theta)}_{=\textcolor{red}{p}(x|\theta)} - 2 \int dz \textcolor{red}{p}(x, z|\theta) g(x, z)$$

$$g^*(x) = \frac{1}{\textcolor{red}{p}(x|\theta)} \int dz \textcolor{red}{p}(x, z|\theta) g(x, z)$$

Two types of likelihood ratio estimators


A) Point by point:

- first, define grid of parameter points $\{(\theta_0, \theta_1)\}$
- for each combination (θ_0, θ_1) ,
create separate estimator $\hat{r}_{\theta_0, \theta_1}(x)$
- final results can be interpolated between grid points




B) Parameterized: [P. Baldi et al. 1506.02169]


- create one estimator $\hat{r}(x|\theta_0, \theta_1)$ that is a function of θ_0 and θ_1
- no further interpolation necessary
- “borrows information” from close points




Point by point




(Agnostic) parameterized estimators




Morphing-aware parameterized estimators




$$\hat{r}(x|\theta_0, \theta_1) = \sum_c w_c(\theta_0) \hat{r}_c(x)$$



Limit setting (frequentist)



Effective field theory



Detector effects

