

# Flows for simultaneous manifold learning and density estimation


Johann Brehmer  
New York University

Kyle Cranmer  
New York University


NeurIPS 2020




The SCAILFIN Project  
[scailfin.github.io](https://scailfin.github.io)




Scientific Data and  
Computing Center



Normalizing flow in ambient data space:




$\mathcal{M}$ -flow:




$\mathcal{M}$ -flow:


Tractable density  
restricted to manifold




$\mathcal{M}$ -flow:




$\mathcal{M}$ -flow:










$$\tilde{u} \sim p_{\tilde{u}}(\tilde{u}) \quad \xleftarrow[h]{} \quad u$$

*n*-dim. latents      bijection      *n*-dim. latents












Ground truth,  $\theta = 0$




Ground truth,  $\theta = 0$





PIE,  $\theta = 0$




$\mathcal{M}$ -flow (M/D),  $\theta = 0$










[CMS collaboration]



Extended version on arXiv: 2003.13913

# Flows for simultaneous manifold learning and density estimation

Johann Brehmer<sup>a,b,1</sup> and Kyle Cranmer<sup>a,b</sup>

<sup>a</sup>Center for Data Science, New York University, USA; <sup>b</sup>Center for Cosmology and Particle Physics, New York University, USA

June 16, 2020

We introduce manifold-learning flows ( $\mathcal{M}$ -flows), a new class of generative models that simultaneously learn the data manifold as well as a tractable probability density on that manifold. Combining aspects of normalizing flows, GANs, autoencoders, and energy-based models, they have the potential to represent datasets with a manifold structure more faithfully and provide handles on dimensionality reduction, denoising, and out-of-distribution detection. We argue why such models should not be trained by maximum likelihood alone and present a new training algorithm that separates manifold and density updates. In a range of experiments we demonstrate how  $\mathcal{M}$ -flows learn the data manifold and allow for better inference than standard flows in the ambient data space.




Fig. 1. Sketch of how a standard normalizing flow in the ambient data space (left, orange surface) and an  $\mathcal{M}$ -flow (right, purple) model data (black dots).

## Contents

### 1 Introduction

### 2 Generative models and the data manifold

#### A Manifold-free models: Ambient flows . . . . .

## 1. Introduction

Inferring a probability distribution from example data is a common problem that is increasingly tackled with deep generative models. Generative adversarial networks (GANs) (1) and variational autoencoders (VAEs) (2) are both based on a lower-dimensional latent space and a learnable mapping from