





Satimage



Cov-Type



Misclassification Error

Dataset	k	Test Error	Train Error
Satimage	5	0.655500	0.656595
Satimage	9	0.651000	0.651409
Satimage	21	0.264500	0.238331
Satimage	27	0.261500	0.235400
Satimage	36	0.245000	0.218715
Cov-Type	5	0.914708	0.683532
Cov-Type	9	0.763602	0.560847
Cov-Type	21	0.541600	0.428968
Cov-Type	27	0.543063	0.406415
Cov-Type	36	0.516842	0.398810

Code

Included are functions for training and updating the weights, and setting the schedule for eliminating variables. For full code see https://github.com/johansent/ML_Fall2017/tree/master/hw7.

```
def updateWeights1(X,Y,w, Ncol,Nrow, learningRate, s):
    L = len(w)
    derivative = np.array([[0.0]*(Ncol)]*L)
    lorenz = 0.0
    X = np.array(X)
    U = np.dot(X, np.transpose(w))
    Uy = [U[i][Y[i]] for i in range(Nrow)]
    for l in range(L):
        diff = (Uy - U[:,l]) - 1
        diff = np.array([-(2 * d) / (1 + d*d)) if d <= 0 else 0 for d in diff])
```

```

    logical = [1 != Y[i] for i in range(Nrow)]
    diff = diff * logical
    lorenz += sum(np.log(1 + diff**2))
    dmat = diff * X.transpose()
    derivative[l] = np.sum(dmat, axis = 1)
    total = [X[i][0] if logical[i] else 0 for i in range(Nrow)]
    w = w - (learningRate * (derivative + (s * w)))
    loss = (lorenz + s * np.linalg.norm(w, 'fro'))
    return w, loss

def TrainWeights(X,Y,Xtest,Ytest,niter,k, learnRate = .01):
    Nrow = len(X)
    Ncol = len(X.columns)
    L = 7
    X1 = X.copy()
    Xtest1 = Xtest.copy()
    s = .001
    w = np.array([[0]*(Ncol)]*L)
    loss = []
    testErrors = []
    trainingErrors = []
    for i in range(niter):
        w, newloss = updateWeights1(X1,Y,w, Ncol,Nrow, learnRate, s)
        loss.append(newloss)
        if Ncol > k:
            Mi = getMi(Ncol, k, niter, i, u = 100)
            w,X,Xtest,Ncol = getMBest(w, X1, Xtest1, Mi, Ncol)
            testErrors.append(Test(w,Xtest1, Ytest))
            trainingErrors.append(Test(w,X1,Y))
        if(i % 50 == 0):
            print('i', i)
    return testErrors,trainingErrors, loss

def getMi(M, k, N, i, u = 100):
    return round(k + (M - k) * max([0,(N - 2 * i)/(2 * i * u + N)]))

```

```
def getMBest(w, X, Xtest, M, Ncol):
    summation = sum(w)
    best = sorted(range(len(summation)), key=lambda i: summation[i])[-M:]
    worst = sorted(range(len(summation)), key = lambda i: summation[i])[0:(Ncol - M)]
    w = np.array([[x[i] for i in sorted(best)] for x in w])
    X.drop(X.columns[worst], axis=1, inplace=True)
    Xtest.drop(Xtest.columns[worst], axis=1, inplace=True)
    return w, X, Xtest, len(X.columns)
```

Bibliography

1. Stéfan van der Walt, S. Chris Colbert and Gaël Varoquaux. The NumPy Array: A Structure for Efficient Numerical Computation, Computing in Science & Engineering, 13, 22-30 (2011), DOI:10.1109/MCSE.2011.37
2. John D. Hunter. Matplotlib: A 2D Graphics Environment, Computing in Science & Engineering, 9, 90-95 (2007), DOI:10.1109/MCSE.2007.55
3. Wes McKinney. Data Structures for Statistical Computing in Python, Proceedings of the 9th Python in Science Conference, 51-56 (2010)
4. Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, Édouard Duchesnay. Scikit-learn: Machine Learning in Python, Journal of Machine Learning Research, 12, 2825-2830 (2011)
5. conner.xyz at <https://stackoverflow.com/questions/20517650/how-to-delete-the-last-column-of-data-of-a-pandas-dataframe>