1) From the Groq and Openairouter

https://developers.openai.com/api/docs/models/all

--List down the Multimodels

Frontier Open AI Models	Best used for
GPT-5.4	Agentic coding, professional workflow
GPT-5.4 Mini	Coding, subagent
GPT-5 mini	Cost sensitive, high volume load
GPT-5	Coding and agentic task
GPT-5.4 Pro	More precise response
GPT-5.4 nano	Cheapest, high volume task
GPT-5 nano	Fastest, most efficient
GPT-4.1	Smartest, non reasoning model
Image Models	
GPT Image 1.5	Advance Image generation
GPT Image 1	Older image generation model
Dalle 3	Older image generation model
Chatgt image-latest	Image model used in chatgpt
Sora-2-pro	Audio video generation

https://console.groq.com/home

Models	Usage
GPT OSS 120B	Reasoning, Functional calling, tool use, text to text
GPT OSS 20B	Reasoning, Functional calling, tool use, text to text
Orpheus English	Text to speech
Orpheus Arabic Saudi	Text to speech
Llama 4 scout	Vision, Functional calling, tool use, text to text multlingual
Safety GPT OSS 20B	Safety, content moderation
Whisper Large V3	Speech to text

2) Take 3 models from each service provider

https://openrouter.ai/models

Context window,Input output token cost

Service provider	Model	Context window	Input cost	Output cost
Google	Gemini 3 Flash	1.05M	$0.50/M	$3/M
Google	Nano Banana	33K	$0.30/M	$2.50/M
Google	Nano Banana Pro	66K	$2/M	$12/M
Anthropic	Claude Opus 4.6	1M	$5/M	$25/M

Anthropic	Claude Sonnet 4.6	1M	$3/M	$15/M
Anthropic	Claude Haiku 4.5	200K	$1/M	$5/M
DeepSeek	DeepSeek V3.2	164K	$0.26/M	$0.38/M
DeepSeek	DeepSeek V3.1	33K	$0.15/M	$0.75/M
DeepSeek	DeepSeek V3	164K	$0.32/M	$0.89/M

3) use the Tokenizer with different prompt and see how the tokens are generated

https://platform.openai.com/tokenizer

GPT-5.x & O1/3 | GPT-4 & GPT-3.5 (legacy) | GPT-3 (legacy)

write a playwright script for simple get call

Clear | Show example

Tokens
8

Characters
45

```
[9566, 261, 147128, 11713, 395, 4705, 717, 2421]
```

Text | Token IDs

GPT-5.x & O1/3 | **GPT-4 & GPT-3.5 (legacy)** | GPT-3 (legacy)

write a playwright script for simple get call

Clear | Show example

Tokens
8

Characters
45

```
[5040, 264, 99468, 5429, 369, 4382, 636, 1650]
```

Text | **Token IDs**

GPT-5.x & O1/3 GPT-4 & GPT-3.5 (legacy) **GPT-3 (legacy)**

write a playwright script for simple get call

Clear **Show example**

Tokens
9

Characters
45

```
[13564, 257, 711, 29995, 4226, 329, 2829, 651, 869]
```

Text **Token IDs**