

Ali-CCP: Alibaba Click and Conversion Prediction

New a noteboc





天池小喵喵 2018-04-19 7769 207

Content Notebook Comment

Description

This data set is provided by Alimama

Data List

| Name | Date | Size | Downlo |
|-------------------------|------------|------------|---|
| sample_test.tar.gz | 2018-04-21 | 4.68GB |  |
| sample_test.tar.gz.md5 | 2018-04-21 | 53.00Bytes |  |
| sample_train.tar.gz | 2018-04-21 | 4.10GB |  |
| sample_train.tar.gz.md5 | 2018-04-21 | 53.00Bytes |  |

Document

Data Set Description

1. Introduction

This is a dataset gathered from real-world traffic logs of the recommender system in Taobao. As the largest online retail platform in the world, Taobao provides item recommendation service for better user experience. Given recommended items(goods) when visiting [Taobao.com](#), users might click interested ones and make a further purchase among them. In other words, user actions follow a sequential pattern of *impression* → *click* → *conversion*.



Figure 1: Illustration of recommender system in Taobao.

In all, the observed dataset is in format of $\{(x_i, y_i \rightarrow z_i)\}_{i=1}^N$, with sample $(x, y \rightarrow z)$ drawn from a distribution D with domain $\mathcal{X} \times \mathcal{Y} \times \mathcal{Z}$, where \mathcal{X} is feature space, \mathcal{Y} and \mathcal{Z} are label spaces, and N is the total number of impressions. x represents feature vector of observed impression, which is usually a high dimensional sparse vector with multi-fields, such as user field, item field etc. y and z are binary labels with $y = 1$ or $z = 1$ indicating whether click or conversion event occurs respectively. $y \rightarrow z$ reveals the sequential dependence of click and conversion labels that there is always a preceding click when conversion event occurs.

Values of y and z in the data can only belong to one of the following cases:

Table 1: Labels Distribution

| Label Values | Is Validation |
|--------------|---------------|
| y=0 & z=0 | Yes |
| y=0 & z=1 | No |
| y=1 & z=0 | Yes |
| y=1 & z=1 | Yes |

2. Sample Organization

The dataset consist of two parts : a train set (sample_train.tar.gz) and a test set (sample_test.tar.gz) with theirs own MD5 checksum files respectively, as shown below in Fig.2.




Figure 2: Illustration of sample organization.

Train and test set are split along the time sequence, which is a traditional industrial setting. Each set has two CSV format files: a sample skeleton file and a common features file. A complete sample record should contain not only the features from a record in sample skeleton file, but also the features from related record in common features file.

3. Sample Skeleton Description

Every row in sample skeleton file represents an impression and is composed of three sections. Fig.3 describes in detail the attributes and formats of different sections.




Figure 3: Illustration of sample skeleton.

- **Sample ID Section.**
The unique identity of a record in skeleton file, ranging from 1 to total record number. It is the primary key of the sample skeleton file.
- **Labels Section.**
There are two types of labels, i.e., click and conversion, for every impression, which follows the sequential patten as described in Table 1.
- **Features Section.**
There are three fields in this section:
 1. an index field named `common_feature_index` which is foreign key of sample skeleton, references the field with the same name in common features file.
 2. a nonnegative integer field named `feature_num` indicates the number of features in the field of `features_list`.
 3. `features_list` which is composed of several features separated by the ASCII character `0x01`. Each feature in the list is represented by Feature Structure, which is a three components data structure separated by the ASCII characters `0x02` and `0x03` , e.g. `feature_field_id 0x02 feature_id 0x03 feature_value`, where: i) `feature_field_id` represents the field of features, as shown below in Table 2, ii) all the features are encoded with global identities `feature_id`, iii) `feature_value` field gives a value of real number corresponding to `feature_id`.

Table 2: Description of feature sets

| Feature Category | Feature Field ID | Feature Field Description |
|----------------------|------------------|--|
| User Features | 101 | User ID. |
| | 109_14 | User historical behaviors of category ID and count*. |
| | 110_14 | User historical behaviors of shop ID and count*. |
| | 127_14 | User historical behaviors of brand ID and count*. |
| | 150_14 | User historical behaviors of intention node ID and count*. |
| | 121 | Categorical ID of User Profile. |
| | 122 | Categorical group ID of User Profile. |
| | 124 | Users Gender ID. |
| | 125 | Users Age ID. |
| | 126 | Users Consumption Level Type I. |
| | 127 | Users Consumption Level Type II. |
| | 128 | Users Occupation: whether or not to work. |
| | 129 | Users Geography Informations. |
| Item Features | 205 | Item ID. |
| | 206 | Category ID to which the item belongs to. |
| | 207 | Shop ID to which item belongs to. |
| | 210 | Intention node ID which the item belongs to. |
| | 216 | Brand ID of the item. |
| Combination Features | 508 | The combination of features with 109_14 and 206. |

| Feature Category | Feature Field ID | Feature Field Description |
|------------------|------------------|--|
| | 509 | The combination of features with 110_14 and 207. |
| | 702 | The combination of features with 127_14 and 216. |
| | 853 | The combination of features with 150_14 and 210. |
| Context Features | 301 | A categorical expression of position. |

*User historical behaviors collected within the past two weeks.

4. Common Features Description

Every row in common feature file represents a collection of features shared by lots of impressions in sample skeleton file and has the same structure of Section 3 in Sample skeleton description, as shown below in Fig.4. The difference between them is that common_feature_index is the primary key of common features file while it is just a foreign key of sample skeleton file.




Figure 4: Illustration of common features.

5. Pseudocode of Sample Completion

A complete sample record should contain not only the features from a record in sample skeleton file, but also the features from related record in common features file, according to the pseudocode shown in Fig.5.

```
--Pseudocode of sample completion
SELECT  a.labels
        ,a.features
        ,b.features
FROM    sample_skeleton_file AS a LEFT
JOIN    common_feautures_file AS b
ON      a.common_feature_index = b.comon_feature_index;
```

Figure 5: Pseudocode of sample completion.

6. Citation

To acknowledge use of the dataset in publications, please cite the following paper:

Xiao Ma, Liqin Zhao, Guan Huang, Zhi Wang, Zelin Hu, Xiaoqiang Zhu, Kun Gai. Entire Space Multi-Task Model: An Effective Approach for Estimating Post-Click Conversion Rate. In SIGIR 2018-Proceedings of the 41th International ACM SIGIR Conference on Research and Development in Information Retrieval 2018 July 8-12. ACM.

阿里巴巴点击与转化预估数据集说明

1. 简介

本数据集采集自手机淘宝移动客户端的推荐系统日志，其中包含点击和与之关联的转化数据，二者的关系图1描述。淘宝平台作为全球最大的在线零售电子商务平台，为提升其用户体验，通过推荐系统提供商品推荐服务，用户可以在浏览（impression）推荐结果中点击（click）感兴趣的物品，或者进一步对物品进行购买（conversion）。因此用户的行为可以抽象为一个序列模式：浏览 -> 点击 -> 购买。



图 1: 手机淘宝上的单品广告

本数据的整体描述为 $\{(x_i, y_i \rightarrow z_i)\}_{i=1}^N$ ，样本的格式为 $(x, y \rightarrow z)$ ，是来自定义域 $(x, y \rightarrow z)$ 的分布D，其中 \mathcal{X} 是特征空间， \mathcal{Y} 和 \mathcal{Z} 是标签空间， N 是样本总量。 x 代表观测样本的特征向量，通常是被划分为多个域的高维稀疏向量，例如，用户域、商品域等。 y 和 z 都是二值标签（0 or 1），其中 $y = 1$ 代表样本发生点击事件，而 $z = 1$ 代表样本发生转化事件，显然，由于业务归因分析的需要，转化事件被定义为由本次点击引导的转化事件，因此同一个样本的点击事件和转化事件不是独立的，转化事件的发生必然要求该样本存在先序点击事件，这种序列依赖关系我们用 $y \rightarrow z$ 来描述。

根据上述说明，本数据集中各样本的标签 y 和 z 字段的值分布，服从如下约束：

表 1: 标签分布

| 标签值域 | 是否合法 |
|-----------|------|
| y=0 & z=0 | 合法 |
| y=0 & z=1 | 非法 |
| y=1 & z=0 | 合法 |
| y=1 & z=1 | 合法 |

2. 样本组织说明

本数据集由两部分组成：第一部分为训练数据（sample_train.tar.gz),第二部分为测试数据（sample_test.tar.gz)，每个部分的数据还分别携带了一个MD5检校文件，详见图2描述。




图 2: 样本组织说明

注意：训练和测试数据严格按照时间顺序划分——训练数据先于测试数据发生，这也遵循了传统工业数据集的实际应用场景。考虑到存储效率问题，每部分数据由两个CSV格式文件构成：一个是样本骨架文件，另一个是公共特征文件。使用本数据集前，应首先确保样本骨架文件与公共特征文件已经进行正确地关联，具体关联方法详细参考本文第5部分样本关联方法。

3. 样本骨架说明

样本骨架文件中的每一条记录代表一次用户浏览，并且由三个部分组成，图3详细描述了各部分属性与格式信息。




图 3: 样本骨架说明

- 样本ID部分**
唯一标识样本骨架中的一条记录，取值从1开始直到全部样本数，是样本骨架文件的主键。
- 标签部分**
标签部分包含一次浏览记录上的两种类型的标签信息：点击和转化事件是否发生，表1对取值范围进行了描述。
- 特征部分**
特征部分包含三个域：
 - 索引（common_feature_index）域：作为样本骨架文件的_外键_，用来关联公共特征文件中的信息，复原样本时使用。
 - 特征数量（feature_num）域：指出本条记录中特征列表（feature_list）域包含的特征总数，是一个非负整数。
 - 特征列表（feature_list）域：由ASCII字符0x01分割的若干特征组成，这些特征由特征数据结构（Feature Structure）描述。特征数据结构由ASCII字符0x02和0x03作为分隔符的字符串构成，例如：feature_field_id 0x02 feature_id 0x03 feature_value，其中feature_field_id字段代表特征域信息，在表2中进行了详细描述；feature_id字段是被全局编码后的特征ID值；feature_value字段是特征ID对应的特征值。

表 2: 特征描述

| 特征域名称 | 特征域ID | 特征域说明 |
|-------|--------|----------------------------|
| 用户域 | 101 | 用户ID。 |
| | 109_14 | 商品类目ID以及用户在该类目上的历史行为累积数量*。 |
| | 110_14 | 商品店铺ID以及用户在该店铺上的历史行为累积数量*。 |
| | 127_14 | 商品品牌ID以及用户在该品牌上的历史行为累积数量*。 |
| | 150_14 | 用户意图ID以及用户在该意图上的历史行为累积数量*。 |

| 特征域名称 | 特征域ID | 特征域说明 |
|-------|-------|-------------------|
| | 121 | 用户的一种分类ID。 |
| | 122 | 用户的一种分类ID |
| | 124 | 用户性别分类ID。 |
| | 125 | 用户年龄分类ID。 |
| | 126 | 用户消费水平分类I。 |
| | 127 | 用户消费水平分类II。 |
| | 128 | 用户是否就业。 |
| | 129 | 用户地理信息分类ID。 |
| 商品域 | 205 | 商品ID |
| | 206 | 商品所属类目ID |
| | 207 | 商品所属店铺ID |
| | 210 | 商品关联用户意图ID |
| | 216 | 商品的品牌ID |
| 组合域 | 508 | 109_14和206域的组合特征。 |
| | 509 | 110_14和207域的组合特征。 |
| | 702 | 127_14和216域的组合特征。 |
| | 853 | 150_14和210域的组合特征。 |
| 场景域 | 301 | 业务场景信息的一种分类表示。 |

*用户历史行为信息来自过去两周。

4. 公共特征说明

公共特征文件中的一条记录代表一个特定的特征集合，这个特征集合被样本骨架文件中若干条记录共享，图4所描述。在公共特征文件中同样存在common_feature_index作为_主键_，与样本骨架文件中的同名字段沟通描述这种共享关系。




图 4: 公共特征说明

5. 样本关联方法

About us Legal agreement Contact Us Email:tianchi_bigdata@member.alibaba.com

| | | | | |
|----------------------|-------------------|--------------------------|---------------------|-----------------------|
| About | Promotions | Explore | Support | Resources |
| About Alibaba Cloud | Free Trial | China Gateway | Contact Sales | Documentation Center |
| Pricing Models | Refer a Friend | ICP License Support | Submit a Ticket | Alibaba Cloud MVP |
| Products | Starter Package | Getting Started | After-Sales Support | Security & Compliance |
| Customers | Web Hosting | Blog | Report Abuse | Press Room |
| Partners | Affiliate Program | Marketplace | Feedback | WHOIS |
| Startups | | Training & Certification | Forum | Site Map |
| Apsara Conference | | | Pricing Calculator | |
| Alibaba Cloud Summit | | | | |



A comprehensive suite of global cloud computing services to power your business