

# Chapter 3 : Multi-valued Data Fusion

John Klein

Université de Lille1 - CRIStAL UMR CNRS 9189



# Chapter organization


- 1 Operators for multi-valued data fusion
- 2 Appendix : Partial order and Lattices

- In this chapter, information sources are allowed to deliver more **imprecise** advocacies, *i.e.* **multi-valued** advocacies.

- In this chapter, information sources are allowed to deliver more **imprecise** advovacies, *i.e.* **multi-valued** advovacies.
- This setting is **more general** than **point data fusion**.

- In this chapter, information sources are allowed to deliver more **imprecise** advocacies, *i.e.* **multi-valued** advocacies.
- This setting is **more general** than **point data fusion**.
- But the advocacy space  $\mathbb{X}$  is **more structured**.

## Multi-valued data fusion setting :



Let us give a definition for **multi-valued fusion problems** :

### Definition


**Partially ordered data fusion** is a subclass of data fusion where advocacies live in  $\mathbb{X} = 2^{\mathcal{X}}$ .

- In this case,  $\mathbb{X}$  has a **distributive complemented lattice** structure.

## Lattice : example

### Example

$\mathbb{X} = 2^{\mathcal{X}}$  is the power set of a given set  $\mathcal{X} = \{a; b; c\}$ , then  $\{2^{\mathcal{X}}, \subseteq, \cap, \cup, .^c\}$  is a complemented lattice. Here is the corresponding Hasse diagram :



The arrow stands for the inclusion **partial order**.



# Chapter organization

1 Operators for multi-valued data fusion

2 Appendix : Partial order and Lattices

## Set-valued data fusion : operators

- In this context, each information source delivers a datum like  $x_*^{(i)} = A \Leftrightarrow x \in A$ .
- Two natural fusion operators arising from the binary operations endowing the lattice.
- Unless explicit comment, we will always consider that the lattice we are interested in is  $(2^{\mathcal{X}}, \subseteq, \cap, \cup)$ .

## Set-valued data fusion : operators

- In this context, each information source delivers a datum like  $x_*^{(i)} = A \Leftrightarrow x \in A$ .
- Two natural **fusion operators** arising from the **binary operations** endowing the lattice.
- Unless explicit comment, we will always consider that the lattice we are interested in is  $(2^{\mathcal{X}}, \subseteq, \cap, \cup)$ .

## Set-valued data fusion : operators

- In this context, each information source delivers a datum like  $x_*^{(i)} = A \Leftrightarrow x \in A$ .
- Two natural **fusion operators** arising from the **binary operations** endowing the lattice.
- Unless explicit comment, we will always consider that the lattice we are interested in is  $(2^{\mathcal{X}}, \subseteq, \cap, \cup)$ .

## Set-valued data fusion : operators

## Definition

Let us consider a data fusion problem as defined in 1. The (canonical) **conjunctive operator**  $\hat{x}_{\cap}$  is defined as follows :

$$\hat{x}_{\cap} : \left( x_*^{(1)}, \dots, x_*^{(N_s)} \right) \rightarrow \bigcap_{i=1}^{N_s} x_*^{(i)}. \quad (1)$$

## Definition

Let us consider a data fusion problem as defined in 1. The (canonical) **disjunctive operator**  $\hat{x}_{\cup}$  is defined as follows :

$$\hat{x}_{\cup} : \left( x_*^{(1)}, \dots, x_*^{(N_s)} \right) \rightarrow \bigcup_{i=1}^{N_s} x_*^{(i)}. \quad (2)$$

## Set-valued data fusion : operator nature

- Roughly speaking, **conjunctive operators** are **efficient** because they converge to the smallest possible set of solutions but they are **risky** if at least one source is not fully truthful. In this latter case,  $\hat{x}_{\cap}$  may give  $\emptyset$  as output, which is a typical case of conflict between sources.
- On the opposite, **disjunctive operators** are regarded as **cautious** operators because they do not discard any possible value supported by any source. However, disjunctive operators are **poorly efficient**. For instance,  $\hat{x}_{\cup}$  may deliver  $\mathcal{X}$  as output making it totally impossible to decide on the value of  $x$ .
- An operator can be neither conjunctive nor disjunctive.

## Set-valued data fusion : operator nature

- Roughly speaking, **conjunctive operators** are **efficient** because they converge to the smallest possible set of solutions but they are **risky** if at least one source is not fully truthful. In this latter case,  $\hat{x}_{\cap}$  may give  $\emptyset$  as output, which is a typical case of conflict between sources.
- On the opposite, **disjunctive operators** are regarded as **cautious** operators because they do not discard any possible value supported by any source. However, disjunctive operators are **poorly efficient**. For instance,  $\hat{x}_{\cup}$  may deliver  $\mathcal{X}$  as output making it totally impossible to decide on the value of  $x$ .
- An operator can be neither conjunctive nor disjunctive.

## Set-valued data fusion : operator nature

- Roughly speaking, **conjunctive operators** are **efficient** because they converge to the smallest possible set of solutions but they are **risky** if at least one source is not fully truthful. In this latter case,  $\hat{x}_{\cap}$  may give  $\emptyset$  as output, which is a typical case of conflict between sources.
- On the opposite, **disjunctive operators** are regarded as **cautious** operators because they do not discard any possible value supported by any source. However, disjunctive operators are **poorly efficient**. For instance,  $\hat{x}_{\cup}$  may deliver  $\mathcal{X}$  as output making it totally impossible to decide on the value of  $x$ .
- An operator can be neither conjunctive nor disjunctive.



## Set-valued data fusion : operators

- Let alone standard set operations like intersection and union, there is also a possibility to map sets with objects with which **calculus** is possible.
- These objects are indicator functions. Let  $A$  be a subset of the solution space :  $A \subseteq \mathcal{X}$  or equivalently  $A \in \mathbb{X} = 2^{\mathcal{X}}$ . The **indicator function**  $1_A$  of set  $A$  is a mapping such that :

$$\begin{aligned} 1_A : \mathcal{X} &\rightarrow \mathbb{R}, \\ x_0 &\rightarrow \begin{cases} 1 & \text{if } x_0 \in A \\ 0 & \text{otherwise} \end{cases} . \end{aligned} \quad (3)$$

- Indicator functions and sets are clearly in bijective correspondance.
- Indicator functions belong to a vector space, which allows us to introduce a generalization of histograms.

## Set-valued data fusion : operators

- Let alone standard set operations like intersection and union, there is also a possibility to map sets with objects with which **calculus** is possible.
- These objects are indicator functions. Let  $A$  be a subset of the solution space :  $A \subseteq \mathcal{X}$  or equivalently  $A \in \mathbb{X} = 2^{\mathcal{X}}$ . The **indicator function**  $1_A$  of set  $A$  is a mapping such that :

$$\begin{aligned} 1_A : \mathcal{X} &\rightarrow \mathbb{R}, \\ x_0 &\rightarrow \begin{cases} 1 & \text{if } x_0 \in A \\ 0 & \text{otherwise} \end{cases} . \end{aligned} \quad (3)$$

- Indicator functions and sets are clearly in bijective correspondance.
- Indicator functions belong to a vector space, which allows us to introduce a generalization of histograms.

## Set-valued data fusion : operators

- Let alone standard set operations like intersection and union, there is also a possibility to map sets with objects with which **calculus** is possible.
- These objects are indicator functions. Let  $A$  be a subset of the solution space :  $A \subseteq \mathcal{X}$  or equivalently  $A \in \mathbb{X} = 2^{\mathcal{X}}$ . The **indicator function**  $1_A$  of set  $A$  is a mapping such that :

$$\begin{aligned} 1_A : \mathcal{X} &\rightarrow \mathbb{R}, \\ x_0 &\rightarrow \begin{cases} 1 & \text{if } x_0 \in A \\ 0 & \text{otherwise} \end{cases} . \end{aligned} \quad (3)$$

- Indicator functions and sets are clearly in bijective correspondance.
- Indicator functions belong to a vector space, which allows us to introduce a generalization of histograms.

## Set-valued data fusion : operators

- Let alone standard set operations like intersection and union, there is also a possibility to map sets with objects with which **calculus** is possible.
- These objects are indicator functions. Let  $A$  be a subset of the solution space :  $A \subseteq \mathcal{X}$  or equivalently  $A \in \mathbb{X} = 2^{\mathcal{X}}$ . The **indicator function**  $1_A$  of set  $A$  is a mapping such that :

$$\begin{aligned} 1_A : \mathcal{X} &\rightarrow \mathbb{R}, \\ x_0 &\rightarrow \begin{cases} 1 & \text{if } x_0 \in A \\ 0 & \text{otherwise} \end{cases} . \end{aligned} \quad (3)$$

- Indicator functions and sets are clearly in bijective correspondance.
- Indicator functions belong to a vector space, which allows us to introduce a generalization of histograms.

## Set-valued data fusion : set-histograms

## Definition

Let  $\left\{x_*^{(i)}\right\}_{i=1}^{N_s}$  denote a set-valued dataset such that  $\forall i, x_*^{(i)} \in 2^{\mathcal{X}}$ . The **set-histogram**  $h$  of the dataset  $\left\{x_*^{(i)}\right\}_{i=1}^{N_s}$  is the a mapping such that :

$$\begin{aligned} h : \mathcal{X} &\longrightarrow \mathbb{N}, \\ x &\longrightarrow \sum_{i=1}^{N_s} 1_{x_*^{(i)}}(x). \end{aligned} \quad (4)$$

In other words,  $h(x)$  is the number of sets in the dataset containing the value  $x$ .

## Set-valued data fusion : operators from set-histograms

- Using this set-histogram all definitions of **voting operators** from the previous chapter immediatly apply :  $\hat{x}_{maj}$ ,  $\hat{x}_{smj}$ ,  $\hat{x}_{amj}$  and  $\hat{x}_{mod}$ .
- This is tantamount to voting with **approval ballots**.

### Example


Suppose we have  $\mathcal{X} = \{1; 2; 3; 4\}$  and the sources delivered the following advocacies :

- $x_*^{(1)} = \{1; 2; 3\}$ ,
- $x_*^{(2)} = \{1\}$ ,
- $x_*^{(3)} = \{2; 3\}$ ,
- $x_*^{(4)} = \{2; 4\}$ ,
- $x_*^{(5)} = \{2; 3; 4\}$ .

The corresponding set histogram is :  $\mathbf{h} = [2 \ 4 \ 3 \ 2]$ .

## Set-valued data fusion : operators from set-histograms

## Example



The contributions of the sources are in yellow for 1<sup>st</sup> source, in orange for the 2<sup>nd</sup> source, in red for the 3<sup>rd</sup> source, in violet for the 4<sup>th</sup> source and in grey for the 5<sup>th</sup> source. .

We have  $\hat{x}_{maj} = \hat{x}_{mod} = 2$  while  $\hat{x}_{\cap} = \emptyset$  and  $\hat{x}_{\cup} = \mathcal{X}$ .

## Set-valued data fusion : example in Machine Learning

- Suppose you want to use SVM to solve a classification task with 3 classes.
- But SVM cannot be generalized to multi-class problems!
- Solution : train 2 SVM in a 1-versus-all fashion.




## Set-valued data fusion : example in Machine Learning

- Suppose you want to use SVM to solve a classification task with 3 classes.
- But SVM cannot be generalized to multi-class problems!
- Solution : train 2 SVM in a 1-versus-all fashion.


## Set-valued data fusion : example in Machine Learning

- Suppose you want to use SVM to solve a classification task with 3 classes.
- But SVM cannot be generalized to multi-class problems!
- Solution : train 2 SVM in a 1-versus-all fashion.

SVM and multi-class problems : a solution using multi-valued data fusion



SVM and multi-class problems : another possibility with point data fusion



# Chapter organization

1 Operators for multi-valued data fusion

2 Appendix :Partial order and Lattices

## Posets :

## Definition

Suppose  $\mathbb{X}$  is an abstract space with  $\leq$  a binary relation that is

- (i) reflexive, *i.e.*  $a \leq a$ ,  $\forall a \in \mathbb{X}$ ,
- (ii) antisymmetric, *i.e.*  $a \leq b$  and  $b \leq a$  implies  $a = b$ ,  $\forall a, b \in \mathbb{X}$ ,
- (iii) and transitive, *i.e.*  $a \leq b$  and  $b \leq c$  implies  $a \leq c$ ,  $\forall a, b, c \in \mathbb{X}$ .

$\leq$  is a **partial order** on  $\mathbb{X}$  and  $(\mathbb{X}, \leq)$  is called a partially ordered set, or **poset** for short.

## Bounds :

### Definition

Let  $(a, b)$  be a pair of element in  $\mathbb{X}$ . An **upper bound** of  $\{a; b\}$  is an element  $u \in \mathbb{X}$  such that  $a \leq u$  and  $b \leq u$ . The **least upper bound** (lub) of  $\{a; b\}$  is the unique element  $v \in \mathbb{X}$  (if it exists) such that  $v$  is an upper bound of  $\{a; b\}$  and for any upper bound  $u$  of  $\{a; b\}$  we have  $v \leq u$ .

### Definition

Conversely, a **lower bound** of  $\{a; b\}$  is an element  $l \in \mathbb{X}$  such that  $l \leq a$  and  $l \leq b$ . The **greatest lower bound** (glb) of  $\{a; b\}$  is the unique element  $w \in \mathbb{X}$  (if it exists) such that  $w$  is a lower bound of  $\{a; b\}$  and for any lower bound  $l$  of  $\{a; b\}$  we have  $l \leq w$ .

## Bounds : example

### Example

Let us suppose that  $\mathbb{X}$  is made of subsets of a given set  $\mathcal{X}$  and the partial order we are interested in is the inclusion  $\subseteq$ .

- If  $\mathbb{X} = \{\{a\}; \{b\}; \{a; c\}; \{b; d\}\}$  with  $a, b, c$  and  $d \in \mathcal{X}$ , then  $\{\{a\}; \{b\}\}$  has no upper bound because  $\{b\} \not\subseteq \{a; c\}$  and  $\{a\} \not\subseteq \{b; d\}$ .
- If  $\mathbb{X} = \{\{a\}; \{b\}; \{a; b; c\}; \{a; b; c; d\}\}$  with  $a, b, c$  and  $d \in \mathcal{X}$ , then  $\{a; b; c; d\}$  is an upper bound of  $\{\{a\}; \{b\}\}$  and  $\{a; b; c\}$  is the least upper bound of  $\{\{a\}; \{b\}\}$ .



## Lattice :

### Definition


If any  $\{a; b\} \subseteq \mathbb{X}$  has a lub denoted by  $a \vee b$  and a glb denoted by  $a \wedge b$ , then  $(\mathbb{X}, \leq, \wedge, \vee)$  is called a **lattice**.

- Note that the above definition is given for a pair of elements in  $\mathbb{X}$ . This definition is formally equivalent to a definition with a finite set of elements in  $\mathbb{X}$ .
- However, this is not true for infinite sets of elements in  $\mathbb{X}$ . If this latter property also holds, then the lattice is said to be **complete**.

## Lattice : example

## Example

Suppose  $\mathbb{X}$  is the power set of a given set  $\mathcal{X} = \{a; b; c\}$ , then  $\{2^{\mathcal{X}}, \subseteq, \cap, \cup\}$  is an example of complete lattice. Here is the corresponding Hasse diagram :



The arrow stands for the inclusion partial order.

## Lattice : example

## Example

As for an example of incomplete lattice, let us suppose that  $\mathbb{X} = ]0; 1[$  endowed with the classical total order on reals  $\leq$ . For any  $a \in \mathbb{X}$ , let  $b = a + \frac{1-a}{2}$ . We have  $b \in \mathbb{X}$  and  $a \leq b$ , hence  $a$  is not a lub of  $\mathbb{X}$ . Consequently, one cannot find a greatest element in  $\mathbb{X}$ .

## Lattice : property

## Property

Suppose  $(\mathbb{X}, \leq, \wedge, \vee)$  is a lattice, then  $\vee$  and  $\wedge$  are two **monotone binary operations** with respect to  $\leq$ . For any  $a_1, a_2, b_1$  and  $b_2 \in \mathbb{X}$  such that  $a_1 \leq a_2$  and  $b_1 \leq b_2$  :

$$a_1 \vee b_1 \leq a_2 \vee b_2, \quad (5)$$

$$a_1 \wedge b_1 \leq a_2 \wedge b_2. \quad (6)$$

Lattice : property

### Definition

A **bounded lattice** is a lattice  $(\mathbb{X}, \leq, \wedge, \vee)$  with a greatest  $1_{\mathbb{X}}$  and a least element  $0_{\mathbb{X}}$ , i.e. for any  $a \in \mathbb{X}$ , we have  $0_{\mathbb{X}} \leq a \leq 1_{\mathbb{X}}$ .

### Definition

A **distributive lattice** is a lattice  $(\mathbb{X}, \leq, \wedge, \vee)$  such that  $\wedge$  is distributive over  $\vee$ , i.e. for any  $a, b$  and  $c \in \mathbb{X}$ , we have :

$$a \wedge (b \vee c) = (a \wedge b) \vee (a \wedge c). \quad (7)$$

Lattice : property

### Definition

A **complemented lattice** is a bounded lattice  $(\mathbb{X}, \leq, \wedge, \vee)$  such that any  $a \in \mathbb{X}$  has a complement  $\neg a$ , i.e. an element  $b \in \mathbb{X}$  with :

$$a \wedge b = 0_{\mathbb{X}}, \quad (8)$$

$$a \vee b = 1_{\mathbb{X}}. \quad (9)$$

Some fusion problems are also often defined on **Boolean algebras** which are complemented distributive lattices. For instance  $(2^{\mathcal{X}}, \subseteq, \cap, \cup, \cdot^c)$  is a Boolean algebra. Propositional logic and propositional calculus are intimately connected to Boolean algebras. This formalism is appealing for modeling deductive arguments in natural language. Boolean searches are notably implemented by Google search engine.