




- 1. DIAPHRAMS TO BE CONSIDERED IN FINAL DESIGN
- 2. AASHTO M 164 BOLTS WITH MINIMUM 7//8" DIA.
  TO BE USED FOR ANY CONNECTION






- 1. DIAPHRAMS TO BE CONSIDERED IN FINAL DESIGN
- 2. AASHTO M 164 BOLTS WITH MINIMUM 7//8" DIA.
  TO BE USED FOR ANY CONNECTION



### **ABUTMENT 1** 16" X 3/4" X 125' (TOP FLANGE) $\bigcirc$ 55" X 1/2" X 125' (WEB) $\bigcirc$ 16" X 1 1/4" X 125' (BOTTOM FLANGE) 100ft-0in

## **GIRDER ELEVATION VIEW**


GIRDER D SHOWN (OTHERS SIMILAR)



**ABUTMENT 2** 


### **SECTION A-A**

(NOT TO SCALE)



FIELD SPLICE BOLTED CONNECTION LOCATED AT L = 100' FOR EACH GIRDER SEE SHEET 104 FOR CONNECTION DETAILS


# SHEAR STUDS



DESIGN, LAYOUT, SIZING OF SHEAR STUDS WILL BE CONSIDERED IN FINAL DESIGN

#### NOTES:


- 1. GIRDERS A-D ARE CUT INTO 100 FT AND 25 FT SECTIONS FOR SHIPPING
- 2. STIFFENERS CONSIDERED IN FINAL DESIGN
- 3. SEC A-A SHOWS FIELD SPLICE LOCATION AT 100 FT FROM A1
- 4. FOR CONNECTION DETAILS, SEE SHEET 104




103

GIRDER ELEVATION VIEW 9 MARCH 2019 1:10 SCALE DRAWN BY DESIGNED BY CHECKED BY:

MSA BGE NMN





- 1. PLATE GIRDER CONSISTS OF 3 PLATES, WELDED CONNECTION
- 2. SHIPPING LIMIT 100' SO GIRDERS A-D WILL BE FABRICATED IN 100' AND 25' SECTIONS (4 EACH)

TOP FLANGE 16" X 3/4"

WEB 55" X 1/2"


BOTTOM FLANGE 16" X 1 1/4"

3. WELD SIZE DEPENDENT UPON MANUFACTURER

1 in. = 8 in.



Bridging The Gap		DGING THE GAP NGINEERING	
BEGLE	EEK BRIDGE Y ROAD COUNTY, WV	SECTION VIEW STEEL PLATE GIRDER ALTERNATIVE	
DATE 9 MARCH 2019		SCALE 1:8	
DRAWN BY	DESIGNED BY	CHECKED BY	SHEET
MSA	BGE	NMN	105



# **SECTION VIEW**


#### **NOTES**

- 1. WVDOH TYPE F BARRIERS USED
- 2. REINFORCEMENT LAYOUT/SIZING TO BE CONSIDERED IN FINAL DESIGN
- 3. 4 GIRDERS @ 8' SPACING, LOOKING FROM A1 TO A2

1 in. = 4 ft.



BRIDGING THE GAP ENGINEERING				
BRYCE CREEK BRIDGE		CONCRETE BEAM		
BEGLEY ROAD		ALTERNATIVE		
CABELL COUNTY, WV		SECTION VIEW		
DATE		SCALE		
9 MARCH 2019		1:4		
DRAWN BY	DESIGNED BY	CHECKED BY	SHEET	
MSA	BGE	NMN	106	



- 1. TYPICAL REBAR EDGE DISATNCE = 2" AS SHOWN
- 2. PRELIMINARY REBAR LAYOUT SHOWN, 2 in. SPACNG (TYP.)
- 3. REINFORCEMENT SIZING, COVER, ETC TO BE CONSIDERED IN FINAL DESIGN



# BRIDGING THE GAP ENGINEERING

BRYCE CRE	EK BRIDGE	CONCRETE	BEAM ALT.
BEGLE	/ ROAD	SECTION	N VIEW
CABELL CC	DUNTY, WV		
DATE		SCALE	
9 MARCH 2019		1:10	
DRAWN BY	DESIGNED BY	CHECKED BY	SHEET
MSA	BGE	NMN	107

# 3in 9in R = 1" -**CLASS B CONCRETE** 32in 5in - 1" DIA. DOWELS 8" LONG 3in DECK 6in


# **NOTES**


- 1. WVDOT STANDARD TYPE F BARRIER (TYP.)
- 2. MINIMUM HEIGHT OF 32 lin. ABOVE DECK SURFACE
- 3. REINFORCEMENT AND DECK SEATING DETAILS TO BE CONSIDERED IN FINAL DESIGN

1 in. = 8 in.



Bridging The Gap	BRI	BRIDGING THE GAP		
Engineering	Engineering		NGINEERING	
BRYCE CRE	BRYCE CREEK BRIDGE BEGLEY ROAD CABELL COUNTY, WV		PARAPET	
BEGLEY			SECTION VIEW	
CABELL CC				
DATE	DATE			
10 MARCH 2019		1:8		
DRAWN BY	DESIGNED BY	CHECKED BY	SHEET	
MSA	BGE	NMN	108	





# SECTION VIEW (NOT TO SCALE)

