AXIS_1553_ENCODER

November 14, 2024

Jay Convertino

Contents

1 Usage

1.1 Introduction

AXIS 1553 Encoder is a core for taking AXIS data and encoding for output to the PMOD1553 device. The output is a TTL differential signal. Meaning when diff[0] is 1 diff[1] is 0. This core also includes a diff enable which allows for mux switching to the transmit (encoder) when active.

1.2 Dependencies

The following are the dependencies of the cores.

- fusesoc 2.X
- iverilog (simulation)
- cocotb (simulation)

1.2.1 fusesoc_info Depenecies

- dep
  - AFRL:utility:helper:1.0.0
- dep_tb
  - AFRL:simulation:axis_stimulator
  - AFRL:utility:sim_helper

1.3 In a Project

Connect the device to your AXIS bus. TUSER is used to set various options such as command/data packet mode.

TDATA input should contain the 16 bit data payload. TUSER is a 8 bit command register that takes a discription what type of data it is (command or data) and other options. described below.

TUSER = TYY,NA,D,I,P (7 downto 0)

- TYY = TYPE OF DATA
  - 000 N/A
  - 001 REG (NOT IMPLIMENTED)
  - 010 DATA
  - 100 CMD/STATUS

- NA = RESERVED FOR FUTURE USE.
- D = DELAY ENABLED
  - 1 = 4 us delay enabled.
  - 0 = no delay between transmissions.
- I = INVERT DATA
  - 1 = Invert data.
  - 0 = Normal data.
- P = PARITY
  - 1 = ODD
  - 0 = EVEN

2 Architecture

This core is made up of a single module.

- **axis_1553_encoder** Interface AXIS to PMOD1553 device (see core for documentation).

For register documentation please see up_uart in 5

3 Building

The AXIS 1553 Encoder is written in Verilog 2001. It should synthesize in any modern FPGA software. The core comes as a fusesoc packaged core and can be included in any other core. Be sure to make sure you have meet the dependencies listed in the previous section.

3.1 fusesoc

Fusesoc is a system for building FPGA software without relying on the internal project management of the tool. Avoiding vendor lock in to Vivado or Quartus. These cores, when included in a project, can be easily integrated and targets created based upon the end developer needs. The core by itself is not a part of a system and should be integrated into a fusesoc based system. Simulations are setup to use fusesoc and are a part of its targets.

3.2 Source Files

3.2.1 fusesoc_info File List

- src

  Type: verilogSource

  - src/axis_1553_encoder.v

- tb

  - 'tb/tb_1553_enc.v': 'file_type': 'verilogSource'

3.3 Targets

3.3.1 fusesoc_info Targets

- default

  Info: Default for IP intergration.

  - src
  - dep

- sim

  Info: Simulation using icarus as the default.

  - src
  - dep
  - tb
  - dep_tb

3.4 Directory Guide

Below highlights important folders from the root of BUS UART.

1. **docs** Contains all documentation related to this project.
   - **manual** Contains user manual and github page that are generated from the latex sources.
2. **src** Contains source files for the core
3. **tb** Contains test bench files for iverilog and cocotb
   - **cocotb** testbench files

4 Simulation

There are a few different simulations that can be run for this core.

4.1 iverilog

iverilog is used for simple test benches for quick verification, visually, of the core.

4.2 cocotb

Future simulations will use cocotb. This feature is not yet implemented.

5 Module Documentation

- **axis_1553_encoder** Interfaces AXIS to the PMOD1553.

The next sections document the module in great detail.

axis_1553_encoder.v

AUTHORS

JAY CONVERTINO

DATES

2021/05/17

INFORMATION

Brief

AXIS MIL-STD-1553 ENCODER

License MIT

axis_1553_encoder

```
module axis_1553_encoder #(
parameter
CLOCK_SPEED
 =
2000000,
parameter
SAMPLE_RATE
 =
2000000
) ( input aclk, input arstn, input [15:0] s_axis_tdata, input s_axis_tvalid,
```

AXI streaming to MIL-STD-1553 encoder. This encoder can be used at 2 Mhz or above. TDATA is 16 bit data to be transmitted. TUSER sets how the core works.

Parameters

CLOCK_SPEED This is the aclk frequency in Hz, must be 2 MHz or above.
parameter

SAMPLE_RATE 2 MHz or above rate that is an even divisor of CLOCK_SPEED
parameter

Ports

aclk Clock for all logic

arstn Negative reset

s_axis_tdata Input data for 1553 encoder.

s_axis_tvalid When set active high the input data is valid.

s_axis_tuser Information about the AXIS data {TYY,NA,I,P}

Bits explained below:

```
- TYY = TYPE OF DATA
      - 000 = NA
      - 001 = REG (NOT IMPLIMENTED)
      - 010 = DATA
      - 100 = CMD/STATUS
- D   = DELAY ENABLED
- I   = INVERT DATA
- P   = PARITY
      - 1 = ODD
      - 0 = EVEN
```

s_axis_tready When active high the device is ready for input data.

diff Output data in TTL differential format.

en_diff When diff is valid data, this is active high and can be used to switch a mux.

base_1553_clock_rate

```
localparam integer base_1553_clock_rate = 1000000
```

1553 base clock rate

samples_per_mhz

```
localparam integer samples_per_mhz = SAMPLE_RATE / base_1553_clock_rate
```

sample rate to caputre transmission bits at

cycles_per_mhz

```
localparam integer cycles_per_mhz = CLOCK_SPEED / base_1553_clock_rate
```

calculate the number of cycles the clock changes per period

samples_to_skip

```
localparam integer samples_to_skip = (
 (cycles_per_mhz > samples_per_mhz) ? cycles_per_mhz / samples_per_mhz -
1
:
0
)
```

calculate the number of samples to skip

bit_rate_per_mhz

```
localparam integer bit_rate_per_mhz = samples_per_mhz
```

bit rate per mhz

delay_time

```
localparam integer delay_time = cycles_per_mhz * 4
```

delay time, 4 is for 4 us (min 1553 time)

sync_pulse_len

```
localparam integer sync_pulse_len = bit_rate_per_mhz * 3
```

sync pulse length

bits_per_trans

```
localparam integer bits_per_trans = 20
```

bits per transmission

synth_bits_per_trans

```
localparam integer synth_bits_per_trans = (
bits_per_trans*bit_rate_per_mhz
)
```

sync bits per trans

bit_pattern

```
localparam [(
bit_rate_per_mhz
)-1:0]bit_pattern = {{bit_rate_per_mhz/2{1'b1}}, {bit_rate_per_mhz/2{1'b0}}
```

create the bit pattern. This is based on outputing data on the negative and positive. This allows the encoder to run down to 1 mhz.

synth_clk

```
localparam [synth_bits_per_trans-1:0]synth_clk = {
bits_per_trans{bit_pattern}
 }
```

synth clock is the clock constructed by the repeating the bit pattern. this is intended to be a representation of the clock. Captured at a bit_rate_per_mhz of a 1mhz clock.

sync_cmd_stat

```
localparam [sync_pulse_len-1:0]sync_cmd_stat = {
                                                {
sync_pulse_len/2{1'b0}},
                                                {
sync_pulse_len/2{1'b1}}
}
```

sync pulse command

sync_data

```
localparam [sync_pulse_len-1:0]sync_data = {
                                                {
sync_pulse_len/2{1'b1}},
                                                {
sync_pulse_len/2{1'b0}}
}
```

sync pulse data

cmd_data

```
localparam cmd_data = 3'b010
```

tuser decode for data

cmd_data

tuser decode for command

cmd_data

enable diff output

STATE MACHINE

Variables that makeup the encoder state machine.

data_cap

```
localparam data_cap = 3'd1
```

data capture

data_invert

```
localparam data_invert = 3'd2
```

invert data

parity_gen

```
localparam parity_gen = 3'd3
```

parity generator

process

```
localparam process = 3'd4
```

command processor

pause_ck

```
localparam pause_ck = 3'd5
```

check for pause (4us)

trans

```
localparam trans = 3'd6
```

transmit data

error

```
localparam error = 3'd0
```

someone made a whoops