

axis_data_to_axis_string.v

AUTHORS

JAY CONVERTINO

DATES

2022/09/19

INFORMATION

Brief

Parse raw binary data into ASCII string output.

License MIT

Copyright 2022 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

axis_data_to_axis_string

```
module axis_data_to_axis_string #(
    parameter
    DELIMITER
    =
    ",",
    parameter
    TERMINATION
    =
    "\n",
    parameter
    SBUS_WIDTH
    =
    1,
    parameter
```

```

USER_WIDTH
=
4,
parameter
DEST_WIDTH
=
4,
parameter
PREFIX_LEN
=
1,
parameter
DATA_PREFIX
=
"##",
parameter
DEST_PREFIX
=
"&",
parameter
USER_PREFIX
=
" * "
) ( input aclk, input arstn, input [(SBUS_WIDTH*8)-1:0] s_axis_tdata, input

```

Parse raw binary data into ASCII string output.

Parameters

DELIMITER parameter	break value between multiple strings
TERMINATION parameter	termination value of full string from serial port, byte only. (\n = 0A \r = 0D).
SBUS_WIDTH parameter	bus width of slave (data) input
USER_WIDTH parameter	user width of slave bus, only in 4 bit nibbles, and at least 4 bits.
DEST_WIDTH parameter	dest width of slave bus, only in 4 bit nibbles, and at least 4 bits.
PREFIX_LEN parameter	length of following prefix strings.
DATA_PREFIX parameter	prefix for data hex strings
DEST_PREFIX parameter	prefix for destination hex strings
USER_PREFIX parameter	prefix for user hex strings

Ports

aclk	Clock for AXIS
arstn	Negative reset for AXIS
s_axis_tdata	Input data
s_axis_tvalid	When set active high the input data is valid
s_axis_tuser	User data to convert.
s_axis_tdest	Destination data to convert
s_axis_tready	When active high the device is ready for input data.
m_axis_tdata	Output data

m_axis_tvalid	When active high the output data is valid
m_axis_tready	When set active high the output device is ready for data.

VARIABLES

s_axis_tready

```
assign s_axis_tready = (
    arstn
    :
    0
)
```

(counter == 0) ? 1 &

ready if count is zero, this is a FWFT so no worries in pumping out data.

m_axis_tdata

```
assign m_axis_tdata = char_buffer[STRING_LEN*8-1 -:8]
```

output whatever is in the character buffer.

m_axis_tvalid

```
assign m_axis_tvalid = (
    1
    :
    0
)
```

counter > 0 ?

Counter greater than 0? Valid output is available.