tb_axis.v

AUTHORS

JAY CONVERTINO

DATES

2022/10/24

INFORMATION

Brief

Test bench for axis_data_to_axis_string using axis stim and clock stim.

License MIT

tb_axis

```
module tb_axis #(
parameter
IN_FILE_NAME
  =
"in.bin",
parameter
OUT_FILE_NAME
  =
"out.bin",
parameter
RAND_READY
  =
0
)
```

Test bench for axis_data_to_axis_string. This will run a file through the system and write its output. These can then be compared to check for errors. If the files are identical, no errors. A FST file will be written.

Parameters

IN_FILE_NAME parameter	File name for input.
OUT_FILE_NAME parameter	File name for output.
RAND_READY parameter	0 = no random ready. 1 = randomize ready.

INSTANTIATED MODULES

clk_stim

```
clk_stimulus #(
                                                                                .
CLOCKS(1),
                                                                                .
CLOCK_BASE(1000000),
                                                                                .
CLOCK_INC(1000),
                                                                                .
RESETS(1),
                                                                                .
RESET_BASE(2000),
                                                                                .
RESET_INC(100)
) clk_stim ( .clkv(tb_dut_clk), .rstnv(tb_dut_rstn), .rstv() )
```

Generate a 50/50 duty cycle set of clocks and reset.

slave_axis_stim

```
slave_axis_stimulus #(
                                                                                .
BUS_WIDTH(BUS_WIDTH),
                                                                                .
USER_WIDTH(USER_WIDTH),
                                                                                .
DEST_WIDTH(DEST_WIDTH),
                                                                                .
FILE(IN_FILE_NAME)
) slave_axis_stim ( .m_axis_aclk(tb_dut_clk), .m_axis_arstn(tb_dut_rstn), .r
```

Device under test SLAVE stimulus module.

dut

```
axis_data_to_axis_string #(
                                                                                .
DELIMITER(";"),
                                                                                .
```

```
 TERMINATION("\n"),                                                                .
 SBUS_WIDTH(BUS_WIDTH),                                                            .
 USER_WIDTH(USER_WIDTH),                                                           .
 DEST_WIDTH(DEST_WIDTH),                                                           .
 PREFIX_LEN(1),                                                                    .
 DATA_PREFIX("#"),                                                                 .
 DEST_PREFIX("&"),                                                                 .
 USER_PREFIX("*")
) dut ( .aclk(tb_dut_clk), .arstn(tb_dut_rstn), .m_axis_tdata(tb_dut_data),
```

Device under test, axis_data_width_converter

master_axis_stim

```
 master_axis_stimulus #(                                                           .
 BUS_WIDTH(BUS_WIDTH),                                                             .
 USER_WIDTH(USER_WIDTH),                                                           .
 DEST_WIDTH(DEST_WIDTH),                                                           .
 RAND_READY(RAND_READY),                                                           .
 FILE(OUT_FILE_NAME)
) master_axis_stim ( .s_axis_aclk(tb_dut_clk), .s_axis_arstn(tb_dut_rstn),
```

Devie under test MASTER stimulus module.