

tb_axis.v

AUTHORS

JAY CONVERTINO

DATES

2024/12/09

INFORMATION

Brief

Test bench for axis_data_width_converter using axis stim and clock stim.

License MIT

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

tb_axis

```
module tb_axis #(
  parameter
  IN_FILE_NAME
  =
  in.bin,
  parameter
  OUT_FILE_NAME
  =
  out.bin,
  parameter
  RAND_READY
```

```

    =
    0,
    parameter
    SLAVE_WIDTH
    =
    2,
    parameter
    MASTER_WIDTH
    =
    4
  )()

```

Test bench for axis_fifo. This will run a file through the system and write its output. These can then be compared to check for errors. If the files are identical, no errors. A FST file will be written.

Parameters

IN_FILE_NAME parameter	File name for input.
OUT_FILE_NAME parameter	File name for output.
RAND_READY parameter	0 = no random ready. 1 = randomize ready.
SLAVE_WIDTH parameter	Width of the slave input bus in bytes
MASTER_WIDTH parameter	Width of the master output bus in bytes

INSTANTIATED MODULES

clk_stim

```

clk_stimulus #(
    CLOCKS(1),
    CLOCK_BASE(1000000),
    CLOCK_INC(1000),
    RESETS(1),
    RESET_BASE(2000),
    RESET_INC(100)
) clk_stim ( .clkv(tb_dut_clk), .rstnv(tb_dut_rstn), .rstv() )

```

Generate a 50/50 duty cycle set of clocks and reset.

slave_axis_stim

```

slave_axis_stimulus #(
    BUS_WIDTH(SBUS_WIDTH),
    USER_WIDTH(USER_WIDTH),

```

```

DEST_WIDTH(DEST_WIDTH),
FILE(IN_FILE_NAME)
) slave_axis_stim ( .m_axis_aclk(tb_dut_clk), .m_axis_arstn(tb_dut_rstn), .m

```

Device under test SLAVE stimulus module.

dut

```

axis_data_width_converter #(
MASTER_WIDTH(MBUS_WIDTH),
SLAVE_WIDTH(SBUS_WIDTH)
) dut ( .aclk(tb_dut_clk), .arstn(tb_dut_rstn), .m_axis_tdata(tb_dut_data),

```

Device under test, axis_data_width_converter

master_axis_stim

```

master_axis_stimulus #(
BUS_WIDTH(MBUS_WIDTH),
USER_WIDTH(USER_WIDTH),
DEST_WIDTH(DEST_WIDTH),
RAND_READY(RAND_READY),
FILE(OUT_FILE_NAME)
) master_axis_stim ( .s_axis_aclk(tb_dut_clk), .s_axis_arstn(tb_dut_rstn),

```

Devie under test MASTER stimulus module.