

axis_ctrl_fifo.v

AUTHORS

JAY CONVERTINO

DATES

2021/06/29

INFORMATION

Brief

Wraps the standard FIFO with an axi streaming interface.

License MIT

Copyright 2021 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

axis_fifo_ctrl

```
module axis_fifo_ctrl #(
    parameter
    BUS_WIDTH
    =
    1,
    parameter
    FIFO_WIDTH
    =
    8,
    parameter
    FIFO_POWER
```

```

    =
    8,
    parameter
    USER_WIDTH
    =
    1,
    parameter
    DEST_WIDTH
    =
    1,
    parameter
    PACKET_MODE
    =
    0
) ( input m_axis_aclk, input m_axis_arstn, output m_axis_tvalid, input m_axi

```

AXIS fifo control

Parameters

BUS_WIDTH parameter	Width of the axis data bus input/output in bytes. FIFO_WIDTH - FIFO_POWER -
USER_WIDTH parameter	Width of the axis user bus input/output in bits.
DEST_WIDTH parameter	Width of the axis dest bus input/output in bits.
PACKET_MODE parameter	Set axis fifo to wait for tlast before allowing a read on master port output.

Ports

m_axis_aclk	Clock for AXIS
m_axis_arstn	Negative reset for AXIS
m_axis_tvalid	When active high the output data is valid
m_axis_tready	When set active high the output device is ready for data.
m_axis_tdata	Output data
m_axis_tkeep	Output valid byte indicator
m_axis_tlast	Indicates last word in stream.
m_axis_tuser	Output user bus
m_axis_tdest	Output destination
s_axis_tlast	Is this the last word in the stream (active high).
rd_en	Active high enable of read interface.
rd_valid	Active high output that the data is valid.
rd_data	Output data
rd_empty	Active high output when read is empty.
wr_full	Active high output that the FIFO is full.