

tb_cocotb.v

AUTHORS

JAY CONVERTINO

DATES

2025/04/24

INFORMATION

Brief

Test bench wrapper for cocotb

License MIT

Copyright 2025 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

tb_cocotb

```
module tb_cocotb #(
  parameter
    CLOCK_SPEED
    =
    20000000,
  parameter
    BUS_WIDTH
    =
    4,
  parameter
    SELECT_WIDTH
    =
    1,
  parameter
```

```

    RATE
    =
    115200
) ( input aclk, input arstn, input [BUS_WIDTH*8-1:0] s_axis_tdata, input s_

```

SPI core with axis input/output data. Read/Write is size of BUS_WIDTH bytes. Write activates core for read.

Parameters

CLOCK_SPEED parameter	This is the aclk frequency in Hz, this is the the frequency used for the bus and is divided by the rate.
BUS_WIDTH parameter	AXIS data width in bytes.
SELECT_WIDTH parameter	Bit width of the slave select.
RATE parameter	Select the data rate of the spi core.

Ports

aclk	Clock for AXIS
arstn	Negative reset for AXIS
s_axis_tdata	Input data for UART TX.
s_axis_tvalid	When set active high the input data is valid
s_axis_tready	When active high the device is ready for input data.
m_axis_tdata	Output data from UART RX
m_axis_tvalid	When active high the output data is valid
m_axis_tready	When set active high the output device is ready for data.
sclk	spi clock, should only drive output pins to devices.
mosi	transmit for master output
miso	receive for master input
ssn_i	slave select input
ssn_o	slave select output
rate parameter	output rate of spi core.
cpol	clock polarity of spi_clk
cpha	clock phase of spi_clk
miso_dcount	Current number of input bits available from parallel register.
mosi_dcount	current number of output bits available to serial shift output.

INSTANTIATED MODULES

dut

```

axis_spi_master #(
    CLOCK_SPEED(CLOCK_SPEED),
    BUS_WIDTH(BUS_WIDTH),
    SELECT_WIDTH(SELECT_WIDTH)

```

```
| ) dut ( .aclk(aclk), .arstn(arstn), .s_axis_tdata(s_axis_tdata), .s_axis_t
```

Device under test, axis_spi_master