

axis_string_to_axis_data.v

AUTHORS

JAY CONVERTINO

DATES

2022/09/19

INFORMATION

Brief

Take input string data and process it into tuser/tdata output.

License MIT

Copyright 2022 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

axis_string_to_axis_data

```
module axis_string_to_axis_data #(
  parameter
  DELIMITER
  =
  " , "
  parameter
  TERMINATION
  =
  "\n"
  parameter
  STRING_LEN
  =
  4,
  parameter
```

```

    MBUS_WIDTH
    =
    1,
    parameter
    USER_WIDTH
    =
    4,
    parameter
    DEST_WIDTH
    =
    4,
    parameter
    PREFIX_LEN
    =
    1,
    parameter
    DATA_PREFIX
    =
    "#",
    parameter
    DEST_PREFIX
    =
    "&",
    parameter
    USER_PREFIX
    =
    "+",
    parameter
    KEYWORD_LEN
    =
    3,
    parameter
    SET_KEYWORD
    =
    "set",
    parameter
    CLR_KEYWORD
    =
    "clr"
) ( input aclk, input arstn, output [(MBUS_WIDTH*8)-1:0] m_axis_tdata, output

```

Convert string data to raw binary data for axis bus.

Parameters

DELIMITER parameter	break value between multiple strings
TERMINATION parameter	termination value of full string from serial port, byte only. (\n = 0A \r = 0D).
STRING_LEN parameter	max length of string including delimiter
MBUS_WIDTH parameter	bus width of master (data) output
USER_WIDTH parameter	user width of master bus, only in 4 bit nibbles, and at least 4 bits.
DEST_WIDTH parameter	dest width of master bus, only in 4 bit nibbles, and at least 4 bits.
PREFIX_LEN parameter	length of following prefix strings in bytes.
DATA_PREFIX parameter	prefix for data hex strings
DEST_PREFIX	prefix for destination hex strings

parameter

USER_PREFIX prefix for user hex strings

parameter

KEYWORD_LEN length of the following keywords

parameter

SET_KEYWORD keyword to output data over tdata,tuser,tdest on master interface.

parameter

CLR_KEYWORD keyword to clear output data and buffers of master interface.

parameter

Ports

aclk Clock for AXIS

arstn Negative reset for AXIS

m_axis_tdata Output data

m_axis_tvalid When active high the output data is valid

m_axis_tuser Output user data

m_axis_tdest Output destination data

m_axis_tready When set active high the output device is ready for data.

s_axis_tdata Input string data

s_axis_tvalid When set active high the input data is valid

s_axis_tready When active high the device is ready for input data.