

axi_lite_1553.v

AUTHORS

JAY CONVERTINO

DATES

2024/10/17

INFORMATION

Brief

AXI Lite 1553 is a core for interfacing with 1553 devices over the AXI lite bus.

License MIT

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

axi_lite_1553

```
module axi_lite_1553 #(
  parameter
    ADDRESS_WIDTH
    =
    32,
  parameter
    BUS_WIDTH
    =
    4,
  parameter
    CLOCK_SPEED
    =
    100000000
)
```

```

input
aclk,
input
arstn,
input
s_axi_awvalid,
input
[ADDRESS_WIDTH-1:0]
s_axi_awaddr,
input
[ 2:0]
s_axi_awprot,
output
s_axi_awready,
input
s_axi_wvalid,
input
[BUS_WIDTH*8-1:0]
s_axi_wdata,
input
[ 3:0]
s_axi_wstrb,
output
s_axi_wready,
output
s_axi_bvalid,
output
[ 1:0]
s_axi_bresp,
input
s_axi_bready,
input
s_axi_arvalid,
input
[ADDRESS_WIDTH-1:0]
s_axi_araddr,
input
[ 2:0]
s_axi_arprot,
output
s_axi_arready,
output
s_axi_rvalid,
output
[BUS_WIDTH*8-1:0]
s_axi_rdata,
output
[ 1:0]
s_axi_rresp,
input
s_axi_rready,
input
[1:0]
rx_diff,
output
[1:0]
tx_diff,
output
tx_active,
output
irq
)

```

(

AXI Lite based 1553 communications device.

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus, max 32 bit.
BUS_WIDTH parameter	Width in bytes of the data bus.
CLOCK_SPEED parameter	This is the aclk frequency in Hz

Ports

aclk input	Clock for all devices in the core
arstn input	Negative reset
s_axi_awvalid input	Axi Lite aw valid
s_axi_awaddr input [ADDRESS_WIDTH- 1:0]	Axi Lite aw addr
s_axi_awprot input [2:0]	Axi Lite aw prot
s_axi_awready output [2:0]	Axi Lite aw ready
s_axi_wvalid input [2:0]	Axi Lite w valid
s_axi_wdata input [BUS_WIDTH* 8- 1:0]	Axi Lite w data
s_axi_wstrb input [3:0]	Axi Lite w strb
s_axi_wready output [3:0]	Axi Lite w ready
s_axi_bvalid output [3:0]	Axi Lite b valid
s_axi_bresp output [1:0]	Axi Lite b resp
s_axi_bready input [1:0]	Axi Lite b ready
s_axi_arvalid input [1:0]	Axi Lite ar valid
s_axi_araddr input [ADDRESS_WIDTH- 1:0]	Axi Lite ar addr
s_axi_arprot input [2:0]	Axi Lite ar prot
s_axi_arready output [2:0]	Axi Lite ar ready
s_axi_rvalid output [2:0]	Axi Lite r valid
s_axi_rdata output [BUS_WIDTH* 8- 1:0]	Axi Lite r data
s_axi_rresp output [1:0]	Axi Lite r resp
s_axi_rready input [1:0]	Axi Lite r ready
rx_diff input [1:0]	Input differential signal for 1553 bus

tx_diff output [1:0]	Output differential signal for 1553 bus
tx_active output [1:0]	Enable output of differential signal (for signal switching on 1553 module)
irq output [1:0]	Interrupt when data is received

up_rreq

```
wire up_rreq
```

uP read bus request

up_rack

```
wire up_rack
```

uP read bus acknowledge

up_raddr

```
wire [ADDRESS_WIDTH-(
BUS_WIDTH
2
)-1:0] up_raddr
```

uP read bus address

up_rdata

```
wire [31:0] up_rdata
```

uP read bus request

up_wreq

```
wire up_wreq
```

uP write bus request

up_wack

```
wire up_wack
```

uP write bus acknowledge

up_waddr

```
wire [ADDRESS_WIDTH-(  
BUS_WIDTH  
2  
)-1:0] up_waddr
```

uP write bus address

up_wdata

```
wire [31:0] up_wdata
```

uP write bus data

INSTANTIATED MODULES

inst_up_axi

Module instance of up_axi for the AXI Lite bus to the uP bus.

inst_up_1553

Module instance of up_1553 creating a Logic wrapper for 1553 bus cores to interface with uP bus.