

tb_cocotb_axi_lite.v

AUTHORS

JAY CONVERTINO

DATES

2025/04/01

INFORMATION

Brief

Test bench wrapper for cocotb

License MIT

Copyright 2025 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.BUS_WIDTH

tb_cocotb

```
module tb_cocotb #(
  parameter
    ADDRESS_WIDTH
    =
    32,
  parameter
    BUS_WIDTH
    =
    4,
  parameter
    CLOCK_SPEED
    =
    100000000
)
```

```

input
aclk,
input
arstn,
input
s_axi_awvalid,
input
[ADDRESS_WIDTH-1:0]
s_axi_awaddr,
input
[ 2:0]
s_axi_awprot,
output
s_axi_awready,
input
s_axi_wvalid,
input
[BUS_WIDTH*8-1:0]
s_axi_wdata,
input
[ 3:0]
s_axi_wstrb,
output
s_axi_wready,
output
s_axi_bvalid,
output
[ 1:0]
s_axi_bresp,
input
s_axi_bready,
input
s_axi_arvalid,
input
[ADDRESS_WIDTH-1:0]
s_axi_araddr,
input
[ 2:0]
s_axi_arprot,
output
s_axi_arready,
output
s_axi_rvalid,
output
[BUS_WIDTH*8-1:0]
s_axi_rdata,
output
[ 1:0]
s_axi_rresp,
input
s_axi_rready,
input
[1:0]
rx_diff,
output
[1:0]
tx_diff,
output
tx_active,
output
irq
)

```

(

AXI Lite slave to AXI Lite 1553 DUT

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus, max 32 bit.
BUS_WIDTH parameter	Width in bytes of the data bus.
CLOCK_SPEED parameter	This is the aclk frequency in Hz

Ports

aclk input	Clock for all devices in the core
arstn input	Negative reset
s_axi_awvalid input	Axi Lite aw valid
s_axi_awaddr input [ADDRESS_WIDTH- 1:0]	Axi Lite aw addr
s_axi_awprot input [2:0]	Axi Lite aw prot
s_axi_awready output [2:0]	Axi Lite aw ready
s_axi_wvalid input [2:0]	Axi Lite w valid
s_axi_wdata input [BUS_WIDTH* 8- 1:0]	Axi Lite w data
s_axi_wstrb input [3:0]	Axi Lite w strb
s_axi_wready output [3:0]	Axi Lite w ready
s_axi_bvalid output [3:0]	Axi Lite b valid
s_axi_bresp output [1:0]	Axi Lite b resp
s_axi_bready input [1:0]	Axi Lite b ready
s_axi_arvalid input [1:0]	Axi Lite ar valid
s_axi_araddr input [ADDRESS_WIDTH- 1:0]	Axi Lite ar addr
s_axi_arprot input [2:0]	Axi Lite ar prot
s_axi_arready output [2:0]	Axi Lite ar ready
s_axi_rvalid output [2:0]	Axi Lite r valid
s_axi_rdata output [BUS_WIDTH* 8- 1:0]	Axi Lite r data
s_axi_rresp output [1:0]	Axi Lite r resp
s_axi_rready input [1:0]	Axi Lite r ready
rx_diff input [1:0]	Input differential signal for 1553 bus

tx_diff	Output differential signal for 1553 bus
output [1:0]	
tx_active	Enable output of differential signal (for signal switching on 1553 module)
output [1:0]	
irq	Interrupt when data is received
output [1:0]	

INSTANTIATED MODULES

dut

Device under test, axi_lite_1553