

wishbone_classic_1553.v

AUTHORS

JAY CONVERTINO

DATES

2024/10/17

INFORMATION

Brief

wishbone classic to uP core for 1553 comms.

License MIT

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

wishbone_classic_1553

```
module wishbone_classic_1553 #(
  parameter
  ADDRESS_WIDTH
  =
  32,
  parameter
  BUS_WIDTH
  =
  4,
  parameter
  CLOCK_SPEED
```

```

=
100000000,
parameter
SAMPLE_RATE
=
2000000,
parameter
BIT_SLICE_OFFSET
=
0,
parameter
INVERT_DATA
=
0,
parameter
SAMPLE_SELECT
=
0
) ( input clk, input rst, input s_wb_cyc, input s_wb_stb, input s_wb_we, input s_wb_addr, input s_wb_data_i, input s_wb_sel, input s_wb_bte, input s_wb_cti, input s_wb_ack, input s_wb_data_o, input s_wb_err )

```

Wishbone Calssic based 1553 communications device.

Parameters

ADDRESS_WIDTH parameter	Width of the address bus in bits
BUS_WIDTH parameter	Width of the data bus in bytes.
CLOCK_SPEED parameter	This is the aclk frequency in Hz
SAMPLE_RATE parameter	Rate of in which to sample the 1553 bus. Must be 2 MHz or more and less than aclk. This is in Hz. BIT_SLICE_OFFSET- Adjust where the sample is taken from the input.
INVERT_DATA parameter	Invert all 1553 bits coming in and out.
SAMPLE_SELECT parameter	Adjust where in the array of samples to select a bit.

Ports

clk	Clock for all devices in the core
rst	Positive reset
s_wb_cyc	Bus Cycle in process
s_wb_stb	Valid data transfer cycle
s_wb_we	Active High write, low read
s_wb_addr	Bus address
s_wb_data_i	Input data
s_wb_sel	Device Select
s_wb_bte	Burst Type Extension
s_wb_cti	Cycle Type
s_wb_ack	Bus transaction terminated
s_wb_data_o	Output data
s_wb_err	Active high when a bus error is present

i_diff	Input differential signal for 1553 bus
o_diff	Output differential signal for 1553 bus
en_o_diff	Enable output of differential signal (for signal switching on 1553 module)
irq	Interrupt when data is received

up_rreq

```
wire up_rreq
```

uP read bus request

up_rack

```
wire up_rack
```

uP read bus acknowledge

up_raddr

```
wire [ADDRESS_WIDTH-3:0] up_raddr
```

uP read bus address

up_rdata

```
wire [31:0] up_rdata
```

uP read bus request

up_wreq

```
wire up_wreq
```

uP write bus request

up_wack

```
wire up_wack
```

uP write bus acknowledge

up_waddr

```
wire [ADDRESS_WIDTH-3:0] up_waddr
```

uP write bus address

up_wdata

```
wire [31:0] up_wdata
```

uP write bus data

INSTANTIATED MODULES

inst_up_wishbone_classic

```
up_wishbone_classic #(
    ADDRESS_WIDTH(ADDRESS_WIDTH),
    BUS_WIDTH(BUS_WIDTH)
) inst_up_wishbone_classic ( .clk(clk), .rst(rst), .s_wb_cyc(s_wb_cyc), .s_v
```

Module instance of up_wishbone_classic for the Wishbone Classic bus to the uP bus.

inst_up_1553

```
up_1553 #(
    ADDRESS_WIDTH(ADDRESS_WIDTH),
    BUS_WIDTH(BUS_WIDTH),
    CLOCK_SPEED(CLOCK_SPEED),
    SAMPLE_RATE(SAMPLE_RATE),
    BIT_SLICE_OFFSET(BIT_SLICE_OFFSET),
    INVERT_DATA(INVERT_DATA),
    SAMPLE_SELECT(SAMPLE_SELECT)
) inst_up_1553 ( .clk(aclk), .rstn(arstn), .up_rreq(up_rreq), .up_rack(up_rack)
```

Module instance of up_1553 creating a Logic wrapper for 1553 bus cores to interface with uP bus.