

tb_cocotb_up.v

AUTHORS

JAY CONVERTINO

DATES

2025/04/01

INFORMATION

Brief

Test bench wrapper for cocotb

License MIT

Copyright 2025 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.BUS_WIDTH

tb_cocotb

```
module tb_cocotb #(
  parameter
    ADDRESS_WIDTH
    =
    32,
  parameter
    BUS_WIDTH
    =
    4,
  parameter
    CLOCK_SPEED
    =
    100000000,
  parameter
```

```

SAMPLE_RATE
=
2000000,
parameter
BIT_SLICE_OFFSET
=
0,
parameter
INVERT_DATA
=
0,
parameter
SAMPLE_SELECT
=
0
) ( input clk, input rstn, input up_rreq, output up_rack, input [ADDRESS_WID

```

uP 1553 testbench

Parameters

ADDRESS_WIDTH parameter	Width of the uP address port, max 32 bit.
BUS_WIDTH parameter	Width of the uP bus data port.
CLOCK_SPEED parameter	This is the aclk frequency in Hz
SAMPLE_RATE parameter	Rate of in which to sample the 1553 bus. Must be 2 MHz or more and less than aclk. This is in Hz. BIT_SLICE_OFFSET- Adjust where the sample is taken from the input.
INVERT_DATA parameter	Invert all 1553 bits coming in and out.
SAMPLE_SELECT parameter	Adjust where in the array of samples to select a bit.

Ports

clk	Clock for all devices in the core
rstn	Negative reset
up_rreq	uP bus read request
up_rack	uP bus read ack
up_raddr	uP bus read address
up_rdata	uP bus read data
up_wreq	uP bus write request
up_wack	uP bus write ack
up_waddr	uP bus write address
up_wdata	uP bus write data
i_diff	Input differential signal for 1553 bus
o_diff	Output differential signal for 1553 bus
en_o_diff	Enable output of differential signal (for signal switching on 1553 module)
irq	Interrupt when data is received

INSTANTIATED MODULES

dut

```
up_1553 #(
    ADDRESS_WIDTH(ADDRESS_WIDTH),
    BUS_WIDTH(BUS_WIDTH),
    CLOCK_SPEED(CLOCK_SPEED),
    SAMPLE_RATE(SAMPLE_RATE),
    BIT_SLICE_OFFSET(BIT_SLICE_OFFSET),
    INVERT_DATA(INVERT_DATA),
    SAMPLE_SELECT(SAMPLE_SELECT)
) dut ( .clk(clk), .rstn(rstn), .up_rreq(up_rreq), .up_rack(up_rack), .up_rack
```

Device under test, up_1553