up_1553.v

AUTHORS

JAY CONVERTINO

DATES

2024/10/17

INFORMATION

Brief

uP Core for interfacing with simple 1553 communications.

License MIT

up_1553

```
module up_1553 #(
parameter
ADDRESS_WIDTH
 =
32,
parameter
BUS_WIDTH
 =
4,
parameter
CLOCK_SPEED
 =
100000000,
parameter
```

```
SAMPLE_RATE
  =
2000000,
parameter
BIT_SLICE_OFFSET
  =
0,
parameter
INVERT_DATA
  =
0,
parameter
SAMPLE_SELECT
  =
0
) ( input clk, input rstn, input up_rreq, output up_rack, input [ADDRESS_WI
```

uP based 1553 communications device.

Parameters

ADDRESS_WIDTH	Width of the uP address port, max 32 bit.	
parameter		
BUS_WIDTH	Width of the uP bus data port.	
parameter		
CLOCK_SPEED	This is the aclk frequency in Hz	
parameter		
SAMPLE_RATE	Rate of in which to sample the 1553 bus. Must be 2 MHz or more and less than aclk. This is in Hz. BIT_SLICE_OFFSET- Adjust where the sample is taken from the input.	
parameter		
INVERT_DATA	Invert all 1553 bits coming in and out.	
parameter		
SAMPLE_SELECT	Adjust where in the array of samples to select a bit.	
parameter		

Ports

clk	Clock for all devices in the core
rstn	Negative reset
up_rreq	uP bus read request
up_rack	uP bus read ack
up_raddr	uP bus read address
up_rdata	uP bus read data
up_wreq	uP bus write request
up_wack	uP bus write ack
up_waddr	uP bus write address
up_wdata	uP bus write data
i_diff	Input differential signal for 1553 bus
o_diff	Output differential signal for 1553 bus
en_o_diff	Enable output of differential signal (for signal switching on 1553 module)
irq	Interrupt when data is received

DIVISOR

```
localparam DIVISOR = BUS_WIDTH/2
```

Divide the address register default location for 1 byte access to multi byte access. (register offsets are byte offsets).

FIFO_DEPTH

```
localparam FIFO_DEPTH = 16
```

Depth of the fifo, matches UART LITE (xilinx), so I kept this just cause

DATA_BITS

```
localparam DATA_BITS = 24
```

Number of bits in RX/TX FIFO that are valid.

REGISTER INFORMATION

Core has 4 registers at the offsets that follow.

RX_FIFO_REG h0
TX_FIFO_REG h4
STATUS_REG h8
CONTROL_REG hC

RX_FIFO_REG

```
localparam RX_FIFO_REG = 4'h0 >> DIVISOR
```

Defines the address offset for RX FIFO

RX FIFO REGISTER		
31:24	23:16	15:0
UNUSED	STATUS DATA	RECEIVED DATA

Valid bits are from 23:0. Bits 23:16 are status bits information about the data. Bit 15:0 are data.

Status Bits

{TY:3,NA:1,D:1,I:1,P:1}

TY Type is 3 bits, 000 NA, 001 = REG, 010 = DATA, 100 = CMD/STATUS
NA Unused is 1 bit
D Delay Enabled is 1 bit, 1 is there was be a delay of 4 us or more, or 0 no delay.
I Data invert enabled is 1 bit, 1 inverted in the core at synth, 0 it is not.
P Parity Good is 1 bit, 1 is Good, 0 is Bad

TX_FIFO_REG

```
localparam TX_FIFO_REG = 4'h4 >> DIVISOR
```

Defines the address offset to write the TX FIFO.

TX FIFO REGISTER		
31:24	23:16	15:0
UNUSED	STATUS DATA	TRANSMIT DATA

Valid bits are from 23:0. Bits 23:16 are status bits information about the data. Bit 15:0 are data.

Status Bits

{TY:3,NA:1,D:1,I:1,P:1}

TY Type is 3 bits, 000 NA, 001 = REG, 010 = DATA, 100 = CMD/STATUS

NA Unused is 1 bit

D Delay Enabled is 1 bit, 1 is there must be a delay of 4 us or more, or 0 no delay.

I Data invert enabled is 1 bit, set to 1 to invert data in the core, 0 it is not.

P Parity Type is 1 bit, 1 is ODD, 0 is EVEN

STATUS_REG

```
localparam STATUS_REG = 4'h8 >> DIVISOR
```

Defines the address offset to read the status bits.

STATUS REGISTER								
31:8	7	6	5	4	3	2	1	0
UNUSED	PC	DI	Delay	irq_en	tx_full	tx_empty	rx_full	rx_valid

Status Register Bits

PC 7, Parity check passed?

DI 6, Build time option to invert data from the core, 1 is active.

Delay 5, Message had a 4uS delay.

irq_en 4, 1 when the IRQ is enabled by CONTROL_REG

tx_full 3, When 1 the tx fifo is full.

tx_empty 2, When 1 the tx fifo is empty.

rx_full 1, When 1 the rx fifo is full.

rx_valid 0, When 1 the rx fifo contains valid data.

CONTROL_REG

```
localparam CONTROL_REG = 4'hC
```

Defines the address offset to set the control bits.

CONTROL REGISTER				
31:5	4	3:2	1	0
UNUSED	ENA_INTR_BIT	UNUSED	RST_RX_BIT	RST_TX_BIT

See Also: ENABLE_INTR_BIT, RESET_RX_BIT, RESET_TX_BIT

Control Register Bits

ENABLE_INTR_BIT 4, Control Register offset bit for enabling the interrupt.

RESET_RX_BIT 1, Control Register offset bit for resetting the RX FIFO.

RESET_TX_BIT 0, Control Register offset bit for resetting the TX FIFO.

INSTANTIATED MODULES

inst_axis_1553_encoder

```
axis_1553_encoder #(
                                                                    .
CLOCK_SPEED(CLOCK_SPEED),
                                                                    .
SAMPLE_RATE(SAMPLE_RATE)
) inst_axis_1553_encoder ( .aclk(clk), .arstn(rstn), .s_axis_tdata(tx_rdata|
```

Encode incoming AXIS data into a differential 1553 data stream

inst_axis_1553_decoder

```
axis_1553_decoder #(
                                                                    .
CLOCK_SPEED(CLOCK_SPEED),
                                                                    .
SAMPLE_RATE(SAMPLE_RATE),
                                                                    .
BIT_SLICE_OFFSET(BIT_SLICE_OFFSET),
                                                                    .
INVERT_DATA(INVERT_DATA),
                                                                    .
SAMPLE_SELECT(SAMPLE_SELECT)
) inst_axis_1553_decoder ( .aclk(clk), .arstn(rstn), .m_axis_tdata(m_axis_td
```

Decode incoming differential 1553 data stream to AXIS data format.

inst_rx_fifo

```
fifo #(
                                                                    .
FIFO_DEPTH(FIFO_DEPTH),
                                                                    .
BYTE_WIDTH(BUS_WIDTH),
```

```
                                                                                .
 COUNT_WIDTH(8),                                                                .
 FWFT(1),                                                                       .
 RD_SYNC_DEPTH(0),                                                              .
 WR_SYNC_DEPTH(0),                                                              .
 DC_SYNC_DEPTH(0),                                                              .
 COUNT_DELAY(0),                                                                .
 COUNT_ENA(0),                                                                  .
 DATA_ZERO(0),                                                                  .
 ACK_ENA(0),                                                                    .
 RAM_TYPE("block")
) inst_rx_fifo ( .rd_clk(clk), .rd_rstn(rstn & r_rstn_rx_delay[0]), .rd_en(s
```

Buffer up to 16 items output from the axis_1553_encoder.

inst_tx_fifo

```
 fifo #(
                                                                                .
 FIFO_DEPTH(FIFO_DEPTH),                                                        .
 BYTE_WIDTH(BUS_WIDTH),                                                         .
 COUNT_WIDTH(8),                                                                .
 FWFT(1),                                                                       .
 RD_SYNC_DEPTH(0),                                                              .
 WR_SYNC_DEPTH(0),                                                              .
 DC_SYNC_DEPTH(0),                                                              .
 COUNT_DELAY(0),                                                                .
 COUNT_ENA(0),                                                                  .
 DATA_ZERO(0),                                                                  .
 ACK_ENA(0),                                                                    .
 RAM_TYPE("block")
) inst_tx_fifo ( .rd_clk(clk), .rd_rstn(rstn & r_rstn_tx_delay[0]), .rd_en(s
```

Buffer up to 16 items to input to the axis_1553_decoder.