

# up\_1553.v

---

## AUTHORS

---

JAY CONVERTINO

---

## DATES

---

2024/10/17

---

## INFORMATION

---

### Brief

---

uP Core for interfacing with simple 1553 communications.

### License MIT

---

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## up\_1553

---

```
module up_1553 #(
    parameter
    ADDRESS_WIDTH
    =
    32,
    parameter
    BUS_WIDTH
    =
    4,
    parameter
    CLOCK_SPEED
```

```

    =
    100000000,
    parameter
    SAMPLE_RATE
    =
    2000000,
    parameter
    BIT_SLICE_OFFSET
    =
    0,
    parameter
    INVERT_DATA
    =
    0,
    parameter
    SAMPLE_SELECT
    =
    0
) ( input clk, input rstn, input up_rreq, output up_rack, input [ADDRESS_WIDTH-1:0] up_addr, output [BUS_WIDTH-1:0] up_data )

```

uP based 1553 communications device.

## Parameters

<b>ADDRESS_WIDTH</b> parameter	Width of the uP address port.
<b>BUS_WIDTH</b> parameter	Width of the uP bus data port.
<b>CLOCK_SPEED</b> parameter	This is the aclk frequency in Hz
<b>SAMPLE_RATE</b> parameter	Rate of in which to sample the 1553 bus. Must be 2 MHz or more and less than aclk. This is in Hz. BIT_SLICE_OFFSET- Adjust where the sample is taken from the input.
<b>INVERT_DATA</b> parameter	Invert all 1553 bits coming in and out.
<b>SAMPLE_SELECT</b> parameter	Adjust where in the array of samples to select a bit.

## Ports

<b>clk</b>	Clock for all devices in the core
<b>rstn</b>	Negative reset
<b>up_rreq</b>	uP bus read request
<b>up_rack</b>	uP bus read ack
<b>up_raddr</b>	uP bus read address
<b>up_rdata</b>	uP bus read data
<b>up_wreq</b>	uP bus write request
<b>up_wack</b>	uP bus write ack
<b>up_waddr</b>	uP bus write address
<b>up_wdata</b>	uP bus write data
<b>i_diff</b>	Input differential signal for 1553 bus
<b>o_diff</b>	Output differential signal for 1553 bus
<b>en_o_diff</b>	Enable output of differential signal (for signal switching on 1553 module)
<b>irq</b>	Interrupt when data is received

## FIFO\_DEPTH

```
localparam FIFO_DEPTH = 16
```

Depth of the fifo, matches UART LITE (xilinx), so I kept this just cause

## REGISTER INFORMATION

Core has 4 registers at the offsets that follow.

**RX\_FIFO\_REG** h0

**TX\_FIFO\_REG** h4

**STATUS\_REG** h8

**CONTROL\_REG** hC

## RX\_FIFO\_REG

```
localparam RX_FIFO_REG = 4'h0
```

Defines the address offset for RX FIFO

RX FIFO REGISTER		
31:24	23:16	15:0
UNUSED	STATUS DATA	RECEIVED DATA

Valid bits are from 23:0. Bits 23:16 are information about the data. Bit 15:0 are data.

## TX\_FIFO\_REG

```
localparam TX_FIFO_REG = 4'h4
```

Defines the address offset to write the TX FIFO.

TX FIFO REGISTER		
31:24	23:16	15:0
UNUSED	STATUS DATA	TRANSMIT DATA

Valid bits are from 23:0. Bits 23:16 are information about the data. Bit 15:0 are data.

## STATUS\_REG

```
localparam STATUS_REG = 4'h8
```

Defines the address offset to read the status bits.

STATUS REGISTER								
31:8	7	6	5	4	3	2	1	0
UNUSED	PC	DI	Delay	irq_en	tx_full	tx_empty	rx_full	rx_valid

## Status Register Bits

<b>PC</b>	7, Parity check passed?
<b>DI</b>	6, Build time option to invert data from the core, 1 is active.
<b>Delay</b>	5, Message had a 4uS delay.
<b>irq_en</b>	4, 1 when the IRQ is enabled by <b>CONTROL_REG</b>
<b>tx_full</b>	3, When 1 the tx fifo is full.
<b>tx_empty</b>	2, When 1 the tx fifo is empty.
<b>rx_full</b>	1, When 1 the rx fifo is full.
<b>rx_valid</b>	0, When 1 the rx fifo contains valid data.

## CONTROL\_REG

```
localparam CONTROL_REG = 4'hC
```

Defines the address offset to set the control bits.

CONTROL REGISTER				
31:5	4	3:2	1	0
UNUSED	ENA_INTR_BIT	UNUSED	RST_RX_BIT	RST_TX_BIT

See Also: **ENABLE\_INTR\_BIT**, **RESET\_RX\_BIT**, **RESET\_TX\_BIT**

## Control Register Bits

<b>ENABLE_INTR_BIT</b>	4, Control Register offset bit for enabling the interrupt.
<b>RESET_RX_BIT</b>	1, Control Register offset bit for resetting the RX FIFO.
<b>RESET_TX_BIT</b>	0, Control Register offset bit for resetting the TX FIFO.

## INSTANTIATED MODULES

### inst\_axis\_1553\_encoder

```
axis_1553_encoder #(
    CLOCK_SPEED(CLOCK_SPEED),
    SAMPLE_RATE(SAMPLE_RATE)
) inst_axis_1553_encoder ( .aclk(clk), .arstn(rstn), .s_axis_tdata(tx_rdata|
```

Encode incoming AXIS data into a differential 1553 data stream

## inst\_axis\_1553\_decoder

```
axis_1553_decoder #(
    CLOCK_SPEED(CLOCK_SPEED),
    SAMPLE_RATE(SAMPLE_RATE),
    BIT_SLICE_OFFSET(BIT_SLICE_OFFSET),
    INVERT_DATA(INVERT_DATA),
    SAMPLE_SELECT(SAMPLE_SELECT)
) inst_axis_1553_decoder ( .aclk(clk), .arstn(rstn), .m_axis_tdata(m_axis_tdata),
```

Decode incoming differential 1553 data stream to AXIS data format.

## inst\_rx\_fifo

```
fifo #(
    FIFO_DEPTH(FIFO_DEPTH),
    BYTE_WIDTH(BUS_WIDTH),
    COUNT_WIDTH(8),
    FWFT(1),
    RD_SYNC_DEPTH(0),
    WR_SYNC_DEPTH(0),
    DC_SYNC_DEPTH(0),
    COUNT_DELAY(0),
    COUNT_ENA(0),
    DATA_ZERO(0),
    ACK_ENA(0),
    RAM_TYPE("block")
) inst_rx_fifo ( .rd_clk(clk), .rd_rstn(rstn & r_rstn_rx_delay[0]), .rd_en(s
```

Buffer up to 16 items output from the axis\_1553\_encoder.

**inst\_tx\_fifo**

```
fifo #(
    FIFO_DEPTH(FIFO_DEPTH),
    BYTE_WIDTH(BUS_WIDTH),
```

```

COUNT_WIDTH(8),
FWFT(1),
RD_SYNC_DEPTH(0),
WR_SYNC_DEPTH(0),
DC_SYNC_DEPTH(0),
COUNT_DELAY(0),
COUNT_ENA(0),
DATA_ZERO(0),
ACK_ENA(0),
RAM_TYPE("block")
) inst_tx_fifo ( .rd_clk(clk), .rd_rstn(rstn & r_rstn_tx_delay[0]), .rd_en(s

```

Buffer up to 16 items to input to the axis\_1553\_decoder.