axi_lite_gpio.v

AUTHORS

JAY CONVERTINO

DATES

2024/07/25

INFORMATION

Brief

AXI Lite GPIO is a core for creating a generic programmable input/output

License MIT

axi_lite_gpio

```
module axi_lite_gpio #(
parameter
ADDRESS_WIDTH
 =
32,
parameter
GPIO_WIDTH
 =
32,
parameter
IRQ_ENABLE
```

```
  =
 0
) ( input aclk, input arstn, input s_axi_aclk, input s_axi_aresetn, input s_
```

AXI Lite based gpio device.

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus
GPIO_WIDTH parameter	Width of the GPIO for inputs and outputs
IRQ_ENABLE parameter	Enable interrupt

Ports

aclk	Clock for all devices in the core
arstn	Negative reset
s_axi_awvalid	Axi Lite aw valid
s_axi_awaddr	Axi Lite aw addr
s_axi_awprot	Axi Lite aw prot
s_axi_awready	Axi Lite aw ready
s_axi_wvalid	Axi Lite w valid
s_axi_wdata	Axi Lite w data
s_axi_wstrb	Axi Lite w strb
s_axi_wready	Axi Lite w ready
s_axi_bvalid	Axi Lite b valid
s_axi_bresp	Axi Lite b resp
s_axi_bready	Axi Lite b ready
s_axi_arvalid	Axi Lite ar valid
s_axi_araddr	Axi Lite ar addr
s_axi_arprot	Axi Lite ar prot
s_axi_arready	Axi Lite ar ready
s_axi_rvalid	Axi Lite r valid
s_axi_rdata	Axi Lite r data
s_axi_rresp	Axi Lite r resp
s_axi_rready	Axi Lite r ready
irq	Interrupt when data is received
gpio_io_i	Input for GPIO
gpio_io_o	Output for GPIO
gpio_io_t	Tristate for GPIO

up_rreq

```
wire up_rreq
```

uP read bus request

up_rack

```
wire up_rack
```

uP read bus acknowledge

up_raddr

```
wire [ADDRESS_WIDTH-3:0] up_raddr
```

uP read bus address

up_rdata

```
wire [31:0] up_rdata
```

uP read bus request

up_wreq

```
wire up_wreq
```

uP write bus request

up_wack

```
wire up_wack
```

uP write bus acknowledge

up_waddr

```
wire [ADDRESS_WIDTH-3:0] up_waddr
```

uP write bus address

up_wdata

```
wire [31:0] up_wdata
```

uP write bus data

INSTANTIANTED MODULES

inst_up_axi

```
up_axi #(
                                                                                .
AXI_ADDRESS_WIDTH(ADDRESS_WIDTH)
) inst_up_axi ( .up_rstn (arstn), .up_clk (aclk), .up_axi_awvalid(s_axi_awv
```

Module instance of up_axi for the AXI Lite bus to the uP bus.

inst_up_gpio

```
up_gpio #(
                                                                                .
ADDRESS_WIDTH(32),
                                                                                .
BUS_WIDTH(2),
                                                                                .
GPIO_WIDTH(GPIO_WIDTH),
                                                                                .
IRQ_ENABLE(IRQ_ENABLE)
) inst_up_gpio ( .clk(aclk), .rstn(arstn), .up_rreq(up_rreq), .up_rack(up_ra
```

Module instance of up_gpio.