

axi_lite_uart.v

AUTHORS

JAY CONVERTINO

DATES

2024/02/29

INFORMATION

Brief

AXI Lite UART is a core for interfacing with UART devices.

License MIT

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

axi_lite_uart

```
module axi_lite_uart #(
    parameter
    ADDRESS_WIDTH
    =
    32,
    parameter
    CLOCK_SPEED
    =
    100000000,
    parameter
    BAUD_RATE
```

```

    =
    115200,
    parameter
    PARITY_ENA
    =
    0,
    parameter
    PARITY_TYPE
    =
    0,
    parameter
    STOP_BITS
    =
    1,
    parameter
    DATA_BITS
    =
    8,
    parameter
    RX_DELAY
    =
    0,
    parameter
    RX_BAUD_DELAY
    =
    0,
    parameter
    TX_DELAY
    =
    0,
    parameter
    TX_BAUD_DELAY
    =
    0
) ( input aclk, input arstn, input s_axi_aclk, input s_axi_aresetn, input s_

```

AXI Lite based uart device.

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus
CLOCK_SPEED parameter	This is the aclk frequency in Hz
BAUD_RATE parameter	Serial Baud, this can be any value including non-standard.
PARITY_ENA parameter	Enable Parity for the data in and out.
PARITY_TYPE parameter	Set the parity type, 0 = even, 1 = odd, 2 = mark, 3 = space.
STOP_BITS parameter	Number of stop bits, 0 to crazy non-standard amounts.
DATA_BITS parameter	Number of data bits, 1 to crazy non-standard amounts.
RX_DELAY parameter	Delay in rx data input.
RX_BAUD_DELAY parameter	Delay in rx baud enable. This will delay when we sample a bit (default is midpoint when rx delay is 0).
TX_DELAY	Delay in tx data output. Delays the time to output of the data.

parameter

TX_BAUD_DELAY Delay in tx baud enable. This will delay the time the bit output starts.

parameter

Ports

aclk	Clock for all devices in the core
arstn	Negative reset
s_axi_awvalid	Axi Lite aw valid
s_axi_awaddr	Axi Lite aw addr
s_axi_awprot	Axi Lite aw prot
s_axi_awready	Axi Lite aw ready
s_axi_wvalid	Axi Lite w valid
s_axi_wdata	Axi Lite w data
s_axi_wstrb	Axi Lite w strb
s_axi_wready	Axi Lite w ready
s_axi_bvalid	Axi Lite b valid
s_axi_bresp	Axi Lite b resp
s_axi_bready	Axi Lite b ready
s_axi_arvalid	Axi Lite ar valid
s_axi_araddr	Axi Lite ar addr
s_axi_arprot	Axi Lite ar prot
s_axi_arready	Axi Lite ar ready
s_axi_rvalid	Axi Lite r valid
s_axi_rdata	Axi Lite r data
s_axi_rresp	Axi Lite r resp
s_axi_rready	Axi Lite r ready
irq	Interrupt when data is received
tx	transmit for UART (output to RX)
rx	receive for UART (input from TX)
rts	request to send is a loop with CTS
cts	clear to send is a loop with RTS

up_rreq

```
wire up_rreq
```

uP read bus request

up_rack

```
wire up_rack
```

uP read bus acknowledge

up_raddr

```
wire [ADDRESS_WIDTH-3:0] up_raddr
```

uP read bus address

up_rdata

```
wire [31:0] up_rdata
```

uP read bus request

up_wreq

```
wire up_wreq
```

uP write bus request

up_wack

```
wire up_wack
```

uP write bus acknowledge

up_waddr

```
wire [ADDRESS_WIDTH-3:0] up_waddr
```

uP write bus address

up_wdata

```
wire [31:0] up_wdata
```

uP write bus data

INSTANTIATED MODULES

inst_up_axi

```
up_axi #(
    AXI_ADDRESS_WIDTH(ADDRESS_WIDTH)
) inst_up_axi ( .up_rstn (arstn), .up_clk (aclk), .up_axi_awvalid(s_axi_aw
```

Module instance of up_axi for the AXI Lite bus to the uP bus.

inst_up_uart

```
up_uart #(
    ADDRESS_WIDTH(ADDRESS_WIDTH),
    CLOCK_SPEED(CLOCK_SPEED),
    BAUD_RATE(BAUD_RATE),
    PARITY_ENA(PARITY_ENA),
    PARITY_TYPE(PARITY_TYPE),
    STOP_BITS(STOP_BITS),
    DATA_BITS(DATA_BITS),
    RX_DELAY(RX_DELAY),
    RX_BAUD_DELAY(RX_BAUD_DELAY),
    TX_DELAY(TX_DELAY),
    TX_BAUD_DELAY(TX_BAUD_DELAY)
) inst_up_uart ( .clk(aclk), .rstn(arstn), .up_rreq(up_rreq), .up_rack(up_rack)
```

Module instance of up_uart creating a Logic wrapper for uart axis bus cores to interface with uP bus.