

tb_cocotb_wishbone_standard.v

AUTHORS

JAY CONVERTINO

DATES

2025/04/01

INFORMATION

Brief

Test bench wrapper for cocotb

License MIT

Copyright 2025 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.BUS_WIDTH

tb_cocotb

```
module tb_cocotb #(
  parameter
    ADDRESS_WIDTH
    =
    32,
  parameter
    BUS_WIDTH
    =
    4,
  parameter
    CLOCK_SPEED
    =
    100000000,
  parameter
```

```

BAUD_RATE
=
115200,
parameter
PARITY_ENA
=
0,
parameter
PARITY_TYPE
=
0,
parameter
STOP_BITS
=
1,
parameter
DATA_BITS
=
8,
parameter
RX_DELAY
=
0,
parameter
RX_BAUD_DELAY
=
0,
parameter
TX_DELAY
=
0,
parameter
TX_BAUD_DELAY
=
0
) ( input clk, input rst, input s_wb_cyc, input s_wb_stb, input s_wb_we, inp

```

Wishbone Stanard based UART communications device.

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus
BUS_WIDTH parameter	Number of bytes for the data bus.
CLOCK_SPEED parameter	This is the aclk frequency in Hz
BAUD_RATE parameter	Serial Baud, this can be any value including non-standard.
PARITY_ENA parameter	Enable Parity for the data in and out.
PARITY_TYPE parameter	Set the parity type, 0 = even, 1 = odd, 2 = mark, 3 = space.
STOP_BITS parameter	Number of stop bits, 0 to crazy non-standard amounts.
DATA_BITS parameter	Number of data bits, 1 to crazy non-standard amounts.
RX_DELAY parameter	Delay in rx data input.
RX_BAUD_DELAY parameter	Delay in rx baud enable. This will delay when we sample a bit (default is midpoint when rx delay is 0).

TX_DELAY <small>parameter</small>	Delay in tx data output. Delays the time to output of the data.
TX_BAUD_DELAY <small>parameter</small>	Delay in tx baud enable. This will delay the time the bit output starts.

Ports

clk	Clock for all devices in the core
rst	Positive reset
s_wb_cyc	Bus Cycle in process
s_wb_stb	Valid data transfer cycle
s_wb_we	Active High write, low read
s_wb_addr	Bus address
s_wb_data_i	Input data
s_wb_sel	Device Select
s_wb_ack	Bus transaction terminated
s_wb_data_o	Output data
s_wb_err	Active high when a bus error is present
irq	Interrupt when data is received
tx	transmit for UART (output to RX)
rx	receive for UART (input from TX)
rts	request to send is a loop with CTS
cts	clear to send is a loop with RTS

INSTANTIATED MODULES

dut

```
wishbone_standard_uart #(
    ADDRESS_WIDTH(ADDRESS_WIDTH),
    BUS_WIDTH(BUS_WIDTH),
    CLOCK_SPEED(CLOCK_SPEED),
    BAUD_RATE(BAUD_RATE),
    PARITY_ENA(PARITY_ENA),
    PARITY_TYPE(PARITY_TYPE),
    STOP_BITS(STOP_BITS),
    DATA_BITS(DATA_BITS),
    RX_DELAY(RX_DELAY),
    RX_BAUD_DELAY(RX_BAUD_DELAY),
    TX_DELAY(TX_DELAY),
    TX_BAUD_DELAY(TX_BAUD_DELAY)
) dut ( .clk(clk), .rst(rst), .s_wb_cyc(s_wb_cyc), .s_wb_stb(s_wb_stb), .s_v
```

Device under test, wishbone_standard_uart