tb_cocotb_up.v

AUTHORS

JAY CONVERTINO

DATES

2025/04/01

INFORMATION

Brief

Test bench wrapper for cocotb

License MIT

tb_cocotb

```
module tb_cocotb #(
parameter
ADDRESS_WIDTH
 =
32,
parameter
BUS_WIDTH
 =
4,
parameter
CLOCK_SPEED
 =
100000000,
parameter
```

```
BAUD_RATE
 =
115200,
parameter
PARITY_ENA
 =
0,
parameter
PARITY_TYPE
 =
0,
parameter
STOP_BITS
 =
1,
parameter
DATA_BITS
 =
8,
parameter
RX_DELAY
 =
0,
parameter
RX_BAUD_DELAY
 =
0,
parameter
TX_DELAY
 =
0,
parameter
TX_BAUD_DELAY
 =
0
) ( input clk, input rstn, input up_rreq, output up_rack, input [ADDRESS_WI
```

uP UART testbench

Parameters

ADDRESS_WIDTH parameter	Width of the axi address bus
BUS_WIDTH parameter	Number of bytes for the data bus.
CLOCK_SPEED parameter	This is the aclk frequency in Hz
BAUD_RATE parameter	Serial Baud, this can be any value including non-standard.
PARITY_ENA parameter	Enable Parity for the data in and out.
PARITY_TYPE parameter	Set the parity type, 0 = even, 1 = odd, 2 = mark, 3 = space.
STOP_BITS parameter	Number of stop bits, 0 to crazy non-standard amounts.
DATA_BITS parameter	Number of data bits, 1 to crazy non-standard amounts.
RX_DELAY parameter	Delay in rx data input.
RX_BAUD_DELAY parameter	Delay in rx baud enable. This will delay when we sample a bit (default is midpoint when rx delay is 0).

TX_DELAY parameter	Delay in tx data output. Delays the time to output of the data.
TX_BAUD_DELAY parameter	Delay in tx baud enable. This will delay the time the bit output starts.

Ports

clk	Clock for all devices in the core
rstn	Negative reset
up_rreq	uP bus read request
up_rack	uP bus read ack
up_raddr	uP bus read address
up_rdata	uP bus read data
up_wreq	uP bus write request
up_wack	uP bus write ack
up_waddr	uP bus write address
up_wdata	uP bus write data
irq	Interrupt when data is received
tx	transmit for UART (output to RX)
rx	receive for UART (input from TX)
rts	request to send is a loop with CTS
cts	clear to send is a loop with RTS

INSTANTIATED MODULES

dut

```
up_uart #(
                                                                    .
ADDRESS_WIDTH(ADDRESS_WIDTH),
                                                                    .
BUS_WIDTH(BUS_WIDTH),
                                                                    .
CLOCK_SPEED(CLOCK_SPEED),
                                                                    .
BAUD_RATE(BAUD_RATE),
                                                                    .
PARITY_ENA(PARITY_ENA),
                                                                    .
PARITY_TYPE(PARITY_TYPE),
                                                                    .
STOP_BITS(STOP_BITS),
                                                                    .
DATA_BITS(DATA_BITS),
                                                                    .
RX_DELAY(RX_DELAY),
                                                                    .
RX_BAUD_DELAY(RX_BAUD_DELAY),
                                                                    .
TX_DELAY(TX_DELAY),
                                                                    .
TX_BAUD_DELAY(TX_BAUD_DELAY)
) dut ( .clk(clk), .rstn(rstn), .up_rreq(up_rreq), .up_rack(up_rack), .up_ra
```

Device under test, up_uart