

system_pl_wrapper.v

AUTHORS

JAY CONVERTINO

DATES

2023/11/02

INFORMATION

Brief

System wrapper for pl only for hanpilot board.

License MIT

Copyright 2023 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

system_pl_wrapper

```
module system_pl_wrapper #(
    parameter
    FPGA_TECHNOLOGY
    =
    0,
    parameter
    FPGA_FAMILY
    =
    0,
    parameter
    SPEED_GRADE
```

```

    =
    0,
    parameter
    DEV_PACKAGE
    =
    0,
    parameter
    ADC_INIT_DELAY
    =
    23,
    parameter
    DAC_INIT_DELAY
    =
    0,
    parameter
    DELAY_REFCLK_FREQUENCY
    =
    200
  ) ( input axi_aclk, input axi_aresetn, input s_axi_awvalid, input [31:0] s_

```

System wrapper for pl only for hanpilot board.

Parameters

FPGA_TECHNOLOGY parameter	Type of FPGA, such as Ultrascale, Arria 10. 103 is for Arria 10.
FPGA_FAMILY parameter	Sub type of fpga, such as GX, SX, etc. 1 is for SX
SPEED_GRADE parameter	Number that corresponds to the ships recommeneded speed. 2 is for 2.
DEV_PACKAGE parameter	Specify a number that is equal to the manufactures package. 3 is for FBGA.
ADC_INIT_DELAY parameter	Initial Delay for the ADC
DAC_INIT_DELAY parameter	Initial Delay for the DAC
DELAY_REFCLK_FREQUENCY parameter	Reference clock frequency used for ad_data_in instances

Ports

axi_aclk	AXI Lite control bus
axi_aresetn	AXI Lite control bus
s_axi_awvalid	AXI Lite control bus
s_axi_awaddr	AXI Lite control bus
s_axi_awready	AXI Lite control bus
s_axi_awprot	AXI Lite control bus
s_axi_wvalid	AXI Lite control bus
s_axi_wdata	AXI Lite control bus
s_axi_wstrb	AXI Lite control bus
s_axi_wready	AXI Lite control bus
s_axi_bvalid	AXI Lite control bus
s_axi_bresp	AXI Lite control bus
s_axi_bready	AXI Lite control bus

s_axi_arvalid	AXI Lite control bus
s_axi_araddr	AXI Lite control bus
s_axi_arready	AXI Lite control bus
s_axi_arprot	AXI Lite control bus
s_axi_rvalid	AXI Lite control bus
s_axi_rready	AXI Lite control bus
s_axi_rresp	AXI Lite control bus
s_axi_rdata	AXI Lite control bus
adc_dma_irq	fmcomms2-3 ADC irq
dac_dma_irq	fmcomms2-3 DAC irq
delay_clk	fmcomms2-3 delay clock
rx_clk_in_p	fmcomms2-3 receive clock in
rx_clk_in_n	fmcomms2-3 receive clock in
rx_frame_in_p	fmcomms2-3 receive frame
rx_frame_in_n	fmcomms2-3 receive frame
rx_data_in_p	fmcomms2-3 receive lvds data
rx_data_in_n	fmcomms2-3 receive lvds data
tx_clk_out_p	fmcomms2-3 transmit clock
tx_clk_out_n	fmcomms2-3 transmit clock
tx_frame_out_p	fmcomms2-3 transmit frame
tx_frame_out_n	fmcomms2-3 transmit frame
tx_data_out_p	fmcomms2-3 transmit lvds data
tx_data_out_n	fmcomms2-3 transmit lvds data
enable	fmcomms2-3 enable
txnrx	fmcomms2-3 txnrx select
up_enable	fmcomms2-3 enable input
up_txnrx	fmcomms2-3 txnrx select input
tdd_sync_t	fmcomms2-3 TDD sync i/o
tdd_sync_i	fmcomms2-3 TDD sync i/o
tdd_sync_o	fmcomms2-3 TDD sync i/o
adc_m_dest_axi_awaddr	fmcomms2-3 ADC DMA
adc_m_dest_axi_awlen	fmcomms2-3 ADC DMA
adc_m_dest_axi_awsz	fmcomms2-3 ADC DMA
adc_m_dest_axi_awburst	fmcomms2-3 ADC DMA
adc_m_dest_axi_awprot	fmcomms2-3 ADC DMA
adc_m_dest_axi_awcache	fmcomms2-3 ADC DMA
adc_m_dest_axi_awvalid	fmcomms2-3 ADC DMA
adc_m_dest_axi_awready	fmcomms2-3 ADC DMA
adc_m_dest_axi_wdata	fmcomms2-3 ADC DMA
adc_m_dest_axi_wstrb	fmcomms2-3 ADC DMA
adc_m_dest_axi_wready	fmcomms2-3 ADC DMA
adc_m_dest_axi_wvalid	fmcomms2-3 ADC DMA

adc_m_dest_axi_wlast	fmcomms2-3 ADC DMA
adc_m_dest_axi_bvalid	fmcomms2-3 ADC DMA
adc_m_dest_axi_bresp	fmcomms2-3 ADC DMA
adc_m_dest_axi_bready	fmcomms2-3 ADC DMA
dac_m_src_axi_arready	fmcomms2-3 DAC DMA
dac_m_src_axi_arvalid	fmcomms2-3 DAC DMA
dac_m_src_axi_araddr	fmcomms2-3 DAC DMA
dac_m_src_axi_arlen	fmcomms2-3 DAC DMA
dac_m_src_axi_arsize	fmcomms2-3 DAC DMA
dac_m_src_axi_arburst	fmcomms2-3 DAC DMA
dac_m_src_axi_arprot	fmcomms2-3 DAC DMA
dac_m_src_axi_arcache	fmcomms2-3 DAC DMA
dac_m_src_axi_rdata	fmcomms2-3 DAC DMA
dac_m_src_axi_rready	fmcomms2-3 DAC DMA
dac_m_src_axi_rvalid	fmcomms2-3 DAC DMA
dac_m_src_axi_rresp	fmcomms2-3 DAC DMA
dac_m_src_axi_rlast	fmcomms2-3 DAC DMA

INSTANTIATED MODULES

inst_ad9361_pl_wrapper

```

ad9361_pl_wrapper #(
    FPGA_TECHNOLOGY(FPGA_TECHNOLOGY),
    FPGA_FAMILY(FPGA_FAMILY),
    SPEED_GRADE(SPEED_GRADE),
    DEV_PACKAGE(DEV_PACKAGE),
    ADC_INIT_DELAY(ADC_INIT_DELAY),
    DAC_INIT_DELAY(DAC_INIT_DELAY),
    DELAY_REFCLK_FREQUENCY(DELAY_REFCLK_FREQUENCY),
    AXI_DMAC_ADC_ADDR(32'h00010000),
    AXI_DMAC_DAC_ADDR(32'h00014000),
    AXI_AD9361_ADDR(32'h00000000)
) inst_ad9361_pl_wrapper ( .axi_aclk(axi_aclk), .axi_aresetn(axi_aresetn),

```

Module instance of ad9361_pl_wrapper for the fmcomms2-3 device.