

# axis\_1553\_string\_decoder.v

---

## AUTHORS

---

JAY CONVERTINO

---

## DATES

---

2021/06/21

---

## INFORMATION

---

### Brief

---

Carriage return terminated string converted to 1553 data.

### License MIT

---

Copyright 2021 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## axis\_1553\_string\_decoder

---

```
module axis_1553_string_decoder #(
    parameter
    byte_swap
    =
    0
) ( input aclck, input arstn, input [167:0] s_axis_tdata, input s_axis_tval;
```

Carriage return terminated string converted to 1553 data.

## Parameters

**byte\_swap**      swap input byte order.  
*parameter*

## Ports

<b>aclk</b>	Master Clock
<b>arstn</b>	Negative Reset
<b>s_axis_tdata</b>	Input raw data
<b>s_axis_tvalid</b>	Input raw data is valid
<b>s_axis_tuser</b>	Input raw user field
<b>s_axis_tready</b>	Input ready for characters
<b>m_axis_tdata</b>	Output string.
<b>m_axis_tvalid</b>	Output string is valid
<b>m_axis_tlast</b>	Indicates output string termination
<b>m_axis_tkeep</b>	What bytes are valid characters in the string.
<b>m_axis_tready</b>	Is the next device ready for output?