

UP_WISHBONE_PIPELINE



November 21, 2024

Jay Convertino

Contents

1 Usage	2
1.1 Introduction	2
1.2 Dependencies	2
1.2.1 fusesoc_info Depenecies	2
1.3 In a Project	2
2 Architecture	5
3 Building	6
3.1 fusesoc	6
3.2 Source Files	6
3.2.1 fusesoc_info File List	6
3.3 Targets	6
3.3.1 fusesoc_info Targets	6
3.4 Directory Guide	6
4 Simulation	8
4.1 iverilog	8
4.2 cocotb	8
5 Module Documentation	9
5.1 up_wishbone_pipeline	10

1 Usage

1.1 Introduction

This core converts the Wishbone Pipeline bus to the uP bus. This allows any core with a uP bus to be interfaced with a Wishbone Pipeline bus. Combination of combinatorial logic and synchronous logic.

1.2 Dependencies

The following are the dependencies of the cores.

- fusesoc 2.X
- iverilog (simulation)
- cocotb (simulation)

1.2.1 fusesoc_info Dependencies

- dep
 - AFRL:utility:helper:1.0.0
- dep_tb
 - AFRL:utility:sim_helper

1.3 In a Project

This core is made to interface Wishbone Pipeline bus to uP based device cores. This is part of a family of converters based on Analog Devices uP specification. Using this allows usage of Analog Devices AXI Lite core, AFRL APB3, AFRL Wishbone Pipeline, and AFRL Wishbone Pipeline converters. Meaning any uP core can be easily customized to any bus quickly. These are made for relatively slow speed bus device interfaces. An example of a Verilog uP interface provided below.

```
//output signals assigned to registers.  
assign up_rack  = r_up_rack & up_rreq;  
assign up_wack  = r_up_wack & up_wreq;  
assign up_rdata = r_up_rdata;  
assign irq      = r_irq;  
  
assign s_rx_ren = ((up_raddr[3:0] == RX_FIFO_REG) &&  
    ↪ up_rreq ? r_up_rack & r_rx_ren : 0);
```

```

//up registers decoder
always @(posedge clk)
begin
    if(rstn == 1'b0)
    begin
        r_up_rack    <= 1'b0;
        r_up_wack    <= 1'b0;
        r_up_rdata    <= 0;

        r_rx_ren      <= 1'b0;

        r_overflow    <= 1'b0;

        r_control_reg <= 0;
    end else begin
        r_up_rack    <= 1'b0;
        r_up_wack    <= 1'b0;
        r_tx_wen      <= 1'b0;
        r_rx_ren      <= 1'b0;
        r_up_rdata    <= r_up_rdata;
        //clear reset bits
        r_control_reg[RESET_RX_BIT] <= 1'b0;
        r_control_reg[RESET_TX_BIT] <= 1'b0;

        if(rx_full == 1'b1)
        begin
            r_overflow <= 1'b1;
        end

        //read request
        if(up_rreq == 1'b1)
        begin
            r_up_rack <= 1'b1;

            case(up_raddr[3:0])
                RX_FIFO_REG: begin
                    r_up_rdata <= rx_rdata & {{(BUS_WIDTH*8-
                        ↪ DATA_BITS){1'b0}}, {DATA_BITS{1'b1}}}};
                    r_rx_ren <= 1'b1;
                end
                STATUS_REG: begin
                    r_up_rdata <= {{(BUS_WIDTH*8-8){1'b0}},
                        ↪ s_parity_err, s_frame_err, r_overflow,
                        ↪ r_irq_en, tx_full, tx_empty, rx_full,
                        ↪ rx_valid};
                    r_overflow <= 1'b0;
                end
            endcase
        end
    end
end

```

```

        end
        default:begin
            r_up_rdata <= 0;
        end
    endcase
end

//write request
if(up_wreq == 1'b1)
begin
    r_up_wack <= 1'b1;

    //only allow write once ack (Analog Devices does
    ↪ the same)
    if(r_up_wack == 1'b1) begin
        case(up_waddr[3:0])
            TX_FIFO_REG: begin
                r_tx_wdata <= up_wdata;
                r_tx_wen <= 1'b1;
            end
            CONTROL_REG: begin
                r_control_reg <= up_wdata;
            end
            default:begin
            end
        endcase
    end
end
end
end

//up control register processing and fifo reset
always @(posedge clk)
begin
    if(rstn == 1'b0)
    begin
        r_rstn_rx_delay <= ~0;
        r_rstn_tx_delay <= ~0;
        r_irq_en <= 1'b0;
    end else begin
        r_rstn_rx_delay <= {1'b1, r_rstn_rx_delay[
            ↪ FIFO_DEPTH-1:1]};
        r_rstn_tx_delay <= {1'b1, r_rstn_tx_delay[
            ↪ FIFO_DEPTH-1:1]};

        if(r_control_reg[RESET_RX_BIT])

```

```

begin
    r_rstn_rx_delay <= {FIFO_DEPTH{1'b0}};
end

    if(r_control_reg[RESET_TX_BIT])
begin
    r_rstn_tx_delay <= {FIFO_DEPTH{1'b0}};
end

    if(r_control_reg[ENABLE_INTR_BIT] != r_irq_en)
        r_irq_en <= r_control_reg[ENABLE_INTR_BIT];
    end
end
end

```

2 Architecture

The only module is the `up_wishbone_pipeline` module. It is listed below.

- **up_wishbone_pipeline** Convert Wishbone Pipeline to the Analog Devices uP BUS. (see core for documentation).

This core has two generate blocks, and two always blocks. They are listed below.

generate:

1. Part Select Write generates uP signals that have the non-selected elements blanked out with zeros.
2. Part Select Read generates Wishbone classic signals that have non-selected elements blanked out with zeros.

always:

- Register Requests
 1. When `cyc` is high and `stb` isn't register signal to keep previous state.
 2. When both `cyc` and `stb` are high register the correct request.
- Reset Hold, holds reset for 8 more clock cycles to comply with Wishbone Standard.

Please see 5 for more information.

3 Building

The Wishbone Pipeline core is written in Verilog 2001. They should synthesize in any modern FPGA software. The core comes as a fusesoc packaged core and can be included in any other core. Be sure to make sure you have met the dependencies listed in the previous section.

3.1 fusesoc

Fusesoc is a system for building FPGA software without relying on the internal project management of the tool. Avoiding vendor lock in to Vivado or Quartus. These cores, when included in a project, can be easily integrated and targets created based upon the end developer needs. The core by itself is not a part of a system and should be integrated into a fusesoc based system. Simulations are setup to use fusesoc and are a part of its targets.

3.2 Source Files

3.2.1 fusesoc_info File List

- src
 - src/up_wishbone_pipeline.v
- tb
 - tb/tb_wishbone_slave.v

3.3 Targets

3.3.1 fusesoc_info Targets

- default
 - Info: Default for IP integration.
- sim
 - Info: Base simulation using icarus as default.

3.4 Directory Guide

Below highlights important folders from the root of the directory.

1. **docs** Contains all documentation related to this project.

- **manual** Contains user manual and github page that are generated from the latex sources.
 - **specs** Contains specifications for the bus.
2. **src** Contains source files for the core
 3. **tb** Contains test bench files for iverilog and cocotb
 - **cocotb** testbench files

4 Simulation

There are a few different simulations that can be run for this core.

4.1 iverilog

iverilog is used for simple test benches for quick verification, visually, of the core.

4.2 cocotb

Future simulations will use cocotb. This feature is not yet implemented.

5 Module Documentation

There is a single async module for this core.

- **up_wishbone_pipeline** Wishbone Pipeline to uP converter

The next sections document the module in great detail.

up_wishbone_pipeline.v

AUTHORS

JAY CONVERTINO

DATES

2024/03/01

INFORMATION

Brief

Wishbone Pipeline Slave to uP interface

License MIT

Copyright 2024 Jay Convertino

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

up_wishbone_pipeline

```
module up_wishbone_pipeline #(
    parameter
    ADDRESS_WIDTH
    =
    16,
    parameter
    BUS_WIDTH
    =
    4
) ( input clk, input rst, input s_wb_cyc, input s_wb_stb, input s_wb_we, in
```

Wishbone Classic slave to uP up_wishbone_classic

Parameters

ADDRESS_WIDTH Width of the Wishbone address port in bits.
parameter

BUS_WIDTH Width of the Wishbone bus data port in bytes.
parameter

Ports

clk	Clock
rst	Positive reset
s_wb_cyc	Bus Cycle in process
s_wb_stb	Valid data transfer cycle
s_wb_we	Active High write, low read
s_wb_addr	Bus address
s_wb_data_i	Input data
s_wb_sel	Device Select
s_wb_bte	Burst Type Extension
s_wb_cti	Cycle Type
s_wb_ack	Bus transaction terminated
s_wb_data_o	Output data
s_wb_err	Active high when a bus error is present
up_rreq	uP bus read request
up_rack	uP bus read ack
up_raddr	uP bus read address
up_rdata	uP bus read data
up_wreq	uP bus write request
up_wack	uP bus write ack
up_waddr	uP bus write address
up_wdata	uP bus write data

VARIABLES

valid

```
assign valid = s_wb_cyc & s_wb_stb & ~r_rst[0]
```

Indicate valid request from wishbone.

s_wb_stall

```
assign s_wb_stall = ~up_ack & s_wb_cyc & ~r_rst[0]
```

if we have not ack'd, cyc is active stall the bus

up_rreq

```
assign up_rreq = (
    s_wb_cyc                                     r_up_rreq ? r_up_rreq &
    :
    valid & ~s_wb_we & ~r_rst[0]
)
```

Convert wishbone read requests to up read requests

up_wreq

```
assign up_wreq = (
    s_wb_cyc                                     r_up_wreq ? r_up_wreq &
    :
    valid & s_wb_we & ~r_rst[0]
)
```

Convert wishbone write requests to up write requests

up_ack

```
assign up_ack = (
    up_rack |
    up_wack
)
```

ack is ack for both, or them so either may pass

s_wb_ack

```
assign s_wb_ack = up_ack & ~r_rst[0]
```

combined uP ack is wishbone ack.

up_raddr

```
assign up_raddr = (
    s_wb_addr                                     ~s_wb_we & ~r_rst[0] ?
    :
    0
)
```

assign wishbone address to read port if selected

up_waddr

```
assign up_waddr = (
    s_wb_addr
    :
    0
)
```

assign wishbone address to write port if selected