About this PDF

Built only from: **NOC:Computer Networks and Internet Protocol (NPTEL course book, weeks 1, 2)** — https://nptel.ac.in/courses/106105183

Licence: CC BY-SA 4.0. Accessed 2026-09-26.

Covers 15 of 15 syllabus sub-topics of this unit.

Partly covered in the source:

- Introduction to Sockets

Data Communication

Definition

Data communication is the transmission of binary or digital data over a physical medium between devices, enabling them to exchange information.

Explanation

The physical layer is responsible for sending binary data across the chosen medium, which may be fiber, wireless, or wired links. Above this, the data link layer groups the bits into frames and performs error checking to ensure reliable transfer of these units. The network layer then forwards packets, handling routing but without guaranteeing reliability. Finally, the transport layer can provide either reliable or unreliable end-to-end delivery, depending on the service required. The communication process is device-independent; as long as devices adhere to the defined protocols, they can interoperate regardless of their underlying hardware or the specific transmission path used. Because modern networks support heterogeneous devices and services, maintaining continuous data communication is critical; any interruption can halt industrial processes and other essential operations.

Example

A multi-port bridge (layer-2 switch) forwards frames based on MAC addresses within the same LAN, while a router (layer-3 device) filters traffic using IP addresses to connect different networks and find appropriate paths for data packets.

Key points

- The physical layer carries binary data over various media.
- Data link layer frames the data and checks for errors.
- Network layer routes packets without guaranteeing reliability.
- Transport layer can provide reliable or unreliable delivery.
- Protocol compliance allows heterogeneous devices to communicate over any medium.

Networks

Definition

A network is a set of interconnected devices whose overall management becomes critical as the network expands, requiring monitoring of health, capacity forecasting, and problem determination.

Explanation

Network management relies on protocols such as SNMP, which uses a manager-client-agent model to gather regular status information from SNMP agents and allows administrators to modify operational values dynamically in response to network conditions. Routers segment a network by breaking broadcast domains, discarding broadcasts received on an interface instead of forwarding them, and also separate collision domains, thereby improving efficiency and reducing unnecessary traffic.

Example

A router receives a broadcast frame on one of its interfaces and discards it, preventing the broadcast from propagating to other network segments.

Key points

- SNMP provides monitoring and control functions through a manager-client-agent architecture.
- Routers partition networks into distinct broadcast and collision domains, enhancing performance.
- Effective network management is essential to maintain health, forecast capacity, and quickly address failures as the network grows.

Network Types

Definition

Network types refer to the hierarchical design of a network, typically organized into core, distribution, and access layers, each serving distinct roles in the overall architecture.

Explanation

The core layer provides very high-speed connectivity and forms the backbone of the network. The distribution layer implements policies and routing functions, acting as an intermediary between the core and the access layer. The access layer connects end devices and delivers network services to users. This layered approach helps manage bandwidth, control broadcast domains, and simplify network administration.

Example

A campus network where the backbone switches and routers constitute the core, the intermediate switches that enforce VLAN policies form the distribution layer, and the edge switches that connect computers and printers represent the access layer.

AcademicsGen — source: NPTEL — CC BY-SA 4.0

Key points

- The hierarchy consists of core, distribution, and access layers.
- Core devices are optimized for speed, while distribution devices handle policy enforcement.
- Access devices provide the “last mile” connectivity to end users.
- Breaking up broadcast domains with routers improves efficiency and reduces unnecessary traffic.

Protocol Layering

Definition

Protocol layering is the organization of networking functions into a stack of distinct layers, where each layer provides specific services and interfaces to the layer above it while hiding its internal details from that layer.

Explanation

Each layer adds its own header (or trailer) to the data received from the upper layer, turning the payload into a new packet that is passed down to the next lower layer. This process continues until the physical layer transmits the bits over the medium. At the receiving end, the layers strip off their respective headers in reverse order, delivering the original data to the application. The layering concept allows different technologies (wired, wireless, etc.) and protocols (e.g., Ethernet, IP, TCP, HTTP) to operate independently while cooperating through well-defined interfaces.

Example

When a web page is requested, the HTTP protocol operates at the application layer, TCP provides a reliable transport service at the transport layer, IP routes the packet at the network layer, Ethernet frames the packet at the data-link layer, and the physical layer carries the bits over the cable or wireless link.

Key points

- Layers are stacked from physical up to application, each with specific responsibilities.
- Upper layers use the services of lower layers without needing to know their internal mechanisms.
- Protocols such as HTTP, TCP, IP, and Ethernet exemplify the functions of the application, transport, network, and data-link layers respectively.
- The payload of one layer becomes the input (payload) for the next lower layer, enabling end-to-end communication.

TCP/IP Protocol suite

Definition

TCP/IP is a suite of public standards that specify how packets of information are exchanged between computers on one or more networks, forming the dominant standard for inter-networking.

Explanation

The suite organizes functionality into layers that map loosely onto the OSI model. The transport layer of TCP/IP incorporates functions of the OSI session and part of the presentation layers, while the application layer covers the remaining presentation and session responsibilities. At the lower end, the networking is performed over IP (IPv4 or IPv6), with transport protocols such as TCP, UDP, and ICMP providing connection-oriented, connectionless, or control services. Higher-level application protocols (e.g., HTTP, FTP, SMTP) rely on these underlying layers to carry their messages, and cross-layer protocols like DNS, SNMP, ARP, and DHCP operate between adjacent layers to support address resolution and network management.

Example

SMTP (Simple Mail Transfer Protocol) operates at the application layer, uses TCP as its transport protocol, and listens on the default port 25.

Key points

- TCP/IP defines a set of protocols that enable packet exchange across heterogeneous networks.
- Its transport layer subsumes OSI session and part of presentation functions, while the application layer includes the rest of those functions.
- Common transport protocols are TCP (connection-oriented) and UDP (connectionless).
- IP (IPv4/IPv6) provides a best-effort, connectionless network layer beneath the transport protocols.
- Application protocols such as SMTP depend on TCP and use well-known ports (e.g., port 25).

OSI Model

Definition

The OSI (Open Systems Interconnection) model is a conceptual framework that defines a seven-layer stack for networking protocols, ranging from the physical transmission of bits up to application-level services.

Explanation

Each layer of the OSI model has a specific function:

1. **Physical layer** – handles transmission of binary data over a medium.
2. **Data link layer** – transfers units of information, providing framing and error checking.

3. **Network layer** – delivers packets, performing routing; it does not guarantee reliability.
4. **Transport layer** – sits above the network layer and offers both reliable and unreliable end-to-end delivery services.
5. **Session layer** – establishes and maintains communication sessions between endpoints.
6. **Presentation layer** – formats data and performs encryption if required.
7. **Application layer** – supports network applications such as file transfer and terminal emulation.

Network devices may implement some or all of these layers; for example, a layer-2 switch operates up to the data link layer, while a layer-3 switch includes network-layer functionality.

Example

A data packet generated by an application is encapsulated successively: the application data becomes payload for the presentation layer, which becomes payload for the session layer, and so on, until the final binary payload is transmitted over the physical layer to the receiving end.

Key points

- The OSI model consists of seven distinct layers: physical, data link, network, transport, session, presentation, and application.
- Each layer provides specific services, such as framing at the data link layer and routing at the network layer.
- The transport layer can provide both reliable and unreliable end-to-end delivery.
- Devices may implement only a subset of layers (e.g., layer-2 or layer-3 switches).
- Encapsulation proceeds from the application layer down to the physical layer, with each layer's data becoming the payload for the next lower layer.

Introduction to Sockets

Partly covered in the source.

Definition

A socket is the interface that establishes a communication link between a source and a destination process, allowing them to exchange data over a network.

Explanation

The transport layer uses IP addresses to identify a host and combines the IP address with a port number to identify a specific process on that host. When a client initiates communication, it specifies the server's IP address and port; the system automatically assigns a client port if none is provided. This creates a path between the two endpoints, abstracting the underlying network details such as routers, and enables the processes to communicate as if they were directly connected.

Example

A Telnet client establishes a TCP connection to a Telnet server that is listening on a specific port. The client can then send commands to be executed on the remote host, providing remote login capabilities.

Key points

- Sockets provide the programming interface for process-to-process communication across a network.
- The combination of IP address and port number uniquely identifies a process on a host.
- The client's port is assigned automatically by the system when not explicitly specified.
- Communication via sockets abstracts the underlying network infrastructure, presenting a simple end-to-end path.
- Applications such as Telnet use sockets to create client-server connections for remote services.

Application Layer protocols: HTTP

Definition

HTTP (Hypertext Transfer Protocol) is the predominant application-layer protocol used for transferring web pages and related data between a client (such as a browser) and a server.

Explanation

When a client wants to retrieve a resource, it sends an HTTP request to an HTTP server; the server replies with an HTTP response message. This request/response exchange occurs over the underlying transport and network layers, but the details of those lower layers are hidden from the user, who only interacts with the web page content. In a typical client-server setup, the browser acts as the HTTP client and the web site provides an HTTP server (often called an HTTP daemon) that serves the requested pages.

Example

Accessing the URL "http://www.iitkgp.ac.in" causes the browser (HTTP client) to send an HTTP request to the corresponding HTTP server, which then returns the requested web page in an HTTP response.

Key points

- HTTP is the main protocol for web page retrieval and is widely allowed through routers and firewalls.
- Communication follows a request from the client and a response from the server.
- The client–server interaction is abstracted from the underlying transport and network layers, providing a simple interface for users.
- In a LAN context, the browser functions as the HTTP client while the web site provides an HTTP server (daemon).

FTP

Definition

FTP is a reliable, connection-oriented service that uses TCP to transfer files between systems that support FTP.

Explanation

FTP operates over TCP, providing reliability through connection-oriented communication. It uses a control channel (port 21) and a separate data channel for the actual file transfer. The service is implemented by an FTP server process (often called **ftpd**) and accessed by an FTP client.

Example

A typical FTP setup consists of an **ftpd** daemon running on a host, which listens for requests from an FTP client.

Key points

- FTP relies on TCP, making it a reliable, connection-oriented file transfer protocol.
- The standard control port for FTP is 21, and a second port is used for data transfer.
- FTP services are provided by an **ftpd** server process and accessed by FTP client applications.

Email protocols (SMTP

Definition

Simple Mail Transfer Protocol (SMTP) is an application-layer protocol used for transferring email messages from one host to another. It operates over TCP, typically on port 25.

Explanation

SMTP works by having mail transfer agents (MTAs) at both the sending and receiving ends. These MTAs communicate with each other to forward mail, and they may also act as relays that pass the message on to additional MTAs until it reaches the final destination. The protocol defines the exchange of a text-file envelope that contains the sender address, receiver address, and other header information, while the body of the message carries the actual content.

Example

A typical email consists of an envelope with fields such as sender, receiver, and subject (the header), followed by the message body. This structure is the format used by SMTP when transmitting the mail between servers.

Key points

- SMTP is the standard protocol for sending and receiving email between servers.
- It runs on TCP port 25 by default.

- MTAs can act as relays, forwarding mail through multiple servers to reach the destination.
- The email format includes a header (sender, receiver, subject) and a body containing the message content.

POP3

Definition

POP3 (Post Office Protocol version 3) is a mail-access protocol that allows a user to retrieve email messages from a mail server's mailbox. It provides a simple way for users to obtain a list of their emails, retrieve them, and optionally delete them from the server to conserve server resources.

Explanation

POP3 works by pulling messages from the mail server to the client. The protocol gives the user a front-end to manage their mail services, enabling actions such as listing, retrieving, and deleting messages. Because it is simple, it minimizes the resources required on the server side. In contrast, IMAP4 offers more features, but POP3's basic philosophy is to provide straightforward access and management of email without the additional capabilities of IMAP. POP3 is mentioned as one of the front-end protocols that complement SMTP, which handles the transport of email.

Key points

- POP3 pulls email messages from the server to the client.
- Users can list, retrieve, and choose to delete or keep messages on the server.
- The protocol is simple and aims to minimize server resource usage.
- It is one of the primary mail-access protocols alongside IMAP4.
- POP3 serves as a front-end protocol complementing SMTP for email delivery.

IMAP

Definition

IMAP (Internet Message Access Protocol) version 4 is a mail-access protocol that lets users manage their email directly on the server, offering more features than POP3.

Explanation

IMAP allows users to view email headers before deciding whether to download the full message, enabling selective retrieval. It also supports searching for specific strings within messages on the server, creating, deleting, and renaming mailboxes, and downloading only parts of an email, thereby giving users greater control and flexibility over their mailbox.

AcademicsGen — source: NPTEL — CC BY-SA 4.0

Example

A user can request only the header of an email, examine it, and then choose to download the entire message or leave it on the server; the same protocol also permits the user to search the server for a particular keyword in messages before any download occurs.

Key points

- IMAP 4 provides server-side mailbox management such as creating, deleting, and renaming mailboxes.
- Users can preview email headers and decide whether to download the full content.
- The protocol supports server-side searching for specific text strings within emails.
- Partial download of email content is possible, enhancing efficiency.

MIME)

Definition

Multipurpose Internet Mail Extension (MIME) provides a way to transmit non-ASCII data such as text, application files, images, audio, and video over SMTP by converting them to a 7-bit NVT ASCII payload that both the sending and receiving SMTP clients can handle.

Explanation

MIME inserts its own headers between the standard email header and the body header. These headers specify the MIME version, content type, content-transfer-encoding, content-ID, and content description, allowing the receiver to decode the original non-ASCII data. Various content-transfer-encoding schemes (e.g., 7-bit, 8-bit, binary, Base64, quoted-printable) are defined to represent different media types such as multipart messages, images, video, audio, and applications. Mail Transfer Agents (MTAs) and mail access protocols (POP3, IMAP4) deliver and retrieve these MIME-encoded messages, but some servers may block certain types (e.g., executables, video) or impose size limits.

Example

An email containing an image is encoded with a MIME header that declares a content type of “image” and uses a suitable transfer encoding (e.g., Base64). The image data is then converted to 7-bit ASCII so it can travel through the SMTP envelope and be decoded by the recipient’s MIME processor.

Key points

- MIME converts non-ASCII content to 7-bit ASCII for SMTP transmission.
- MIME headers (version, content type, transfer encoding, etc.) are placed between the email header and body.
- Supports multiple media types: text, application, image, audio, video.

- Uses various encoding schemes such as Base64 and quoted-printable to represent binary data.
- Mail servers may restrict certain MIME types or sizes, affecting delivery.

DNS

Definition

Domain Name System (DNS) is a service whose primary job is to translate a domain name into its corresponding IP address, enabling the network layer to route packets using numeric addresses.

Explanation

When a user requests a resource such as “www.iitkgp.ac.in”, the name itself has no meaning for the IP layer. The system therefore sends a query to a DNS resolver, which contacts a DNS server to obtain the IP address associated with that name. The client machine (e.g., a laptop) contains a DNS client that performs this request. The DNS server’s address is obtained from network configuration, DHCP, or manual setup. DNS operates as a cross-layer protocol, interacting between the application and lower layers to provide name-to-IP resolution.

Example

A user types “www.iitkgp.ac.in” in a browser; the DNS client sends a query to the configured DNS server, receives the IP address for that domain, and then uses the IP address to establish the subsequent connection.

Key points

- DNS converts human-readable domain names to IP addresses required for routing.
- The resolver on the client contacts a DNS server whose address is supplied via configuration or DHCP.
- DNS is considered a cross-layer protocol, bridging application-level name resolution with lower-layer networking functions.

SNMP

Definition

SNMP (Simple Network Management Protocol) is an application-layer protocol that facilitates the exchange of management information between network devices such as hosts, routers, and printers. It operates primarily over UDP and follows a manager-agent model where the manager queries or modifies data maintained by agents in a Management Information Base (MIB).

Explanation

The SNMP architecture consists of three main components: the SNMP manager (an application program that initiates queries or updates), the SNMP agent (software running on network equipment that maintains configuration and state information in MIBs), and the MIB itself, which defines the structure of the managed data. Communication follows a request-response pattern: the manager sends Get, Get-Next, or Set requests to the agent, which replies with the requested values or confirmation of changes. Agents can also generate unsolicited notifications called traps to inform the manager of significant events without a prior request.

Example

When a particular event occurs on a device, its SNMP agent sends a trap message directly to the SNMP manager to notify it of the event, without the manager having issued any prior query.

Key points

- SNMP uses a manager-agent model with agents maintaining device state in MIBs.
- Communication is carried out over UDP, typically using port 161 for requests and responses.
- Managers issue Get, Get-Next, and Set requests; agents respond accordingly.
- Traps are unsolicited notifications sent by agents to managers when specific events occur.
- Three versions (v1, v2c, v3) exist, with v3 providing enhanced security features.

Source and licence

This PDF is adapted from **NOC:Computer Networks and Internet Protocol (NPTEL course book, weeks 1, 2)** (https://nptel.ac.in/courses/106105183), accessed 2026-09-26.

Source licence: **CC BY-SA 4.0** — https://creativecommons.org/licenses/by-sa/4.0/

Changes made by AcademicsGen: the source text was rephrased, reorganised and grammar-corrected into study material; nothing added.

This PDF is shared under the same licence (CC BY-SA 4.0).