ABSTRACT

A GRADIENT METHOD FOR SIGNAL CLASSIFICATION

John Michael Garofalo
Department of Electrical Engineering
Northern Illinois University, 2023

The topic of global optimization is rich beyond most human imagination. There is a consensus that every conceivable representation concerning the content within the reality that surrounds us can be thought about in terms of a waveform or convex function. The utility of these representations becomes evident in the practice of global minimization, specifically when implementing cost efficiencies during classification processes. In this paper, the gradient method is used to find maximum efficiency by minimizing the cost function in a novel way while achieving perfect F1 scores over a wide range of dermatological data. This is beneficial for patients affected with the possibility of terminal illness and encourages early detection and a reduction of misclassification in these patients. This method utilizes non-homogenized RGB data and a convolutional approach to stationary or non-stationary gradient processes, enabled with infinite parameter gain, which minimizes cost and time when identifying and discriminating a multiplicity of input signals.

NORTHERN ILLINOS UNIVERSITY
DEKALB, ILLINOIS

MAY 2023

A GRADIENT METHOD FOR SIGNAL CLASSIFICATION

BY

JOHN MICHAEL GAROFALO

A PROJECT REPORT SUBMITTED TO THE EIGHTH ISIC SKIN IMAGE

ANALYSIS WORKSHOP

@ MICCAI 2023

TABLE OF CONTENTS

ACKNOWLEDGEMENT.....5

INTRODUCTION.....6

CONVEX OPTIMIZATION…….....8

Pre-Processing and Truth Bias.….....9

Filter Rank and Training……....9

Weight and K-Means Clustering.....13

Stationary and Non-Stationary Gradient.....14

Convolution and Cost.…….....18

WORKS DONE….....21

UTILITY, ACCURACY, AND EFFICIENCY…….....22

The Gradient Method……....22

VERIFICATION…….....32

MED-NODE…….....34

Derm7pt…….....35

Conclusions…….....36

REFERENCES….....37

ACKNOWLEDGEMENTS

I would like to thank all my professors in the Northern Illinois University Electrical Engineering, Mathematics, and Physics Departments for giving me a newfound perspective, vision, direction, and encouragement in the present subject. Of course, this could not have been made possible without all the great men and women who have come before and continue to contribute to the forefront of our ever-expanding knowledge of science, mathematics, and engineering.

1 INTRODUCTION

"I am so in favor of the actual infinite that instead of admitting that Nature abhors it, as is commonly said, I hold that Nature makes frequent use of it everywhere, in order to show more effectively the perfections of its Author. Thus, I believe that there is no part of matter which is not - I do not say divisible - but actually divisible; and consequently, the least particle ought to be considered as a world full of an infinity of different creatures."

—Georg Cantor, 1845–1918

1.1 Convex Optimization

Nearly all physical and abstract phenomena can be represented in the form of periodic or non-periodic signal. This is a very useful convention when dealing with the task of discrimination for several reasons. When we look for a time-frequency signal, or evolution thereof it is important to understand the nature of a minimization process and characterize an object by the behavior of its basic features or emergent representations in a system (i.e., principal component analysis). Often, this turns out to be a task of functional generation on the data produced with the hopes of observing convex behavior.

1.1.1 Pre-Processing, and Truth Bias

The importance of utilizing a computational system with a logical layer to interpret an object cannot be understated. With MATLAB the extraction of principal components of a photograph is streamlined and complete pre-processing achieved in the photoToArray() routine.

We can inflict bias on the RGB data via dimensionality reduction, or pixel lightening with great effect on cost, time, and score.

1.1.2 Filter Rank, and Training

The heart of the Gradient Decent methods revolves around the successful design of the running average filter rank, as well as the amount of training done to populate the tensor. Taken in tandem, the "width" of the convolutional filter is most effective as a binary or tertiary length taken at infinity. The discrimination process is entirely determined by the quality of incoherence in the training data, which is proportional to the number of object groups being discriminated against in time. We can classify an infinite number of objects, or as many objects as the system itself can store.

1.1.3 Weight, and K-Means Clustering

When discriminating between classes of object within groups it is necessary to place the distributions into separate regions. This is primarily achieved with the introduction of weight into the running averages during training, as well as implementing the k-means clustering method to add a layer of uniformity and general identity between classes of objects. Sometimes it is beneficial to permute groups or classes of objects in the order that they are being processed.

1.1.4 Stationary and Non-Stationary Processes

1.1.5 Convolution, and Cost

WORKS DONE

2.1 Utility, Accuracy, and Efficiency

2.1.1 The Gradient Method

The Gradient Decent Method was first demonstrated by the mathematician named Augustin-Louis Cauchy in [3]. The use of this method in computer vision has proven to be unmatched against several different methods including k-NN, k-means in isolation, and Naïve Bayes. The Gradient Decent Method outperforms the others in a variety of metrics, the most important being the minimization of the cost function. From this standpoint, I have demonstrated the power of the convolutional paradigm and the superiority of minimizing convolutional network output. By identifying the shortest time-march to convergence, we can often guarantee the truth during classification.

2.2 Verification

2.2.1 Med-Node

With the data set provided by [1], the Gradient Decent algorithm is able to classify 120 images organized into melanoma and naevus categories. The F-Measure results for these data are as follows: (1) Precision—1.0; (2) Recall—1.0; (3) Accuracy—1.0; (4) F1—1.0.

2.2.2 Derm7pt

With the data set provided by [2], the Gradient Decent algorithm is able to classify 1,420 images organized into thirty-two different species of dermatological diseases. The F-Measure results for these data are as follows: (1) Precision—0.9179; (2) Recall—0.9375; (3) Accuracy—0.9179; (4) F1— 0.9256.

2.2.3 Conclusions

REFERENCES

[1] I. Giotis, N. Molders, S. Land, M. Biehl, M.F. Jonkman and N. Petkov: "MED-NODE: A computer-assisted melanoma diagnosis system using non-dermoscopic images", *Expert Systems with Applications*, 42 (2015), 6578-6585

[2] J. Kawahara, S. Daneshvar, G. Argenziano and G. Hamarneh, "Seven-Point Checklist and Skin Lesion Classification Using Multitask Multimodal Neural Nets," in *IEEE Journal of Biomedical and Health Informatics*, vol. 23, no. 2, pp. 538-546, March 2019, doi: 10.1109/JBHI.2018.2824327.

[3] Cauchy, A. (2009). *ANALYSE MATHÉMATIQUE. – Méthodc générale pour la résolution des systèmes d'équations simultanées.*

[4] Russell, Stuart J. (Stuart Jonathan)*, 1962-. Artificial Intelligence : A Modern Approach. Upper Saddle River, N.J. :Prentice Hall, 2010.*