

2DM- Two Door Panel

Includes power for panel and readers with battery back up – expandable up to 4 doors

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader


Part: 2DM



Features

- Multi function as a **Server, Expansion panel or Elevator**
- Out of the box ready browser managed
- Embedded Linux operating system
- 4 Readers (In/Out)
- 4 Relays (Lock/Aux)
- 6 Inputs (REX, DPS, Aux) Global
- UL 294 Ed. 8 / CAN/ULC 60839-11-1:2022 Ed.2
- 5- year warranty

Optional Accessory



Part: ACM-2D

Add on 2 door module for future expansion

Technical Specification

Model	2DM
Operating System	Embedded Linux
Transactions	> 60 per second
System Power	115VAC – 35 Watt
Operating Temperature	50°F to 95°F (10°C to 35°C)
Enclosure Size (W x H x D)	14.25 x 14.25 x 3.75in (362 x 362 x 95mm)
Internal Power Supply	Controller & Readers Only
Lock out put power	NA
Battery Backup	Controllers & Readers Only
Recommended Battery Type (battery is not included)	Power sonic PS-1270-FI or Similar 12V, 7AH, Sealed Lead Acid with 0.187-inch terminals
Standby Power Requirement	400mA @ 12V
Readers (Wiegand)	4 Total, One In & One Out Reader for Each Door
Reader Power	300mA @ 12V Max per Reader 1000mA @ 12V Max per System
Request to Exit (REX) Inputs	2 Total, One for Each Door
Door Position (status) Inputs	2 Total, One for Each Door
Auxiliary Input	2 Total, General Purpose
Mechanical Tamper	Yes
Power Fault Monitoring	Yes
Door Lock Outputs	2 Form C Relay, 24V @ 2.0A
Auxiliary Outputs	2 Form C Relay, 24V @ 2.0A

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader