

4DM - Four Door Controller

Integrated power for the controller and readers with battery back up.

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader

Part: 4DM



Features

- Functions as a Server, Expansion panel or Elevator
- “Out of the Box” ready browser managed
- Embedded Linux operating system
- 4 Doors / 8 Readers (In/Out)
- 8 Relays (Lock/Aux)
- 12 Inputs (REX, DPS, Aux) Global
- OSDP 2.2 compliant
- UL 294 Ed. 8 / CAN/ULC 60839-11-1:2022 Ed.2
- 5-year hardware warranty

Technical Specification

Model	4DM
Processor	Quad Core , 1.5 GHz
Memory	1GB DDR3 & 8GB eMMC
Operating System	Embedded Linux
Transactions	> 60 per second
System Power Requirements	115VAC @ 1.5A
Operating Temperature	50°F to 95°F (10°C to 35°C)
Enclosure Size (W x H x D)	14.25 x 14.25 x 3.75in (362 x 362 x 95mm)
Internal Power Supply	Controller, Readers & 12V & 24V DC for Door Locks
Battery Backup	Controllers, Readers, & Door Locks
Recommended Battery Type (Battery is not included)	12V, 7AH, Sealed Lead Acid with 0.187-inch terminals
Standby Power Requirement	450mA @ 12V
Readers (Wiegand & OSDP 2.2)	8 Total, One In & One Out Reader for Each Door
Reader Power	300mA @ 12V Max per Reader 1000mA @ 12V Max per System
Request to Exit (REX) Inputs	4 Total, One for Each Door
Door Position (status) Inputs	4 Total, One for Each Door
Auxiliary Input	4 Total, General Purpose
Tamper Input	Yes
Power Fault Monitoring	Yes
Door Lock Relay Ratings	4 Form C Relay, 24V @ 2.0A
Auxiliary Relay ratings	4 Form C Relay, 24V @ 2.0A

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader