

13.5 MHz Contactless Card Reader

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader

Part # MI-RD-M

MIFARE is the [NXP Semiconductors](#)-owned trademark of a series of [integrated circuit \(IC\)](#) chips used in some [contactless smart cards](#).

Mi-RD-M conforms to the [ISO/IEC 14443](#) Type A 13.56 [MHz](#) contactless smart card standard. It uses [AES](#) and [DES/Triple-DES](#) encryption.



Features

- Secure Smart Card Technology
- Modern LED design for a premium look
- Fully potted and functional at extreme temperatures
- Mullion mounted
- Indoor / Outdoor applications
- Compatible with “Mi” series of credentials
- Wires like most Wiegand readers
- Red, Read LED
- Sounder option (Wire Connection)
- Color – Black
- 18” Pigtail connection
- 5-year hardware warranty

Technical Specification

Model	
Frequency	13.56 MHz
Card / Fob Type	Encrypted
Operating Voltage	9 – 24 V DC
Standby Current	<25 mA
Read Range	12VDC @ 4Amp
Operating Temperature	-40 F - 140 F
Enclosure Size (W x H x D)	4” x 1.88 x 0.75 in
Index of protection	Potted – IP 66
Operating Humidity	10% to 95% RH
Output Format	32 bits Wiegand – Designed to decode credentials for Mi an ET Series Readers
Credential Parts:	
ISO Proxcard	Mi-ISO-Crd-25
Fob	Mi-Fob-25
Wafer	Mi-Wafer-25

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader

13.5 MHz Contactless Credentials

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader

Part # Mi-ISO-Crd-25



Features

- Secure Smart Card Technology
- Sicunet Branded
- Laser printed FC and Card Number
- ISO Thickness – Blank printable back
- Works with Mi-RD-M and all mobile credential readers
- Dots for Lanyard punch alignment
- Pack of 25 in sequential order

*Black outline is Die-cut line

**Back side is blank

Specification

Quantity per pack	25 white cards
Frequency	13.56 MHz
Type	Card
Bit type	32 bit credential

Part # Mi-Fob-25



Features

- Secure Smart Credential Technology
- Sicunet Branded
- Laser printed FC and Card Number on back of each FOB
- Works with Mi-RD-M and all ET Series mobile credential readers
- Pack of 25 in sequential order

Specification

Quantity per pack	25 blue key fobs with key ring
Frequency	13.56 MHz
Type	Fob
Bit type	32 bit credential

Part # Mi-Wafer-25



Features

- Secure Smart Credential Technology
- Sicunet Branded
- Printed FC and Card Number
- Works with Mi-RD-M and all ET Series mobile credential readers
- Pack of 25 in sequential order

*Red outline is Die-cut line

**Back side 3M Adhesive

Specification

Quantity per pack	25 PVC Wafers
Frequency	13.56 MHz
Wafer Size	1.18"
Bit type	32 bit credential

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader