


Mobile Access Control Readers - Wavelynx

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader



ET5 / ET10



ET20



ET25

Sicunet's line of multi-technology contactless access control readers offers a modern aesthetic and a state-of-the-art feature set. Sicunet's access system provide automated issuance and enrollment of mobile credentials providing a fast and more efficient credential management. All readers offer Wiegand as well as OSDP™ compliant output. Each are currently enabled for Secure Channel and remote firmware upgrades. Sicunet readers offer OSDP Auto-Detect, automatically detecting Wiegand or OSDP over the same wires.

KEY FEATURES

- Multiple technologies in a single reader: Proximity, Smart, NFC & BLE
- OSDP Auto-Detect
- OSDP Secure Channel and remote firmware upgradability
- MIFARE DESFire® EV1 & EV2 support
- FSK and ASK legacy proximity credentials support for seamless transitions
- Tri-state LED light bar (red, green, amber) and audible beeper
- Designed to meet the harshest indoor and outdoor installation environments

Model	ET5	ET10	ET20	ET25
Style	Mullion	Mullion	Single gang	Single gang with Keypad
Environment	In / Outdoor - IP55 Rated			
RF Technologies	13.56MHz & Mobile	125 KHz & 13.56MHz & Mobile		
Voltage	106 mA average, 144 mA peak		118 mA average, 169 mA peak	
Current	5-16 V DC			
Temp Range	UL™ tested -35° to 66°C and EN -40° to 70°C and 95% humidity			
Dimensions	5.1” x 1.7” x 0.71		5.1” x 3.25” x 0.71	
Read Ranges	EV1: 1.2”, EV2: 2.2”, 125 KHz up to 4"		EV1: 1.5”, EV2: 2.5”, 125 KHz up to 4”	
Output	Wiegand, OSDP			
Warranty	Lifetime			3 Years
Certifications	FCC, IC, CE, UL 294, EN 302291, EN 301489, EN 300330, EN 50130-4, BIS IS 13252			

CCTV | Security System | Elevator Control | Intercom | Multi Site | Mobile Credentials | Facility Automation | Mobile App | On-Premise | Cloud | Video Directory Intercom | QR Code Reader

BLE Credentials:



Device No	1234
User No	1
User Key	JSmith@blecredential.com
format	W36-9

Sicunet Credential: Available on the App Store or Google Play

Touch Less Mobile Credentials: Safe, Secure, and Convenient Issuance

Sicunet Credential application securely stores your BLE / NFC ID and communicates it securely to your access control system for authentication. Sicunet Credential features mobile “touchless” cloud-issued credentials for automated and manual enrollment into your access control system.

Sicunet Credentials offer two methods of issuance.

With Sicunet Access Control, the issuance and database data is automatically synchronized via the credential issuance server. Whether you are adding one or many adding users is fast and easy. Sicunet’s embedded flat file bulk loading import tool allows the administrator bulk load users into the access system and then with one click send credential invitation, issue a unique credential to each user and automatically populate the mobile credential data in the system. The integrated process is fast, saving the system administrator data entry time, providing an exceptional TCO when compared to other systems.

For legacy or other access systems looking to also use the mobile credentials the administrator can manually issue the credential invitation via Sicunet Credential cloud User Interface and manually enter the card data into most existing systems.

Ultra low battery draw as the application stays almost completely dormant, only becoming active when readers are nearby / in range of the device.

TECHNICAL FEATURES

- Bluetooth® Low Energy for iOS and Android
- Ultra-fast transaction times of less than 1 second
- Complete user privacy
- No personal information is used by the app
- All data is stored in separate secure element
- Guaranteed uniqueness of Sicunet Credential ID
- ID data secured at rest in device in secure enclave storage
- Fully authenticated issuance from secure cloud credential authority
- End-to-end encrypted and signed credential data (AES 256)
- Multi-factor authentication using both user PIN and device security
- Hardware Requirements: Android devices with NFC and iPhone® 6 and later
- Available for iOS 10 and later and Android Marshmallow 6.0 and later
- ID is selectable for 26-bit or 36-bit unique number (Start and stop parity bits apply emulating traditional proximity card for legacy system integration)
- Once a credential is sent and enrolled into the access system the mobile device does not require an internet connection. The phone and reader interaction is now standalone
- Hold-to-reader mimics proximity card (short read range)

TIPS

- Hold phone within 1 inch of the reader
- Some phone cases may interfere with communication—remove case when troubleshooting
- On Android, ensure the screen is illuminated (device does not need to be unlocked)
- Ensure NFC is enabled on Android and BLE is enabled on iOS

