

Sicunet's "Automated Credential Issuance" ACI and complete line of readers seamlessly allows administrators to send mobile credentials with "one click" invitation. ACI is easy and reduces the Total Cost Of Ownership "TCO" by dramatically reduces the time managing credential data and issuance.

Sicunet's line of multi-technology contactless access control readers offers a modern aesthetic and a state-of-the-art feature set. Reader RF options include Proximity (125 kHz), Smart (13.56 MHz), NFC, and Bluetooth®, so that customers can set their migration path to secure credentials and security ecosystems.



SC-CSR-35L Bluetooth Low-Energy (BLE)/Contactless Smartcard Reader



SICUNET MOBILE SMARTPHONE ACCESS CONTROL ID SOLUTION

With Sicunet and Farpointe, the smartphone is the access credential

Sicunet and Farpointe Data's mobile-ready access control ID solution—consisting of a smartphone app, mobile and physical credentials, and Bluetooth Low Energy (BLE) readers. Based upon the proven LEGIC® contactless digital radio frequency identification (RFID) platform. The readers support Wiegand protocol or the bi-directional Open Supervised Device Protocol (OSDP).*

In addition to supporting mobile access credentials, using the BLE feature of select smartphones, The reader supports a range of traditional physical access credentials, such as clamshell cards, ISO cards, and key tags.

Featuring easy automated issuance of mobile credentials, and multi-technology readers, Sicunet is the next-generation ID solution for lower cost management of your access systems.

Benefits:

- Readers read Sicunet BLE mobile credentials as well as traditional cards and tags
- Readers are OSDP Verified by SIA*
- Fully potted, IP67-rated design for outstanding durability indoors or out
- Supports industry standard and custom formats
- Field-adjustable read ranges up to 15 feet (4.6 m)

*OSDP readers are independent models and need to be appended with the suffix "-OSDP" when ordering (Example: CSR-35L-OSDP).

Mobile Support as Easy as 1-2-3!

1. Add a user into the access system.

End users appreciate the one click issuance
The system automatically produces key in the system.

2. Mobile credentials with digital delivery

Recipient get an email that step through the enrollment
The invitation auto populates the access system and app
Simplifies and reduces indirect labor or credential issuance.

3. Readers combining BLE and traditional RFID technologies

Sicunet allows access control supports mobile credentials and traditional physical credentials.



Look for **Sicunet** on the App Store and on Google Play

Readers & Credentials

SELECTION GUIDE



BLE/Contactless Smartcard Readers^{1,2}

	Frequency	Read Range ³	Mullion Mount	Single-Gang Mount	Lifetime Warranty
SC-CSR-35L	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 1.5 inches (38 mm)	•	•	•
SC-CSR-6.2L(2x6 keypad)	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 2 inches (51 mm)	•		•
SC-CSR-6.4L(3x4 keypad)	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 2 inches (51 mm)		•	•

BLE/Proximity Readers²

SC-PCR-35L	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)	•	•	•
SC-PCR-620L(2x6 keypad)	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)	•		•
SC-PCR-640L(3x4 keypad)	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)		•	•



AES

Credentials	Frequency	Read Range	DESFire EV2	MAXSecure™	ValidID™	Wiegand	Magnetic Stripe	Lifetime Warranty
CSC-2	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•		•
CSM-2P	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•		1 Year
CSM-2S	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•	•	1 Year
CSK-2	13.56 MHz	up to 1 inch (25 mm)	•	•	•	•		1 Year

¹ CSR line Revision 8 or newer includes technology support for certain HID® standard classic-type 13.56-MHz contactless smartcard protocols.

² Mobile credential read range can be adjusted on-site in the field. Please see our [BLE Range Setting Reference Document](#) for details.

Farpointe Data reserves the right to change specifications without notice.

© 2018-2024 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE and MIFARE DESFire are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.