Quadratic Studio

Muratbek Nurniyaz · Quadratic equations · Individual project

Live: johndoe018.github.io/bekarys1/ · **Source:** github.com/johndoe018/bekarys1

One concept. Three starting points.

A responsive learning lab develops one core task: finding and interpreting the zeros of a quadratic. A shared seed connects three differentiated versions; eight seeds provide 24 tasks. Learners choose their level, receive progressive guidance and check their understanding.

LEVEL	EXAMPLE & VERIFIED RESULT	DIFFERENTIATION
Foundation	$x^2 - 5x + 6 = 0$ Roots: 2 and 3	Integer factors; visible three-step scaffold; direct hints and zero-product reasoning.
Standard	$2x^2 - 10x + 9 = 0$ Roots: $(5 \pm \sqrt{7}) / 2$	Non-monic equation; irrational roots; discriminant and quadratic formula; less scaffolding.
Advanced	$h(t) = -5t^2 + 25t + 30$ Landing: 6 s; maximum: 61.25 m	Physical domain and units; reject negative time; evaluate the vertex at $t = 2.5$ s.

AI architecture

Transformers.js runs the open-source SmolLM2-135M-Instruct model (q4) in a browser Web Worker using ONNX WASM. The first coach request downloads model files; inference runs on-device. No API key or external inference backend is required; questions are not uploaded. Deterministic code transforms parameters and checks answers. The model selects a verified guidance card using the learner's question and level. Constrained decoding permits only four labels; displayed mathematics is never unrestricted model prose.

Prompt design

Abridged system template: "Select the most useful VERIFIED guidance card for the learner. [Level-specific style.] Output exactly one letter: A, B, C or D. A = next step; B = why the method works; C = checking an answer; D = a deeper connection. Do not generate mathematics or prose."

Foundation prioritises direct scaffolding and one small next step. **Standard** supports independent reasoning about coefficients, Δ and ± cases. **Advanced** emphasises units, the physical domain and the vertex. Context includes the equation, level, question and four verified cards, adapted to hints used and checking feedback. The model's relative label scores choose the card; final results appear only with an open walkthrough. Exact prompts: **src/math.js**.

Feedback, validation and limitations

Immediate checking accepts fractions, radicals and decimals within 0.01, and explains notation errors, duplicate roots and inadmissible negative time. Hints, complete solutions and an interactive graph support self-paced learning. Progress is stored locally. Ten test groups verify all 24 tasks, parsing, prompt context and output constraints; browser checks exercise learning interactions and the honestly labelled model-unavailable fallback. Real browser model selection passed on all three levels in GitHub Actions. The source is public and the Pages deployment succeeded. Free-form outputs were rejected after real tests found errors; constrained selection prevents invented displayed mathematics.

Development disclosure: Prepared with AI assistance; mathematics verified independently of model output.
References: huggingface.co/docs/transformers.js · huggingface.co/HuggingFaceTB/SmolLM2-135M-Instruct · vite.dev/guide/static-deploy.html · GitHub Pages documentation.