

## M-1 FLOOR FRAMING PLAN - NE SECTOR SHEET S1.20

LEGEND: BRACE FRAME PER ELEVATION BRACING (dashed)

GRID: H.1 to R.8 / 5 to 8

BEAMS:

W24x76 Length 17'-7"

W24x62 Length 18'-10"

W21x50 Length 17'-11"

W21x44 Length 12'-5"

W18x35 Length 15'-6"

W16x26 Length 19'-2"

W12x19 Length 12'-5"

W12x14 Length 15'-6"

B1 W18x35 Length=24'-0" Material A992 Start EL +12.500 End EL +12.500

B-2 W21x44 L=30'-6" A992 EL +12.500 EL +12.500

BRACING:

BR1 HSS6x6x3/8 Length 18'-10"

BR-2 HSS5x5x3/8 Length 17'-7"

BRACE BR3 L4x4x3/8 Length 12'-5"

Diagonal bracing BR4 HSS4x4x1/4 Length 15'-6"

BASE PLATE SCHEDULE

BP1 PLATE 600x600x30 Thickness 30 Anchor 4-M20 Top of Concrete EL 0.000

## BRACE FRAME ELEVATION Detail 11/S5.61

### COLUMN SCHEDULE / ELEVATION VIEW

C1 W14x82 Height=14'-0" Base Elevation +0.000 Top Elevation +14.000 Material A992

COL-2 W12x65 Ht=3750mm Base EL 0.000 Top EL +3.750 A572 Gr.50

C3 UC254x254x73 Height=4500mm Base Elevation -0.500 Top Elevation +4.000 S355JR

Column C4 W10x49 Height=12'-0" Base Elevation 0'-0" Top Elevation 12'-0" A36

C5 W14x61 Height=16'-0" Base Elevation 0'-0" Top Elevation 16'-0" A992