

Etihad Airways AWO Approvals

Notes: (*) CAT II approaches for category D aircraft, RVR of 300m may be used only when an autoland is been conducted.

(**) Whenever multiple RVR observations are reported for the runway. If only Touchdown RVR is available then LVTO minima shall be 350 metres.

Country	Dest	Approval	Date	Serial Number	Type	Category	Approach Ban		CAT II (RA/RVR)		CAT IIIA	CAT IIIB	LVTO	
									C	D	(DH/RVR)	(DH/RVR)	C	D
Australia	MEL	Letter	18-May-10	EF09/3132 ARN 764490	A330-200	CAT II / IIIA + B	1000 ft	DH	100ft	100ft	50ft	NO	125m	150m
					A340-500/600			RVR	300m	350m *	200m	75m		
					B777-300									
Belgium	BRU	Letter	17-Mar-06	AIR/KT/0594	All	CAT II / III	OM / Equivalent Point	DH	chart	chart	50ft	NO	150m	150m
								RVR	300m	350m *	200m	150m		
Belarus	MSQ	AIP	Current	ENR Section	All	CAT II	OM / Equivalent Point	DH	chart	chart			150m	200m
								RVR	350m	350m				
Canada	YYZ	Foreign Air Operations Specifications	21-Apr-06	F-10757	All	CAT II / III	OM / Equivalent Point	DH	chart	chart	50ft		600ft	600ft
								RVR	1200ft	1200ft	600ft			
France	CDG	Letter	21-Nov-06	2006/4009-DCS/NO/OA	All	CAT II / III	OM / Equivalent Point	DH	100ft	100ft	50ft	20ft	125m	150m
	LYS							RVR	300m	350m *	200m	125m		
	ORY													
Germany	FRA	Letter	10-Oct-06	B138F-439 ETD	All	CAT II / IIIA + B	OM / Equivalent Point	DH	chart	chart	50ft	NO	125m	150m
	HHN							RVR	300m	350m *	200m	75m		
	MUC													
India	DEL	Letter	29-Jul-08	A.V.22029/1/2005-FID	All	CAT II / IIIA + B	OM / Equivalent Point	DH	100ft	100ft	50ft	NO	200m**	200m**
								RVR	350m	350m	200m	75m		
	CCU					CAT II		DH	100ft	100ft				
								RVR	350m	350m				
Ireland	DUB	Letter	1-May-07	LVO and LVTO	All	CAT II / IIIA	OM / Equivalent Point	DH	chart	chart	50ft		125m	150m
								RVR	300m	350m *	200m			
Italy	MXP	AIP	Current	ENR Section 1.6.2	All	CAT II / IIIA + B	OM / Equivalent Point	DH	chart	chart	50ft	NO	125m	150m
	BGY							RVR	300m	350m *	200m	75m		
Kazakhstan	ALA	AIP	Current	ENR Section	All	CAT II / IIIA	OM / Equivalent Point	DH	chart	chart	50ft		125m	150m
	TSE							RVR	350m	350m	200m			

Etihad Airways AWO Approvals

Page : 2
Revision: 27
Author : FOS
Date : 24-Feb-11

Notes: (*) CAT II approaches for category D aircraft, RVR of 300m may be used only when an autoland is been conducted.

Country	Dest	Approval	Date	Serial Number	Type	Category	Approach Ban		CAT II (RA/RVR)		CAT	CAT	LVTO	
											IIIA	IIIB		
									C	D	(DH/RVR)	(DH/RVR)	C	D
Korea	ICN	Letter	6-Jan-11	Ref. Flight Operations Div.	All	CAT II / IIIA + B	1000ft	DH	100ft	100ft	50ft	NO	125m	150m
						RVR		350m	350m	200m	75m			
	GMP					CAT II / IIIA		DH	chart	chart	50ft			
						RVR		350m	350m	200m				
Kuwait	KWI	Letter	17-Oct-06 11-Apr-10	REF:643/8 REF: 3884/51	A330	CAT II	OM / Equivalent Point	DH	100ft	100ft			150m	200m
					A346			RVR	300m	350m *				
					B777									
Morocco	CMN	Letter	31-Aug-06	NO: 1550/DAC/DSA/OPS	All	CAT II / IIIA	OM / Equivalent Point	DH	100ft	100ft	50ft		150m	200m
								RVR	350m	350m	200m			
Pakistan	LHE	Letter	14-Dec-04	HQCAA/5262/85/FS/1856	All	CAT II	OM / Equivalent Point	DH	100ft	100ft			150m	200m
								RVR	350m	350m				
Qatar	DOH	Letter	13-Apr-10	CA/ASD/DIA/OPS/82/12/10	All	CAT II / IIIA + B	1000 ft	DH	100ft	100ft	50ft	NO	125m	150m
								RVR	300m	350m *	200m	150		
Russia	DME	AIP	Current	ENR Section	All	CAT II / IIIA	OM / Equivalent Point	DH	chart	chart	50ft		150m	200m
								RVR	350m	350m	200m			
Saudi Arabia	JED	Letter	11-May-05	N0: 9/8/A5/266	All	CAT II	FAF	DH	100ft	100ft			200m	200m
								RVR	350m	350m				
South Africa	JNB	Letter	23-Mar-06	CAA/ETIHAD	A330/A340/B777	CAT II	OM / Equivalent Point	DH	100ft	100ft			150m	200m
								RVR	300m	350m *				
	CPT					CAT II / IIIA + B		DH	100ft	100ft	50ft	NO	125m	150m
						RVR		300m	350m *	200m	150m			
Switzerland	GVA	Letter	22-Jan-06	REF: 5/52/52-99	A330 / A340	CAT II / IIIA + B	OM / Equivalent Point	DH	100ft	100ft	50ft	NO	150m	200m
			23-Mar-06	REF:5/52/52-99	B777									
			4-Feb-05	REGISTER 652.00				RVR	300m	350m *	200m	75m		

Etihad Airways AWO Approvals

Page : 3
Revision: 27
Author : FOS
Date : 24-Feb-11

Notes: (*) CAT II approaches for category D aircraft, RVR of 300m may be used only when an autoland is been conducted.

Country	Dest	Approval	Date	Serial Number	Type	Category	Approach Ban		CAT II (RA/RVR)		CAT	CAT	LVTO	
											IIIA	IIIB		
									C	D	(DH/RVR)	(DH/RVR)	C	D
Thailand	BKK	Letter	14-Sep-06	NO. 0507/6372	A330	CAT II	1000 ft	DH	100ft	100ft			200m	250m
		Letter	11-Feb-10	NO. 0506/1173	A346	CAT II		RVR	350m	350m				
					B777	CAT II								
U.A.E.	AUH	Letter	6-Nov-08	24300/32127/AUH/08	All	CAT II / IIIA + B	1000 ft	DH	100ft	100ft	50ft	NO	125m	150m
	DXB								TD / MP / RO					
								RVR	300m/200m/200m		200 m	75m		
United Kingdom	LHR	EMAIL	14-Nov-05	CAP393	All	CAT II / IIIA + B	1000 ft	DH	chart	chart	50ft	NO	125m	150m
	MAN							RVR	300m	350m *	200m	75m		
	LGW													
USA	JFK	Foreign Air Operations Specifications	28-May-10	YY6F141F	A330-200/300	CAT II / IIIA + B	FAF	DH	100ft	100ft	50ft	NO	600ft	600ft
	ORD				A340-500/600	CAT II / IIIA + B								
					B777-300	CAT II / IIIA + B								
								RVR	1000ft	1000ft	700ft	600ft		

ETIHAD AIRWAYS - UNITED ARAB EMIRATES