



北京大學  
PEKING UNIVERSITY

# Integrating Relation Constraints with Neural Relation Extractors

**Yuan Ye**, Yansong Feng\*, Bingfeng Luo, Yuxuan Lai, Dongyan Zhao

Wangxuan Institute of Computer Technology, Peking University

# Relation Extraction



**Relation Extraction (RE)** aims to extract predefined relations between two marked entities in plain texts.

*Barack Obama married Michelle Obama on October 3, 1992.*

*Entity<sub>1</sub>*

*Entity<sub>2</sub>*

*Spouse*

# Motivation



北京大学  
PEKING UNIVERSITY

<USA, New York>, <i>LargestCity</i>

<USA, Washington D.C.>, <i>Capital</i>

<Richard Fuld, USA>, <i>Nationality</i>

# Motivation




<USA, New York>, <i>LargestCity</i>
<i>Capital</i> : 0.5
<i>LargestCity</i> : 0.4
<i>LocationCity</i> : 0.05

<USA, Washington D.C.>, <i>Capital</i>
<i>Capital</i> : 0.95
<i>LocationCity</i> : 0.03

<Richard Fuld, USA>, <i>Nationality</i>
<i>Nationality</i> : 0.7
<i>BirthPlace</i> : 0.2

# Motivation



# Relation Constraints



北京大学  
PEKING UNIVERSITY

Set	Sampled Positive Rules
$C^{ts}$	<i>(almaMater, knowFor), (city, region), (spouse, child)</i>
$C^{to}$	<i>(almaMater, owner), (city, hometown), (capital, city)</i>
$C^{tso}$	<i>(birthPlace, capital), (child, spouse), (city, country)</i>
$C^{cs}$	<i>almaMater, country, city, hometown</i>
$C^{co}$	<i>foundationPerson, child, knownFor, product</i>

Table 1: Example rules for each constraint set  $C^\phi$ .

# Relation Constraints




北京大学  
PEKING UNIVERSITY

Set	Sampled Positive Rules
$C^{ts}$	<i>(almaMater, knowFor), (city, region), (spouse, child)</i>
$C^{to}$	<i>(almaMater, owner), (city, hometown), (capital, city)</i>
$C^{tso}$	<i>(birthPlace, capital), (child, spouse), (city, country)</i>
$C^{cs}$	<i>almaMater, country, city, hometown</i>
$C^{co}$	<i>foundationPerson, child, knownFor, product</i>

Table 1: Example rules for each constraint set  $C^\phi$ .

# Our Approach






# Our Approach




北京大学  
PEKING UNIVERSITY



# Our Approach



北京大学  
PEKING UNIVERSITY



*Coherent* treats one constraint set as a whole.




*Semantic* pays more attention to which specific rules in the constraint sets the pairwise local predictions should satisfy.

# Our Approach




北京大学  
PEKING UNIVERSITY



# Our Approach




北京大学  
PEKING UNIVERSITY



# Our Approach



北京大学  
PEKING UNIVERSITY




# Our Approach



北京大学  
PEKING UNIVERSITY

$$f(p^m, p^n, c) = \prod_{u_i=1} q_i \prod_{u_i=0} (1 - q_i) \quad q_i = p_i^m + p_i^n - p_i^m p_i^n$$

$$L(p^m, p^n, C^\phi) = -I_\phi^{mn} \log \sum_{c \in C^\phi} f(p^m, p^n, c)$$



# Experiments



## Datasets

- ◆ **English Dataset:** constructed by mapping triples in *Dbpedia* to sentences in the *New York Times* corpus
- ◆ **Chinese Dataset:** built by mapping the triples of *HudongBaiKe*, a large Chinese encyclopedia, with four Chinese economic newspapers



	Relations	Train Set		Test Set		Constraints
		# Triples	# Sent	# Triples	# Sent	
English Dataset	51	50k	134k	30k	53k	541
Chinese Dataset	28	60k	120k	40k	83k	110

# Experiments



北京大学  
PEKING UNIVERSITY

## Main Results





# Experiments



北京大学  
PEKING UNIVERSITY

## Main Results

Model Name	English Dataset				$\Delta_{Base}$
	P@100	P@200	P@300	Mean	
<i>ACNN</i>	96.70	92.61	91.72	93.68	—
<i>ACNN(Coh)</i>	97.39	93.78	90.69	93.96	+0.3
<i>ACNN(Sem)</i>	97.62	95.87	94.12	95.87	+2.2
<i>ACNN+ILP</i>	97.87	94.36	93.16	95.13	+1.5
<i>ACNN(Coh)+ILP</i>	97.73	94.51	91.29	94.51	+0.8
<i>ACNN(Sem)+ILP</i>	<b>98.17</b>	<b>96.6</b>	<b>95.48</b>	<b>96.75</b>	<b>+3.1</b>
<i>APCNN</i>	100	98.97	97.41	98.79	—
<i>APCNN(Coh)</i>	100	99.57	97.33	98.97	+0.2
<i>APCNN(Sem)</i>	100	100	97.95	99.32	+0.5
<i>APCNN+ILP</i>	100	99.13	97.55	98.89	+0.1
<i>APCNN(Coh)+ILP</i>	100	100	98.03	99.34	+0.6
<i>APCNN(Sem)+ILP</i>	<b>100</b>	<b>100</b>	<b>98.39</b>	<b>99.46</b>	<b>+0.7</b>



<USA, New York>, <i>LargestCity</i>
<i>Capital</i> : 0.5
<i>LargestCity</i> : 0.4
<i>LocationCity</i> : 0.05

<USA, Washington D.C.>, <i>Capital</i>
<i>Capital</i> : 0.95
<i>LocationCity</i> : 0.03

<Richard Fuld, USA>, <i>Nationality</i>
<i>Nationality</i> : 0.7
<i>BirthPlace</i> : 0.2

# Experiments



## Main Results

Model Name	English Dataset				$\Delta_{Base}$
	P@100	P@200	P@300	Mean	
<i>ACNN</i>	96.70	92.61	91.72	93.68	—
<i>ACNN(Coh)</i>	97.39	93.78	90.69	93.96	+0.3
<i>ACNN(Sem)</i>	97.62	95.87	94.12	95.87	+2.2
<i>ACNN+ILP</i>	97.87	94.36	93.16	95.13	+1.5
<i>ACNN(Coh)+ILP</i>	97.73	94.51	91.29	94.51	+0.8
<i>ACNN(Sem)+ILP</i>	<b>98.17</b>	<b>96.6</b>	<b>95.48</b>	<b>96.75</b>	<b>+3.1</b>
<i>APCNN</i>	100	98.97	97.41	98.79	—
<i>APCNN(Coh)</i>	100	99.57	97.33	98.97	+0.2
<i>APCNN(Sem)</i>	100	100	97.95	99.32	+0.5
<i>APCNN+ILP</i>	100	99.13	97.55	98.89	+0.1
<i>APCNN(Coh)+ILP</i>	100	100	98.03	99.34	+0.6
<i>APCNN(Sem)+ILP</i>	<b>100</b>	<b>100</b>	<b>98.39</b>	<b>99.46</b>	<b>+0.7</b>

After equipped with our *CLC* modules, i.e., *Coherent* and *Semantic*, both *ACNN* and *APCNN* obtain improvement on the English dataset.

# Experiments



## Main Results

Model Name	English Dataset				$\Delta_{Base}$
	P@100	P@200	P@300	Mean	
<i>ACNN</i>	96.70	92.61	91.72	93.68	–
<i>ACNN(Coh)</i>	97.39	93.78	90.69	93.96	+0.3
<i>ACNN(Sem)</i>	97.62	95.87	94.12	95.87	+2.2
<i>ACNN+ILP</i>	97.87	94.36	93.16	95.13	+1.5
<i>ACNN(Coh)+ILP</i>	97.73	94.51	91.29	94.51	+0.8
<i>ACNN(Sem)+ILP</i>	<b>98.17</b>	<b>96.6</b>	<b>95.48</b>	<b>96.75</b>	<b>+3.1</b>
<i>APCNN</i>	100	98.97	97.41	98.79	–
<i>APCNN(Coh)</i>	100	99.57	97.33	98.97	+0.2
<i>APCNN(Sem)</i>	100	100	97.95	99.32	+0.5
<i>APCNN+ILP</i>	100	99.13	97.55	98.89	+0.1
<i>APCNN(Coh)+ILP</i>	100	100	98.03	99.34	+0.6
<i>APCNN(Sem)+ILP</i>	<b>100</b>	<b>100</b>	<b>98.39</b>	<b>99.46</b>	<b>+0.7</b>

Applying ILP to our approach can obtain further improvement.

# Experiments



北京大学  
PEKING UNIVERSITY

## Main Results

English Dataset					
Model Name	P@100	P@200	P@300	Mean	$\Delta_{Base}$
ACNN	96.70	92.61	91.72	93.68	—
ACNN( <i>Coh</i> )	97.39	93.78	90.69	93.96	+0.3
ACNN( <i>Sem</i> )	97.62	95.87	94.12	95.87	+2.2
ACNN+ILP	97.87	94.36	93.16	95.13	+1.5
ACNN( <i>Coh</i> )+ILP	97.73	94.51	91.29	94.51	+0.8
ACNN( <i>Sem</i> )+ILP	<b>98.17</b>	<b>96.6</b>	<b>95.48</b>	<b>96.75</b>	<b>+3.1</b>

# Conclusions



- A unified framework to integrate relation constraints with neural networks for RE
  - Coherent (general perspectives), Semantic (precise perspectives)
  - Validating our approach on English and Chinese datasets
- Our study reveals that learning with the constraints can better utilize the constraints from a different perspective compared to the ILP post-processing method



北京大學  
PEKING UNIVERSITY

**Thank you!**

**Q&A**

[pkuyeyuan@pku.edu.cn](mailto:pkuyeyuan@pku.edu.cn)

WICT, PKU