

UNIVERSITY COLLEGE LONDON
DEPARTMENT OF SPACE AND CLIMATE PHYSICS

Candidate Code: HYXC3

Programme Title: MSc Scientific Computing

Module Code: SPCE0038

Module Title: Machine Learning with Big Data

End Assessment

In submitting this coursework, I assert that the work presented is entirely my own except where properly marked and cited.

Date of Submission:	11/05/20
------------------------	----------

Question 1

1(a)

With reference to the diagram of the basic *logistic unit* on the following page:

The input vector \mathbf{x} is the input to the *logistic unit*.

Each input x_i has an associated weight θ_i . The weights are set to a random value prior to *training*. The *training* process determines these weights.

The product of each input x_i and weight θ_i is summed to produce a weighted sum z .

The output, $h_\theta(x)$, is the the non-linear *activation function*, h , applied to z .

1(b)

Consider the diagram of Question 1(a).

The weighted sum of the inputs, z , is:

$$z = \sum_{j=1}^n \theta_j x_j = \theta^T x \quad (1)$$

where x_i is the i^{th} element of input vector \mathbf{x} of length n , and θ_i is the associated *weight*.

And, the output from the *logistic unit*, $h_\theta(x)$, is:

$$h_\theta(x) = h(z) \quad (2)$$

where h is a non-linear *activation function*.

Question 1(a) – Basic Logistic Unit



x_i : Input

θ_i : Weight

Weighted Sum: $z = \sum_{j=1}^n \theta_j x_j = \theta^T x$

Activation: $a = h(z)$

1(c)

See diagram on following page.

1(d)

Consider the diagram of Question 1(c).

Firstly, consider the data transformation from the input vector \mathbf{x} to the hidden layer. We now need two indices, one for the input vector elements, and one for the *hidden layer* nodes. We will use i for the input vector index, and j for the *hidden layer* nodes.

The weighted sum of the inputs at the j^{th} *hidden layer* node is:

$$z_j = \sum_{i=1}^n \theta_{ij} x_i \quad (3)$$

where θ_{ij} is the weight between input element i and *hidden layer* node j , and n is the length of the input vector \mathbf{x} .

Secondly, the output from each *hidden layer* node is the non-linear *activation function*, h , applied to each z_j :

$$h_{\theta_j}(x) = h(z_j) \quad (4)$$

And finally, the output from the whole network, $h_{\Theta}(x)$ is the sum of the *hidden layer* outputs:

$$h_{\Theta}(x) = \sum_{j=1}^m h_{\theta_j}(x) \quad (5)$$

where m is the number of *hidden layer* nodes.

Question 1(c) – Fully Connected, Feed Forward, Artificial Neural Network



x_i : Input

θ_{ij} : Weight, e.g. θ_{11} θ_{33}

Weighted Sums:
$$z_j = \sum_{i=1}^n \theta_{ij} x_i$$

Activations:
$$a_j = h(z_j)$$

- Input Layer Logistic Units
- Hidden Layer Logistic Units
- Output Node

1(e)

The cost function typically used to train neural networks for regression problems is *mean square error*:

$$MSE(\Theta) = \frac{1}{m} \sum_i \sum_j (p_j^{(i)} - y_j^{(i)})^2 \quad (6)$$

The cost function typically used to train neural networks for classification problems is *cross-entropy*:

$$C(\Theta) = -\frac{1}{m} \sum_i \sum_j y_j^{(i)} \log(p_j^{(i)}) \quad (7)$$

1(f)

Artificial Neural Networks (ANNs) are described as *shallow* or *deep*, and *wide* or *narrow*. *shallow* or *deep* refers to the number of layers in the network, and *wide* or *narrow* refers to the number of nodes in each layer.

The *credit assignment path*, the CAP, of a neural network is a measure of the number of data transformations that occur as data passes through the network. For *feed-forward* networks the CAP is the number of *hidden layers* plus one.

A *deep* neural network is generally considered to be a network with multiple layers and a CAP > 2.

1(g)

TODO

Question 2

2(a)

TODO

2(b)

TODO

2(c)

TODO

2(d)

TODO

2(e)

TODO

2(f)

TODO

2(g)

TODO

2(h)

TODO

Question 3

3(a)

TODO

3(b)

TODO

3(c)

TODO

3(d)

TODO

3(e)

TODO

3(f)

TODO

Question 4

4(a)

TODO

4(b)

TODO

4(c)

TODO

4(d)

TODO

4(e)

TODO

4(f)

TODO

question_4f

May 7, 2020

```
[ ]: # Fetch batch function:

def fetch_batch(epoch, batch_index, batch_size):

    return X_batch, y_batch

# Set up computational graph:

import tensorflow as tf
reset_graph ()

n_epochs = 1000
learning_rate = 0.01

X = tf.constant(scaled_housing_data_plus_bias, dtype=tf.float32, name="X")
y = tf.constant(housing_data_target, dtype=tf.float32, name="y")

theta = tf.Variable(tf.random_uniform([n + 1, 1], -1.0, 1.0), name="theta")
y_pred = tf.matmul(X, theta, name="predictions")
error = y_pred - y
mse = tf.reduce_mean(tf.square(error), name="mse")
optimizer = tf.train.GradientDescentOptimizer(learning_rate)
training_op = optimizer.minimize(mse)

# Execute:

init = tf.global_variables_initializer()

with
tf.Session() as sess:
    sess.run(init)
    for epoch in range(n_epochs):
        if epoch % 100 == 0:
            print("Epoch", epoch, "MSE=", mse.eval()) sess.run(training_op)
    best_theta = theta.eval()
```

```

1  # Fetch batch function:
2
3  def fetch_batch(epoch, batch_index, batch_size):
4      return X_batch, y_batch
5
6
7  # Set up computational graph:
8
9  import tensorflow as tf
10 reset_graph ()
11
12 n_epochs = 1000
13 learning_rate = 0.01
14
15 X = tf.constant(scaled_housing_data_plus_bias, dtype=tf.float32, name="X")
16 y = tf.constant(housing_data_target, dtype=tf.float32, name="y")
17
18 theta = tf.Variable(tf.random_uniform([n + 1, 1], -1.0, 1.0), name="theta")
19 y_pred = tf.matmul(X, theta, name="predictions")
20 error = y_pred - y
21 mse = tf.reduce_mean(tf.square(error), name="mse")
22 optimizer = tf.train.GradientDescentOptimizer(learning_rate)
23 training_op = optimizer.minimize(mse)
24
25
26 # Execute:
27
28 init = tf.global_variables_initializer()
29
30 with tf.Session() as sess:
31     sess.run(init)
32     for epoch in range(n_epochs):
33         if epoch % 100 == 0:
34             print("Epoch", epoch, "MSE=", mse.eval())
35             sess.run(training_op)
36     best_theta = theta.eval()

```

Listing 1: Question 4f

Question 5

5(a)

TODO

5(b)

TODO

5(c)

TODO

5(d)

TODO

5(e)

TODO

5(f)

TODO