

Experiments Around Training Data Selection Methods for Image Classification

Department of Statistics Data Analysis Qualifying Exam

John Koo

December 16, 2019

Problem Statement and Objective

- ▶ Deep convolutional neural networks make use of the current wealth of curated image datasets and computational resources

Problem Statement and Objective

- ▶ Deep convolutional neural networks make use of the current wealth of curated image datasets and computational resources
- ▶ CNNs may fit poorly when there is insufficient data, and the data collection and labelling process can be expensive

Problem Statement and Objective


- ▶ Deep convolutional neural networks make use of the current wealth of curated image datasets and computational resources
- ▶ CNNs may fit poorly when there is insufficient data, and the data collection and labelling process can be expensive
- ▶ Goal: Determine a training set sampling method to select the best possible images under a fixed training set size

Problem Statement and Objective

- ▶ Deep convolutional neural networks make use of the current wealth of curated image datasets and computational resources
- ▶ CNNs may fit poorly when there is insufficient data, and the data collection and labelling process can be expensive
- ▶ Goal: Determine a training set sampling method to select the best possible images under a fixed training set size
- ▶ Largely based on a paper by Crandall et al. (2018)

Background: “Toddler-Inspired Visual Object Learning”



- ▶ Compared images taken by first-person cameras mounted on toddlers and parents
- ▶ Training VGG16 using toddler data resulted in higher test accuracy than training on parent data (same test set in both cases)



Background: “Toddler-Inspired Visual Object Learning”

- ▶ Distilled the differences in the datasets into two components: object size (how much of the image does the object take up) and image “diversity” (hard to measure)
- ▶ Subsampled the images to obtain training subsets of:
 - ▶ big objects
 - ▶ small objects
 - ▶ diverse images
 - ▶ similar images
 - ▶ random subset
- ▶ Image similarity/distance based on an image embedding (GIST features)
- ▶ Found that when objects are larger or when images are more diverse, test accuracy improves

Background: “Toddler-Inspired Visual Object Learning”



Outline and Summary

1. Replication studies

Outline and Summary



1. Replication studies
2. New methods for training data selection

Outline and Summary

1. Replication studies
2. New methods for training data selection
3. Conclusions and future work



Replication Study: Stanford Dogs dataset

- ▶ 20,000 images of 120 dog breeds
- ▶ 100 images per breed set aside for training
 - ▶ further subdivided into 50-50 big/small or diverse/similar
- ▶ 25 images per breed set aside for validation
- ▶ Remainder for testing



Replication Study: Stanford Dogs dataset

- ▶ Some evidence that object size affects training
- ▶ No significant evidence that image diversity affects training



Replication Study: CIFAR-10

CIFAR-10


- ▶ 32×32 RGB images of 10 different object classes
- ▶ 5,000 training and 1,000 testing images per class
- ▶ No bounding box information
 - ▶ Diversity experiment only
 - ▶ No adjusting field of view

Sampling method

1. Choose training size n
2. Draw $2n$ images using diverse, similar, or random sampling
3. Split the data in half for training and validation
4. Fit VGG16 and assess accuracy on the test set

Replication Study: CIFAR-10

airplane



automobile



bird



cat



deer




dog




frog



horse




ship






truck




Diverse vs. Similar Samples from a Point Cloud




Diverse vs. Similar vs. Random Samples of CIFAR-10 Cats



Replication Study: CIFAR-10



New Approaches to Training Set Selection



Wilson Editing

- ▶ Originally developed for k -nearest neighbors
- ▶ Algorithm
 1. Start with a sample $X_1, \dots, X_n \in \mathbb{R}^p$ and corresponding discrete labels $Y_1, \dots, Y_n \in \{1, \dots, q\}$
 2. For $i = 1, \dots, n$, determine \hat{Y}_i using leave-one-out cross-validated k -nearest neighbors classification
 3. Discard $i \in \{1, \dots, n\}$ where $Y_i \neq \hat{Y}_i$ to construct a reduced, “edited” training set
 4. Use the edited training set to fit a new k -nearest neighbors model
- ▶ Outperforms “unedited” k -nearest neighbors (comparing risk on a held-out test set)


► Algorithm

1. Use Wilson editing (using the GIST embedding) to reduce the training set
2. For a training size n , draw a diverse sample from the edited training set
3. Fit VGG16 on the diverse, edited training subset
4. Assess model performance on the test set


► Idea: Draw a diverse sample while excluding “outliers”

Wilson Editing

Editing done prior to drawing diverse samples




Effect of editing prior to drawing diverse samples



Clustering

Algorithm


1. Use k -means clustering (using the GIST embedding) to split each class into “subclasses”
2. For a training size n , draw a cluster/subclass-stratified sample
3. Fit VGG16 on the stratified training subset
4. Assess model performance on the test set



Summary and Conclusions

- ▶ Diverse sampling outperforms similar sampling but fails to improve upon uniform random sampling
- ▶ Removing outlier images prior to drawing a diverse sample seems to improve model performance
- ▶ Cluster-stratified sampling resulted in equivalent model performance as uniform random sampling
- ▶ Future work
 - ▶ More sophisticated clustering methods
 - ▶ Active learning based approaches

Comparison of sampling methods



Additional Slides

GIST Embedding

Transfer Learning