


Popularity Adjusted Block Models are Generalized Random Dot Product Graphs

JSM Speed Presentation

August 2022



John Koo,
PhD Student in
Statistical Science,
Indiana University




Minh Tang,
Assistant Professor of
Statistics,
NC State University



Michael W. Trosset,
Professor of Statistics,
Indiana University

Community Detection for Networks



Def Popularity Adjusted Block Model (Sengupta and Chen, 2017):


Let each vertex $i \in [n]$ have K popularity parameters

$\lambda_{i1}, \dots, \lambda_{iK} \in [0, 1]$.


Then $A \sim \text{BernoulliGraph}(P)$ is a PABM if each $P_{ij} = \lambda_{iz_j} \lambda_{jz_i}$

Connecting Block Models to the GRDPG


SBM




Point Masses




DCBM




Rays



PABM



Subspaces (Projected)



- K-means clustering
- Gaussian mixture models
- K-means with cosine similarity
- GMM on angles
- ???

Orthogonal Spectral Clustering

Theorem (KTT): If $P = V\Lambda V^\top$ and $B = nVV^\top$, then $B_{ij} = 0$ if $z_i \neq z_j$.


Algorithm: Orthogonal Spectral Clustering:

1. Let V be the eigenvectors of A corresponding to the $K(K+1)/2$ most positive and $K(K-1)/2$ most negative eigenvalues.
2. Compute $B = |nVV^\top|$ applying $|\cdot|$ entry-wise.
3. Construct graph G using B as its similarity matrix.
4. Partition G into K disconnected subgraphs.

Theorem (KTT): \forall pairs (i, j) belonging to different communities, $\max_{i,j} B_{ij} = O_P\left(\frac{(\log n)^c}{\sqrt{n\rho_n}}\right)$.

Corollary: OSC results in zero clustering error as $n \rightarrow \infty$, with probability 1.

Simulation Study



Thank you

Published in *Journal of Computational and Graphical Statistics*

arXiv preprint: <https://arxiv.org/abs/2109.04010>

GitHub repository: <https://github.com/johneverettkoo/pabm-grdpg>

R package: <https://github.com/johneverettkoo/osc>