Natural-Language Routing on an Open Stack

John Gunnar Carlsson Andreas Royset

FOSS4G 2026
Wednesday, November 4

Maps expose toggles, but requests are more fluid

- What navigation products accept:
  - global switches: avoid highways, tolls, ferries
  - search ranked by distance from the user ("coffee near me")
- What people actually ask for:
  - "gas on the right, so I don't turn across traffic"
  - "coffee about an hour from now"
  - "stay off 880"
  - "between the two of us, who picks up our kid?"
- Each is a constraint expressible in plain language and computable with open tools

Operations research in one slide


- A model: decision variables, constraints, an objective

$$\min_{x \in X} f(x) \text{ subject to } g_i(x) \leq 0$$

- The modelling is the hard part; solvers are interchangeable behind it
- Families: linear programs (LP), mixed-integer programs (MIP), constraint programming (CP), local search
- Classic uses: airline crews, supply chains, scheduling, network design, and vehicle routing
- Most routing problems are NP-hard; practical instances are solved by good heuristics with a time limit, not by proofs of optimality

Vehicle routing: a family of problems

- TSP: one tour through all nodes, minimum length
- VRP: several vehicles share the nodes
- VRPTW: each node has an arrival window $[a_i, b_i]$
- Pickup and delivery: pairs (p, d), same vehicle, p before d
- Generalized TSP: nodes come in clusters; visit exactly one per cluster
- Prize-collecting: nodes are optional; skipping one costs a penalty
- All of these are one solver configured differently



visit exactly one node per cluster;
the solver picks the member and the order together

Google OR-Tools

- Open source (Apache 2.0), maintained by Google
- CP-SAT: constraint programming over a SAT core; many MiniZinc Challenge gold medals
- Linear and mixed-integer: one interface over GLOP, PDLP, SCIP, HiGHS, and commercial solvers
- Graph algorithms: shortest paths, max flow, min-cost flow, assignment
- Routing: a vehicle-routing library on top of a CP solver, with local search
- We use the routing library; the same install would also schedule, pack and assign

The routing library, in OR terms

Concept	In the model	OR-Tools name
Arc cost	t_{ij}, driving times from Valhalla	transit callback
Time along a route	$T_j \geq T_i + s_i + t_{ij}$ on arcs used	time dimension
Time window	$a_i \leq T_i \leq b_i$	bounds on T_i
One of a cluster	$\sum_{i \in G_k} y_i = 1$	disjunction
Optional node	skip i at penalty π_i	disjunction, penalty π_i
Pickup before drop	same vehicle, $T_p \leq T_d$	pickup–delivery pair
Makespan	$\max_v T_v^{\text{end}} - \min_v T_v^{\text{start}}$	span cost

- Search: a construction heuristic, then a metaheuristic (guided local search, simulated annealing, tabu) until a time limit
- No lower bound: the answer is a good solution, not a certified optimum


Approach: the model fills in a form

- A language model reads the request and fills in a fixed form
- The fields and their allowed values are set in advance; the model cannot answer outside them
- Ordinary code turns the form into an optimization model and solves it
- The model never routes or optimizes; it sees no coordinates and no store names
- The start is the phone's GPS position
- Every result is re-checked against the final route

"I need a pharmacy before it closes at six, groceries, and gas, in any order, and I have to be home by 6:15."

Field	Value
start	the phone's position
end	home
errand	pharmacy, closes 18:00
errand	groceries
errand	gas
order	any
arrive by	18:15

How one request runs



One request, end to end

"I need a pharmacy before it closes at six, groceries, and gas, in any order, and I have to be home by 6:15." (5:15 pm, Great Mall)

	Stage	Done by	Output	Time
1	Read the request	language model	it is a trip: plan it	
2	Fill in the form	language model	3 errands, 2 deadlines	2.8 s
3	Choose the method	fixed rules	errands, any order $\Rightarrow$ GTSP	
4	Places	saved places	home = Milpitas Library	
5	Direct route	Valhalla	7.2 min	
6	Candidates	Overture places	7 pharmacies, 27 groceries, 15 gas	
7	Screen	detour of each	best 6 per errand	
8	Travel times	Valhalla	20×20 matrix	0.34 s
9	Solve	OR-Tools	Nilgiris, Walgreens, 76; 10.4 min	1.0 s
10	Check	Valhalla map-match	5 of 5 checks pass	
			optimization total 1.4 s; request total	6.9 s

Steps 1–2: the two model calls

- The agent chooses a tool: place search, or drive time
- Its prompt sends errands and task splits to `plan_trip` unmodified, so the optimizer chooses the stores
- Extraction fills a fixed JSON schema, enforced by the API (`response_format: json_schema`; Ollama: `format`)
- Then a sanitizer: enums checked, numbers clamped, missing fields defaulted
- No coordinates or store names in the form, only words and times

```
// 1. agent -> tool call
{"tool": "plan_trip", "args": {"request":
  "pharmacy, groceries, and gas, in any
   order, pharmacy must be before 6 PM,
   home by 6:15 PM"}}

// 2. extraction -> the form (trimmed)
{"origin": null,  "destination": "home",
 "stopOrder": "any", "arriveBy": "18:15",
 "stops": [
   {"kind": "errand", "what": "pharmacy",
    "closesAt": "18:00", "brands": []},
   {"kind": "errand", "what": "groceries"},
   {"kind": "errand", "what": "gas"}],
 "team": null, "meetup": null,
 "custom": null}
```

Step 3: the form determines the problem

- The model never names an algorithm; it answers narrow questions about the text ("did they give an order?")
- Fixed rules read the form, top to bottom
- Same form, same method: a wrong method traces back to one wrong field
- Here: errands, any order $\Rightarrow$ GTSP with time windows

The form has	Problem	Solved by
a friend to meet	choose a meeting point	enumeration
tasks for two drivers	VRP, pickup–delivery	OR-Tools
a rule with no field	model-written filter	then as below
no errands	shortest path	Valhalla
errands, order given	layered shortest path	dynamic program
errands, any order	GTSP, time windows	OR-Tools

What each field becomes

Field of the form	In the optimization model
errand (a kind, or chains)	cluster G_k of candidates from Overture; visit exactly one
named place	one node, geocoded
closes at, arrive by	time window: $T_i \leq b_i$
about N minutes in	candidates near where the direct route is at time N
on the right	within 80 m, right of travel; re-pick on arrival
maximum detour D	candidates only with $\delta(p) \leq D$
avoid a road or area	edges removed; re-solve until no avoided edge is used
pick someone up	pickup–delivery pair: same vehicle, $T_p \leq T_d$
two drivers	second vehicle; objective adds the makespan
anything else	a model-written filter and check, run in isolation

New combinations need no new code; a new kind of constraint needs a field and its translation.

Steps 4–8: from words to a 20-node instance

- Candidates: Overture places within 2 km of the direct route
- Screen by detour; keep the best 6

$$\delta(p) = t(o, p) + t(p, d) - t(o, d)$$

- Instance: start, home, 3×6 candidates $= 20$ nodes
- One 20×20 travel-time matrix from Valhalla (0.34 s; typical speeds in this run)
- Choices: 6^3 stores $\times 3!$ orders $= 1296$ tours

Errand	Found	Kept	Best two, δ (min)
pharmacy	7	6	Walgreens 2.8, CVS 6.5
groceries	27	6	New India Bazar 0.8, Nilgiris 1.2
gas	15	6	76 1.6, City Gas 2.5

Screening is per errand; the solver then sees the interactions: the chosen grocery is not the one with the smallest detour on its own

Steps 9–10: solve, then check independently

- Model: 1 vehicle, start and end fixed, 3 clusters of 6, pharmacy by 6:00, home by 6:15
- Search: cheapest-arc construction, guided local search, 1 s limit
- Result: 10.4 min (direct: 7.2)
- Re-costed from the matrix; the solver's objective is not trusted
- Check on a fresh map-match of the final route: each stop within 20 m of it, both deadlines met

Stop	Arrive	Limit
Great Mall	5:15	
Nilgiris (groceries)	5:21	
Walgreens (pharmacy)	5:22	6:00
76 (gas)	5:23	
home	5:25	6:15

Tools

- Valhalla (OpenStreetMap road graph): routes, travel-time matrices, map-matching, road exclusions, time-dependent travel times
- Overture Maps places (273k in the Bay Area), queried with DuckDB
- Photon and Nominatim: OSM geocoding, self-hosted
- OR-Tools routing: disjunctions, time windows, pickup and delivery
- Language model: any hosted model with a standard API, or one run locally with Ollama
- Demos use Reflection AI's Beam-1.0 (501B-A23B), chosen because its weights are open; 3–14 s per request
- Caltrans PeMS loop detectors: hour-of-week speeds loaded as Valhalla predicted traffic
- Ferrostar: turn-by-turn navigation in the browser
- The local model works too: all five demos run on qwen3.6 35B-A3B through Ollama on one laptop with a 12 GB GPU (18–61 s each)

Five requests from the Great Mall, Milpitas

- Start: a GPS fix posted by the phone; no request states where the driver is
- Requests, and what each exercises:
  1. Gas on the right, on the way to Levi's Stadium
     DuckDB on Overture; arrival-side geometry
  2. Coffee about an hour into the drive to Sacramento
     maneuver times; Valhalla matrix
  3. Oakland airport, but stay off 880
     map-match, exclude, re-route
  4. Pharmacy before 6, groceries, gas, home by 6:15
     OR-Tools: disjunctions and time windows
  5. Split the afternoon's tasks between two drivers
     OR-Tools: two vehicles, pickup and delivery
- All screenshots come from the live path (model in the loop), via `scripts/capture_talk.py`


1. Gas on the right

Prompt

"Take me to Levi's Stadium, and get gas on the way at a station on the right so I don't have to turn across traffic."

Result

The route stops at a 76 station on West Calaveras Boulevard. The station is on the right when the driver arrives, and the stop adds about 30 seconds.




2. Coffee during the drive

Prompt

"I'm driving to the Sheraton in downtown Sacramento, and I'm going to want coffee about an hour from now. Keep the detour small."

Result

There was no coffee shop near the exact one-hour point, so the app widened the search slightly and said so. It chose a Peet's in Pleasant Hill, reached about 50 minutes into the trip, with a detour of about 20 seconds.




3. A route that avoids I-880

Prompt

"Get me to Oakland airport, but stay off 880."

Result

The route takes I-680 and I-580 instead of I-880. It takes 63 minutes, about 20 minutes longer than the usual route.




4. Three errands with deadlines

Prompt

"It's 5:15 pm. I need a pharmacy before it closes at six, groceries, and gas, in any order, and I have to be home by 6:15."

Result

The app chooses the stores and their order. It reaches Walgreens at 5:23, before the pharmacy closes at 6:00, and gets home at 5:25, before the 6:15 deadline.




5. Splitting tasks between two drivers

Prompt

"It's 3:00 pm. Another driver is at Fremont BART. Between us, someone needs to pick up a friend at Stratford School and get the friend home by 3:30. We also need groceries, which will take about 30 minutes, and a stop at CVS. Then we both go home. Who should do what?"


Result

Driver 1 shops at Trader Joe's and gets home at 3:40. Driver 2 picks up the friend, gets home at 3:29, then stops at CVS and is home again at 3:38. If either driver did everything alone, the work would finish at 3:58 or 4:17.



Sending a driver their part

- "Send to Wife": a link with an unguessable token, valid 30 minutes; no account, no app
- The page shows her part of the plan and can share her location back
- "Start turn-by-turn": Ferrostar in her browser, on the plan's exact route request (exclusions kept on reroute)
- On expiry the position is deleted and the link returns 410
- Limits: browsers share location only while the page is open; Google Maps location sharing has no API



Every route is checked independently of the planner

- The final line is map-matched again (`/trace_attributes`); checks read those edges
- Checked: stops reached and in order; roads and areas avoided; detour bounds; side of road on arrival; "about *N* min in"; closing times; deadline; pickup before drop in the same car
- A failed check is shown with the measured value; the route is still drawn
- Retry loops fix loud failures
- Silent failures seen in practice: an exclusion polygon rejected by the engine, a stop skipped by the solver, a deadline missed by a relaxed solve

Data: the verifier cannot catch a wrong category


- Overture places with confident, wrong categories:
  - Oportun (≈20 sites): pharmacy; a lender (confidence 0.92–0.99)
  - Evernote: gas station; Biocardia: pharmacy
  - Hills Bros. Coffee Plant: coffee shop; a historic building
  - Gano Excel (Fairfield): coffee shop; a coffee company's business-park unit
- The route does stop where the data says a pharmacy is: geometric checks pass
- Mitigation: a small, visible deny list in code; better: report upstream
- Geocoding ranks names, not meaning: "Oakland airport" → Oakland Airport Executive Hotel, until the OSM tag had to match the named kind

Engines: silent failures

- Valhalla matrices: ≈2% of places null in their entire row and column (8 of 400 shops); all snapped to a parking aisle or service road; `/route` reaches them. Fix: re-snap those points to the street
- Default `max_exclude_polygons_length`: 10 km total perimeter; over it the request is rejected, and the easy fallback silently drops the constraint
- Ollama: tool-call arguments must be objects, not JSON strings; every turn after a tool call failed
- Ollama: two context sizes (8k, 16k) load two copies of a 35B model; on a 12 GB GPU the second load crashed

Impossible requests: say no

- “Home by five” at 4:55 with three errands: OR-Tools relaxes the deadline; the verifier fails it: arrive 5:05
- “A car wash under one minute out of the way”: the closest adds 3.2 min
- Never a plausible route that quietly violates the request



What constraints cannot express yet

- "Downtown": no usable boundary in OSM; a gazetteer circle
- "The Bay Bridge": the name is in `bridge:name`, absent from the routing graph; matched by footprint for a short list
- "Before it closes": no opening hours in the open places data; the driver must state the time
- A named place ("Tartine") is resolved to one point before solving; only categories and chains ("a Safeway") reach the solver as alternatives
- A verifier that shares the planner's definitions shares its mistakes: checks need independent data, not only independent code

Summary

1. Give the language model one job: fill a typed schema. Open engines do the geometry and the optimization.
2. Constraints are predicates over graph edges, not road names; iterate until the route satisfies them.
3. Verify the final route from fresh data, and report failures with the measured value.

Thank you

- Code: github.com/johngcarlsson-usc/TurnByTurn
- Built on Valhalla, OpenStreetMap, Overture Maps, DuckDB, OR-Tools, Photon, Nominatim, Caltrans PeMS, Ferrostar, MapLibre, OpenFreeMap, Open-Meteo, Ollama