

Migration — velbaz7-1022 → managed Runnable app (velbaz7)

Second port. `https://github.com/johnghost-j/velbaz7-1022.git` (template 0.7.0) was copied onto a freshly provisioned managed app scaffold (template **0.8.0**). Nothing from the repo was dropped: 524 repo files → 524 identical files in the app, plus the provisioned `.env`.

What was verified (2026-09-11)

Step	Result
File-level completeness	524/524 repo files present, byte-identical
Protected template files	13/13 identical between 0.7.0 and 0.8.0 — only <code>__ports.cjs</code> changed (now reads <code>.runable/ports.json</code>), kept from the new scaffold
Dependency install	ok (<code>bun install</code> , isolated per-package <code>node_modules</code>)
Schema push to Turso	ok (<code>db:push</code> → "Changes applied")
Full build	ok (<code>bun run build</code> → <code>tsc --noEmit + vite build</code> , 2/2 packages, 1m41s)
Dev server	ok on port 4200
Routes <code>/login</code> <code>/dashboard</code> <code>/chat</code> <code>/editor</code> <code>/plans</code>	all HTTP 200, rendered and screenshotted
<code>/api/health</code>	HTTP 200 <code>{"status":"ok"}</code>
Auth + DB write	<code>POST /api/auth/register</code> then <code>/api/auth/login</code> → 200, user created with 5000-credit signup bonus (test user deleted afterwards)
AI gateway	ok (<code>bun gw-check.ts</code> → "GATEWAY OK")
Lint integrity	0 template-integrity / protected-file / asset-location violations

Managed infra provisioned (live in root `.env`)

New values, provisioned for this app — not the previous sandbox's keys:

`DATABASE_URL` , `DATABASE_AUTH_TOKEN` (Turso), `S3_*` (Tigris storage), `AI_GATEWAY_BASE_URL` ,
`AI_GATEWAY_API_KEY` , `BETTER_AUTH_SECRET` , `AUTUMN_SECRET_KEY` , `APPLICATION_ID` , `WEBSITE_URL` ,
`VITE_RUNABLE_AUTH_ISSUER` , `VITE_APPLICATION_ID` , `RUNABLE_URL` .

Ports are fixed in `.runable/ports.json` (web 4200, mobile 4300, desktop 4400).

Optional integration keys NOT set

The code reads these; the app boots and runs without them. Every feature degrades honestly — it announces the missing key instead of faking a result — and stays inert until the key is supplied.

Two ways to supply a key. Keys marked **Admin Panel** are in `KNOWN_SECRETS` (`packages/web/src/api/secret-store.ts`): they are entered at runtime from Admin Panel → API Keys, stored AES-encrypted in the DB, and no restart or `.env` edit is needed. Keys marked `.env` are read straight from `process.env` and require an `.env` entry plus a restart.

Payments — Stripe (`api/billing.ts`)

Key	Where	Effect if missing
<code>STRIPE_SECRET_KEY</code>	Admin Panel	No real checkout. Plans page and credit packs stay visible but report that payment is unconfigured.
<code>STRIPE_WEBHOOK_SECRET</code>	Admin Panel	Optional even with Stripe live: <code>/api/billing/webhook</code> skips signature verification, and the return-to-site confirmation path still credits the account.

Custom domains (`api/domains.ts`)

Works with **zero keys**: real DNS verification (DNS-over-HTTPS, Cloudflare + Google fallback), domain uniqueness, and serving the published site on the customer's domain over **HTTP**.

Key	Where	Effect if missing
CLOUDFLARE_API_TOKEN	Admin Panel	No automatic HTTPS/CDN on customer domains (Cloudflare for SaaS). Needs the "SSL and Certificates: Edit" permission. Domain still connects, verifies and serves over HTTP; the UI says so rather than advertising a nonexistent certificate (<code>ssl: "unmanaged"</code>).
CLOUDFLARE_ZONE_ID	Admin Panel	Same. Required together with the token — the zone that hosts the custom hostnames.
VELBAZ_DOMAIN_TARGET	Admin Panel	Optional override. CNAME target announced to customers. Default <code>cname.velbaz.site</code> .
VELBAZ_ROOT_DOMAIN	Admin Panel	Optional override. Hosting root domain used for <code>*.velbaz.site</code> subdomains. Default <code>velbaz.site</code> .
VELBAZ_DEPLOY_TOKEN	Admin Panel	Optional external hosting provider token. Without it the site is still published on Velbaz's own hosting (<code>/s/:subdomain</code>).

A key present but **invalid** is distinguished from a key absent: the Cloudflare call is really made, its rejection is surfaced, and the state becomes `ssl: "failed"` (vs `"unmanaged"`).

Domain purchase — registrar Namecheap (`api/index.ts`)

Availability search (RDAP, public) works without any key. The 4 below are required **together**; without them the purchase endpoint answers `501` and names the missing keys.

Key	Where
NAMECHEAP_API_USER	Admin Panel
NAMECHEAP_API_KEY	Admin Panel
NAMECHEAP_USERNAME	Admin Panel
NAMECHEAP_CLIENT_IP	Admin Panel — the server IP must be whitelisted in Namecheap's API settings

Error monitoring & self-healing — Sentry (`api/selfheal/sentry.ts`)

Key	Where	Effect if missing
<code>SENTRY_DSN</code>	Admin Panel	Errors are not sent to Sentry. Self-healing falls back to the internal <code>error_logs</code> stream.
<code>SENTRY_AUTH_TOKEN</code>	Admin Panel	Self-healing cannot READ issues back from the Sentry API.
<code>SENTRY_ORG</code>	Admin Panel	Required with the auth token (org slug).
<code>SENTRY_PROJECT</code>	Admin Panel	Required with the auth token (project slug).
<code>SENTRY_API_URL</code>	Admin Panel	Optional. Only for self-hosted Sentry; defaults to <code>sentry.io</code> .

Note: these five are the only optional keys currently also present (empty) in the root `.env`.

Email (`api/email.ts`)

Key	Where	Effect if missing
<code>RESEND_API_KEY</code>	Admin Panel	No transactional email is sent.
<code>RESEND_FROM</code>	Admin Panel	Default "from" address, e.g. Velbaz <no-reply@ton-domaine.com> .
<code>EMAIL_WEBHOOK_SECRET</code>	Admin Panel	Incoming email webhooks are not signature-verified.

Media generation — Higgsfield (`api/higgsfield.ts`)

Key	Where	Effect if missing
<code>HF_API_KEY</code> / <code>HF_API_SECRET</code>	Admin Panel	Image/video generation via Higgsfield is unavailable.
<code>HF_CREDENTIALS</code>	Admin Panel	Alternative combined form (<code>key:secret</code>).
<code>HIGGSFIELD_KEY_ID</code> / <code>HIGGSFIELD_KEY_SECRET</code> / <code>HF_KEY</code> / <code>HF_SECRET</code>	.env	Legacy env fallbacks, read only if the Admin Panel values are absent.
<code>HF_BASE_URL</code>	.env	Optional API base override.

GitHub export (`api/github.ts`)

Key	Where	Effect if missing
<code>GITHUB_TOKEN</code>	Admin Panel	Projects cannot be exported to GitHub.
<code>GITHUB_OWNER</code>	Admin Panel	Target account/organization for the export.

Builder & AI extras

Key	Where	Effect if missing
TWENTY_FIRST_API_KEY	.env	No 21st.dev premium React components; the builder falls back to its own generated components.
FIRECRAWL_API_KEY	.env	Web scraping uses the local headless browser instead of Firecrawl.
OPENROUTER_API_KEY	.env	OpenRouter routing unavailable (an <code>openrouter</code> provider key in the secret store also satisfies this).
AI_MODEL , IMAGE_MODEL , UNCENSORED_MODEL , TIER_MODEL_LITE / _PRO / _MAX , BUILDER_REPAIR_MODEL , SELFHEAL_MODEL , COMMS_REASONING_MODEL	.env	Model overrides. Built-in defaults are used.
AI_CREDITS_PER_USD	.env	Credit-to-USD conversion rate. Default applies.
SELFHEAL_DISABLED	.env	Set to disable automatic self-healing.

Social publishing (`api/social/`)

OAuth client pairs, all `.env`. Each platform's publishing stays disabled until its pair is set:

`DISCORD_CLIENT_ID / DISCORD_CLIENT_SECRET / DISCORD_BOT_TOKEN` ,
`INSTAGRAM_CLIENT_ID / INSTAGRAM_CLIENT_SECRET` , `REDDIT_CLIENT_ID / REDDIT_CLIENT_SECRET` ,
`TWITTER_CLIENT_ID / TWITTER_CLIENT_SECRET` , plus `OAuth_REDIRECT_BASE` , `OAuth_STATE_SECRET`
and `X_LIVE_ENABLED` .

Platform / operational

Key	Where	Effect if missing
SECRET_STORE_KEY	.env	The API-key vault falls back to BETTER_AUTH_SECRET for encryption. Set it explicitly in production.
ADMIN_EMAILS	.env	Falls back to the built-in default admin address — set it to control who reaches the admin pages.
BETA_PUBLIC_CODE , BETA_ADMIN_CODE , BETA_MAX_TESTERS	.env	Beta access codes and tester cap; defaults apply (VELBAZ-BETA).
PUBLIC_BASE_URL / APP_BASE_URL / VELBAZ_URL / VELBAZ_API_URL	.env	Absolute-URL generation falls back to WEBSITE_URL .
VELBAZ_APPS_ROOT , CHIMERA_ASSETS_DIR , MAX_AUTO_RELAUNCH_PER_BOOT , DISABLE_SERVER_JSX	.env	Builder runtime paths and limits; defaults apply.

Known inherited debt

`bun run lint` reports 595 errors, all pre-existing in the copied source (579 on 0.7.0; the extra 16 come from newer rules in 0.8.0). Breakdown: `no-unused-vars` (156), `react-hooks/exhaustive-deps` (43), `max-lines` (5), misc unicorn/eslint. Build and runtime are unaffected.

Commands

```
bun run dev      # web on 4200
bun run build    # build all packages
bun run start    # pm2 production server
cd packages/web && bun run db:push
```