

## Table of Contents

1. Testing your query .....	1
1.1. Gotchas for testing your query .....	1
1.1. Parent and child rows.....	2
2. Resetting the tables .....	2

I showed you the syntax of the insert statement in unit 01. What I want to discuss here is something of the logic for inserting rows into a table. Your first question might be why would you want to do that since I provide the inserts for all of the demo and assignment tables.

## 1. Testing your query

One time that you might want to do inserts is to test your query. Suppose I ask you to write a query that finds all of the dogs in the animals table that have the name 'Buddy'. We have not discussed all of the following row filters, but you should be able to see that this query does that task.

```
select *
from a_vets.vt_animals
where an_type = 'dog' and an_name = 'Buddy';
```

But if you run this query, the result is empty; we do not currently have any dogs named Buddy. But that does not give you any reassurance that the query is correct. There are a lot of queries that you could write that return an empty result.

So you might want to add a row to the animals table that adds a dog named Buddy. Following the model in the inserts script, you might try the following:

```
insert into a_vets.vt_animals ( an_id, cl_id, an_name, an_type, an_dob)
values (15165, 42, 'Buddy', 'dog', '2007-07-07');
```

The syntax is valid, but that insert won't run. If you review the document on the vets database you can detect two errors in the insert.

- 1) The column `an_id` is the primary key for this table and we already have an animal row using the `an_id` value 15165. So we would need to use a value for `an_id` that does not match any of our current rows.
- 2) The column `cl_id` is the client id and it is the foreign key to the clients table, so that value has to match a client we have in the clients table. We do not have a client with an id of 42.

We could do the following insert:

```
insert into a_vets.vt_animals ( an_id, cl_id, an_name, an_type, an_dob)
values (15, 5689, 'Buddy', 'dog', '2007-07-07');
```

Now if we run the first query again- to find dogs named Buddy, we get our new row in the result.

### 1.1. Gotchas for testing your query

One thing that can get confusing is that you cannot prove your query is correct by examining the result. For example, I could write the following query- which returns the same result but which is not a valid query to find dogs named Buddy.

```
select *
from a_vets.vt_animals
where an_dob = '2007-07-07';
```


You can demonstrate that your query is wrong if it returns an incorrect result- if your query returns cats then your query is incorrect. But you cannot prove your query is correct by examining the result.

But it can help to add test rows.

## 1.1. Parent and child rows

The following is a diagram of some of the tables in the vets databases that shows the tables and their PK and FK columns. Note that the tables for clients, animal types and services have no FK columns. You can add columns to these tables without worrying about FK- without worrying about the parent table rows.

But if you add a row to the animals table, you need to worry about the `an_type` (it needs to match a row in the `animal_types` table) and about the `cl_id` (which needs to match a row in the `clients` table).



Suppose you want to insert a row in the `vt_exam_details` table; in that case you need to have FK matches for the other 5 tables shown.

The `srv_id` needs to match a `srv_id` in the `vt_services` table; the `ex_id` needs to match a row in the `vt_exam_headers` table.

The `an_id` value in the `vt_exam_headers` table needs to match an `an_id` in the `vt_animals` table.

The `cl_id` value in the `vt_animals` table needs to match an `cl_id` in the `vt_clients` table. The `an_type` value in the `animals` table needs to match an `an_type` in the `vt_animal_types` table.

You could either build on the existing rows to add additional rows to the tables, starting with the insert for the parent before the insert for the child.

## 2. Resetting the tables

When you run the assignment script to turn in, you need to use the original inserts that I provided- this should not include any test data that you inserted, You did the test inserts to test your queries- but not for grading.

If you did a simple one row add- such as in the start of the discussion, you could do a simple delete based on the pk.

```
delete from a_vets.vt_animals where an_id = 15;
```

But if you have added several rows, it can be quicker to simply rerun the inserts script before you run the assignment script for grading.