

Table of Contents

1. Row filters	1
2. Testing for nulls	2
3. The IN list test	3
3.1. Simple In lists.....	3
3.2. In lists that contain nulls	5
3.3. In lists that contain row values	5
3.4. Testing a literal against an in list	6
4. The BETWEEN test.....	7
4.1. Gotchas	8

1. Row filters

Most of our queries so far have returned all of the data from the table in the From clause. We are working with very small tables. Imagine the output if we had thousands of rows in our tables. We seldom want to see all of the data in a table. Rather we want to see only a subset of the data- a subset that matches some search condition. If you are using the CCSF WebStars system to see your current schedule- you do not want to see everyone's schedule- just yours.

To filter the output add a WHERE clause to the SQL statement after the From clause. The Where clause specifies which rows should be returned. The Where clause contains a logical expression (a predicate or test) that is applied to each row in the table. If the logical expression evaluates to true for a row from the table (if that row passes the test), that row is returned in the result. The row is not returned if the predicate evaluates as False or as Unknown. . We will cover a variety of comparison operators and conditional expressions in this unit and in the following units. We will also investigate the concept of Unknown.

Our query model is now

```
Select col_expressions
From table_expression
WHERE predicate
Order By sort_keys;
```

In this unit, we will look at several filters: we will discuss more filters soon.

- the Is Null and Is Not Null filters
- the In list filter
- the Between filter

A few general rules for writing filters

- You cannot test a column alias in a Where clause; you need to test using the column name.
- Character literals are enclosed in single quotes: 'CA', 'Anderson'
- In tests against character literals, leading blanks are significant. The value ' CA ' does not match the value 'CA '. Trailing blanks are not significant.
- Numbers are not enclosed in quotes; do not include punctuation such as commas or dollar signs when you write numeric literals
- Dates are more complex; for now write date literals in the standard default format: '2008-04-01'. Note that this is a string literal; MySQL will cast it to a date for date testing.

For these queries the table expressions will follow the format of databaseName.tableName such as

```
from a_oe.order_headers
```

This means you can run these queries from within any of your databases.

2. Testing for nulls

You may want to write your queries to skip any rows where certain column values are null. The way to test for this is to add a Where clause after the From clause that filters for the nulls.

Testing for missing values requires the use of the IS NULL operator. Think of IS NULL and IS NOT NULL as single operators. You use the same operator IS NULL for any data type that you are testing.

If you try to test using the syntax = NULL, you will get no rows returned. This is not flagged as an error.

Demo 01: Test for empty attributes by using the test IS NULL. You use the same test for attributes of any data type. This tests for a null shipping_mode which is a char(6) attribute.

```
Select ord_id, ord_date, sales_rep_id, shipping_mode
From a_oe.order_headers
WHERE shipping_mode IS NULL;
```

ord_id	ord_date	sales_rep_id	shipping_mode
116	2013-11-12 00:00:00	155	NULL
117	2013-11-28 00:00:00	150	NULL
118	2013-11-28 00:00:00	150	NULL
119	2013-11-28 00:00:00	155	NULL
120	2014-01-02 00:00:00	NULL	NULL
121	2014-01-03 00:00:00	NULL	NULL
550	2014-08-02 00:00:00	NULL	NULL
551	2014-08-03 00:00:00	NULL	NULL

8 rows in set (0.00 sec)

Demo 02: Test for empty attributes by using the test IS NULL. This is testing an integer column.

```
Select ord_id, ord_date, sales_rep_id
From a_oe.order_headers
WHERE sales_rep_id IS NULL;
```

ord_id	ord_date	sales_rep_id
115	2013-11-08 00:00:00	NULL
120	2014-01-02 00:00:00	NULL
121	2014-01-03 00:00:00	NULL
225	2013-08-09 00:00:00	NULL
227	2013-08-01 00:00:00	NULL
525	2014-05-09 00:00:00	NULL
527	2014-05-01 00:00:00	NULL
550	2014-08-02 00:00:00	NULL
551	2014-08-03 00:00:00	NULL

9 rows in set (0.00 sec)

Demo 03: We can use IS NOT NULL to find rows that have a data value.

```
Select ord_id, ord_date, shipping_mode
From a_oe.order_headers
WHERE shipping_mode IS NOT NULL
Order by ord_date
Limit 5;
```

ord_id	ord_date	shipping_mode
227	2013-08-01 00:00:00	USPS1
223	2013-08-05 00:00:00	USPS1

```

| 224 | 2013-08-07 00:00:00 | FEDEX1 |
| 218 | 2013-08-08 00:00:00 | USPS1 |
| 225 | 2013-08-09 00:00:00 | FEDEX1 |
+-----+-----+-----+
5 rows in set (0.00 sec)

```

Demo 04: Note what happens if you use the test = null instead of Is null

```

Select ord_id, ord_date, shipping_mode
From a_oe.order_headers
WHERE shipping_mode = NULL
;

```

Empty set

The null indicator does not equal any value in the table. So testing with = Null or <> Null is not a true test and that filter will return no rows. The use of Nulls in tables is important but null testing is not always obvious.

3. The IN list test

Suppose we want to display all customers named Morris or Morse or Morise. This is testing against a specific set of values and we can use an IN list for this. The list of values is enclosed in parentheses and the values are separated by commas.

3.1. Simple In lists

Demo 05: Using the IN list for text values. Each text value is enclosed in quotes .

```

Select cust_id
, cust_name_last
, cust_name_first
From a_oe.customers
Where cust_name_last in( 'Morise', 'Morris', 'Morse' )
;
+-----+-----+-----+
| cust_id | cust_name_last | cust_name_first |
+-----+-----+-----+
| 401250 | Morse          | Samuel          |
| 402100 | Morise         | William         |
| 404950 | Morris        | William         |
| 409010 | Morris        | William         |
+-----+-----+-----+
4 rows in set (0.00 sec)

```

Demo 06: Using the IN list for numeric values. It is not an error to have a value in the list which does not match any rows in the table. . It is not an error to have a in the list appear more than once.

```

Select ord_id
, ord_date
, cust_id
From a_oe.order_headers
WHERE ord_id IN (101, 107, 95, 125)
;
+-----+-----+-----+
| ord_id | ord_date          | cust_id |
+-----+-----+-----+
| 107    | 2013-10-02 00:00:00 | 403050 |
| 125    | 2013-12-09 00:00:00 | 409160 |
+-----+-----+-----+

```

Demo 07: You can use the NOT IN test to exclude specified data values.

```
Select prod_id, prod_name, catg_id
From a_prd.products
WHERE catg_id NOT IN ('HW', 'PET');
+-----+-----+-----+
| prod_id | prod_name      | catg_id |
+-----+-----+-----+
| 1010    | Weights        | SPG     |
| 1020    | Dartboard      | SPG     |
. . .    rows omitted
| 1130    | Mini Freezer   | APL     |
| 4569    | Mini Dryer     | APL     |
| 5000    | Fingerling Potatoes | GFD     |
| 5001    | Ginger Preserve | GFD     |
| 5002    | Ball-Peen Hammer | HD      |
| 5004    | Dead Blow hammer | HD      |
| 5005    | Shingler Hammer | HD      |
| 5008    | Claw Framing   | HD      |
+-----+-----+-----+
```

Demo 08: You can use a list that contains only one item.

```
Select job_id, job_title, max_salary
From a_emp.jobs
WHERE max_salary IN (120000 );
+-----+-----+-----+
| job_id | job_title      | max_salary |
+-----+-----+-----+
| 16     | Programmer     | 120000.00  |
+-----+-----+-----+
1 row in set (0.01 sec)
```

Demo 09: You can use a NOT IN list that contains only one item.

```
Select job_id, job_title, max_salary
From a_emp.jobs
WHERE max_salary NOT IN (120000 );
+-----+-----+-----+
| job_id | job_title      | max_salary |
+-----+-----+-----+
| 1      | President      | 100000.00  |
| 2      | Marketing      | 75000.00   |
| 4      | Sales Manager  | 60000.00   |
| 8      | Sales Rep      | 30000.00   |
+-----+-----+-----+
4 rows in set (0.00 sec)
```

The above two queries may look like they should return all rows in one or the other of these queries. But we have 8 rows in the jobs table; one was returned with the IN (12000) test and four with the NOT IN (12000) test. What happened to the other three rows? Neither the IN test nor the NOT IN test return the rows where the max_salary is null. For that you need to test with the IS NULL test.

Demo 10: Test with IS NULL

```
Select job_id, job_title, max_salary
From a_emp.jobs
WHERE max_salary is null;
+-----+-----+-----+
| job_id | job_title      | max_salary |
+-----+-----+-----+
| 32     | Code Debugger  | NULL       |
+-----+-----+-----+
```

```

|      64 | DBA      |      NULL |
|     128 | RD       |      NULL |
+-----+-----+-----+
3 rows in set (0.00 sec)

```

3.2. In lists that contain nulls

If you try putting a Null in a list you will find that it does not match a row with a null. The rule is that a row is returned if the Where predicate evaluates as True; a null in the table does not match a null in the list. A null value does not match another null value. The logical value of a null matching a null is Unknown; the value of the filter expression must be True for the row to be returned.

Demo 11: Trying to use Null in a list.

```

Select job_id, job_title, max_salary
From a_emp.jobs
WHERE max_salary IN (120000, null );
+-----+-----+-----+
| job_id | job_title | max_salary |
+-----+-----+-----+
|      16 | Programmer | 120000.00 |
+-----+-----+-----+
1 row in set (0.01 sec)

```

What may seem more surprising is the following query, which returns no rows. The rule is that a row is returned if the Where predicate evaluates as True; the row is not returned if the predicate evaluates as False or as Unknown. Here we are negating the Unknown value which is still Unknown.

Demo 12: Nulls always get interesting

```

Select job_id, job_title, max_salary
From a_emp.jobs
WHERE max_salary NOT IN (120000, null );

```

```

Empty set (0.00 sec)

```

3.3. In lists that contain row values

You can test constructed rows with an In test. In MySQL you can use the expression row(30, 101) to refer to a two part value. The word row is optional; I will use it here to emphasis that we are comparing multi-part row values.

Demo 13: Suppose we wanted to find employees in dept 30 with manager 101. We could use the following. The row values is (30, 101) and it is enclosed in parentheses for the In list. The two columns we are comparing are also enclosed in parentheses.

```

Select emp_id, name_last, dept_id, emp_mng
From a_emp.employees
Where row(dept_id, emp_mng) IN( row(30, 101) );
+-----+-----+-----+-----+
| emp_id | name_last | dept_id | emp_mng |
+-----+-----+-----+-----+
|     108 | Green    |      30 |     101 |
|     203 | Mays     |      30 |     101 |
|     205 | Higgs    |      30 |     101 |
+-----+-----+-----+-----+

```

Demo 14: Now suppose we wanted to find employees in dept 30 with manager 101 and also employees in dept 35 with manager 101.

```

Select emp_id
      , name_last
      , dept_id
      , emp_mng
From a_emp.employees
Where row( dept_id, emp_mng ) in (
      row( 30, 101 )
      , row( 35, 101 )
)
Order by dept_id, emp_mng;
+-----+-----+-----+-----+
| emp_id | name_last | dept_id | emp_mng |
+-----+-----+-----+-----+
|    108 | Green    |      30 |    101 |
|    203 | Mays     |      30 |    101 |
|    205 | Higgs    |      30 |    101 |
|    162 | Holme    |      35 |    101 |
|    200 | Whale    |      35 |    101 |
+-----+-----+-----+-----+

```

Demo 15: You could rewrite this without the keyword row- but include the parentheses which make this a row.

```

Select emp_id, name_last, dept_id, emp_mng
From a_emp.employees
Where (dept_id, emp_mng) IN( (30, 101), (35, 101) )
Order by dept_id, emp_mng;

```

3.4. Testing a literal against an in list

Commonly we think of testing a column against an In list of literals. But with some tests we can reverse that type of thinking. Suppose we are working with the vets database and we are told that the vet got a message that "Edgar is sick" but the message does not say if Edgar is a client or an animal. You can use a Where clause such as this to look for a match for the literal "Edgar with any of these columns.

```
where 'Edgar' in ( cl_name_last, cl_name_first, an_name);
```

Demo 16: And then run this query which looks for the literal Edgar in three columns(don't worry about the join in the From clause at this time)

```

Select cl_name_last, cl_name_first, an_name
From vt_clients C
left join vt_animals A on C.cl_id = a.cl_id
Where 'Edgar' in ( cl_name_last, cl_name_first, an_name);
+-----+-----+-----+
| cl_name_last | cl_name_first | an_name |
+-----+-----+-----+
| Harris      | Eddie        | Edgar   |
| Boston      | Edgar        | NULL    |
+-----+-----+-----+

```

This could use useful for searches where you do not know if a value was entered as a person's first or last name; that happens fairly frequently when people fill out forms.

This syntax is not as obvious in meaning as testing a column against a list of values. Avoid this for a simple In list.

4. The BETWEEN test

To test data against a range of values, use BETWEEN. The Between test is an inclusive test. If the row being tested matches an end point of the range, the test has a true value, and the row will get into the output display. The range should be an increasing range. If you test `WHERE salary BETWEEN 72000 and 3000` the query will run but no rows will be returned.

Demo 17: Using BETWEEN with a numeric range.

```
Select emp_id, name_last AS "Employee", salary
From a_emp.employees
Where salary BETWEEN 65000 AND 70000;
```

emp_id	Employee	salary
104	Ernst	65000.00
109	Fiet	65000.00
160	Dorna	65000.00
200	Whale	65000.00
103	Hunol	69000.00

Demo 18: Using NOT BETWEEN to exclude values in the range.

```
Select emp_id
, name_last as "Employee"
, salary
From a_emp.employees
Where salary not between 25000 and 105000
Order by salary ;
```

emp_id	Employee	salary
201	Harts	15000.00
150	Tuck	20000.00
161	Dewal	120000.00

Demo 19: Using BETWEEN with a date range.

```
Select emp_id, name_last AS "Employee", hire_date
From a_emp.employees
Where hire_date BETWEEN '2001-01-01' AND '2007-12-31';
```

emp_id	Employee	hire_date
150	Tuck	2001-10-28
155	Hiller	2004-03-05
201	Harts	2004-08-25

Demo 20: Using BETWEEN with character range.

```
Select emp_id, name_last AS "Employee", dept_id
From a_emp.employees
Where name_last BETWEEN 'J' and 'T'
Order by name_last;
```

emp_id	Employee	dept_id
--------	----------	---------

	100	King		10	
	204	King		30	
	101	Koch		30	
	203	Mays		30	
	146	Partne		215	
	145	Russ		80	
	207	Russ		35	
+-----+-----+-----+-----+-----+					

You need to be careful with character range tests. If we had an employee with a last name composed of just the letter T, that employee would be returned. But the employee with the name Tuck is not returned.

Demo 21: Customer with a low credit rating

```
Select cust_id, cust_name_last, cust_name_first, credit_limit
From a_oe.customers
Where credit_limit between 0 and 1000;
```

	cust_id		cust_name_last		cust_name_first		credit_limit	
+-----+-----+-----+-----+-----+								
	400801		Washington		Geo		750	
	401250		Morse		Samuel		750	
	402100		Morise		William		750	
	402110		Coltrane		John		750	
	402120		McCoy		Tyner		750	
+-----+-----+-----+-----+-----+								

Demo 22: But customers with no credit rating were not returned by the previous query.

```
Select cust_id, cust_name_last, cust_name_first, credit_limit
From a_oe.customers
Where credit_limit is null;
```

	cust_id		cust_name_last		cust_name_first		credit_limit	
+-----+-----+-----+-----+-----+								
	402500		Jones		Elton John		NULL	
	405000		Day		David		NULL	
+-----+-----+-----+-----+-----+								

The word "between" is one of those words that can be ambiguous in English. If I ask you how many animals appear between the Cat and the Dog, you will probably say 3.



But if I asked you how many integers there are between 12 and 16 { 12, 13, 14, 15, 16} some people will say 3 (13,14,15), some will say 5 [12, 13, 14, 15, 16], and a few people will say 4 [12, 13, 14, 15] or (13, 14, 15, 16]. So if someone asks you to write a query that finds values between two points, it is a good idea to ask if they want to include the end points.

The SQL between operator is always inclusive of the end points. Your job is to write a query that does the job you were asked to do.

4.1. Gotchas

Some tests to watch out for with the use of Between.

The Between operator will match no rows if the range is descending or if one of the range points is a null.

Demo 23: Range is decreasing

```

Select emp_id, name_last AS "Employee", salary
From a_emp.employees
Where salary BETWEEN 70000 AND 65000
;
Empty set (0.00 sec)

```

Demo 24: One end of the range is a null

```

Select emp_id, name_last AS "Employee", salary
From a_emp.employees
Where salary BETWEEN 30000 AND null
;
Empty set (0.00 sec)

```

Demo 25: One end of the range is a null

```

Select emp_id, name_last AS "Employee", salary
From a_emp.employees
Where salary BETWEEN null AND 51000
;
Empty set (0.00 sec)

```

Using Between with datetime values can also be a problem. The ex_date in the vets exam headers table is a date time value.

Demo 26: These are all the exam dates in date order

```

Select ex_id, stf_id, ex_date
From a_vets.vt_exam_headers
Order by ex_date;

```

ex_id	stf_id	ex_date
3105	29	2013-08-10 09:15:00
3010	29	2013-08-22 10:45:00
3001	29	2013-08-24 10:45:00
3203	29	2013-10-03 14:30:00
3202	29	2013-10-03 14:30:00
3304	15	2013-11-06 10:30:00
3282	15	2013-11-23 10:30:00
3306	29	2013-12-06 10:45:00
3390	15	2013-12-22 09:00:00
3393	29	2013-12-23 12:15:00
3392	15	2013-12-26 09:30:00
3409	29	2013-12-27 10:45:00
3486	15	2013-12-31 13:00:00
4101	15	2014-01-02 13:00:00
4102	15	2014-01-08 13:00:00
4103	38	2014-01-08 15:30:00
3288	25	2014-01-09 09:00:00
3104	38	2014-01-09 16:30:00
3322	29	2014-02-10 09:15:00
3321	29	2014-02-17 10:45:00
3324	29	2014-02-25 10:45:00
3323	29	2014-02-25 14:30:00
3325	29	2014-03-15 10:45:00
3420	15	2014-04-01 16:30:00
3494	25	2014-04-22 09:00:00
3411	29	2014-04-29 14:00:00
3412	29	2014-04-30 14:30:00

```

| 3413 |      15 | 2014-05-01 16:30:00 |
| 3612 |      15 | 2014-05-23 08:30:00 |
| 3513 |      15 | 2014-06-06 10:30:00 |
| 3552 |      15 | 2014-06-10 10:30:00 |
| 3514 |      29 | 2014-06-10 10:45:00 |
+-----+-----+-----+

```

Demo 27: But if I filter for exam dates in April 2014 by using between 2014-04-01 and 2014-04-30, I will not get the exam that occurred on April 30, 2014 at 14:30. If you do not include a time component, then the datetime value gets a default time component of midnight.

```

Select ex_id, stf_id, ex_date
From a_vets.vt_exam_headers
Where ex_date between '2014-04-01' and '2014-04-30'
;
+-----+-----+-----+
| ex_id | stf_id | ex_date                |
+-----+-----+-----+
| 3411 |      29 | 2014-04-29 14:00:00 |
| 3420 |      15 | 2014-04-01 16:30:00 |
| 3494 |      25 | 2014-04-22 09:00:00 |
+-----+-----+-----+
4 rows in set (0.00 sec)

```

Demo 28: I could include a time components for the end of the range

```

Select ex_id, stf_id, ex_date
From a_vets.vt_exam_headers
Where ex_date between '2014-04-01' and '2014-04-30 23:59:59';
+-----+-----+-----+
| ex_id | stf_id | ex_date                |
+-----+-----+-----+
| 3411 |      29 | 2014-04-29 14:00:00 |
| 3412 |      29 | 2014-04-30 14:30:00 |
| 3420 |      15 | 2014-04-01 16:30:00 |
| 3494 |      25 | 2014-04-22 09:00:00 |
+-----+-----+-----+
4 rows in set (0.00 sec)

```

You might try to solve this by using a filter

```
Where ex_date between '2014-04-01' and '2013-04-01';
```

But that would include exam date on May 1, 2014 that have the time defaulted to midnight.

We will have a better way to write this query in Unit 05.