

---

# **Python technicalities**

*Release 10.6*

**The Sage Development Team**

**Apr 01, 2025**



# CONTENTS

1 Utilities for interfacing with the standard library's atexit module.	3
2 String <-> bytes encoding/decoding	7
3 Various functions to debug Python internals	9
4 Variants of getattr()	17
5 Metaclasses for Cython extension types	27
6 Slot wrappers	31
7 Delete item from PyDict by exact value and hash	33
8 Indices and Tables	35
Python Module Index	37
Index	39



SageMath has various modules to provide access to low-level Python internals.



## UTILITIES FOR INTERFACING WITH THE STANDARD LIBRARY'S ATEXIT MODULE.

```
class sage.cpython.atexit.restore_atexit
```

Bases: object

Context manager that restores the state of the atexit module to its previous state when exiting the context.

INPUT:

- `run` – boolean (default: `False`); if `True`, when exiting the context (but before restoring the old exit functions), run all atexit functions which were added inside the context
- `clear` – boolean (default: equal to `run`); if `True`, clear already registered atexit handlers upon entering the context

 **Warning**

The combination `run=True` and `clear=False` will cause already-registered exit functions to be run twice: once when exiting the context and again when exiting Python.

EXAMPLES:

For this example we will wrap the entire example with `restore_atexit(clear=True)` so as to start with a fresh atexit module state for the sake of the example.

Note that the function `atexit._run_exitfuncs()` runs all registered handlers, and then clears the list of handlers, so we can use it to test manipulation of the atexit state:

```
sage: import atexit
sage: from sage.cpython.atexit import restore_atexit
sage: def handler(*args, **kwargs):
....:     import sys
....:     # see https://github.com/sagemath/sage/issues/25270#comment:56
....:     sys.stdout.write(str((args, kwargs)))
....:     sys.stdout.write('\n')
sage: atexit.register(handler, 1, 2, c=3)
<function handler at 0x...>
sage: atexit.register(handler, 4, 5, d=6)
<function handler at 0x...>
sage: with restore_atexit(clear=True):
....:     atexit._run_exitfuncs()  # Should be none registered
....:     atexit.register(handler, 1, 2, c=3)
....: with restore_atexit():
```

(continues on next page)

(continued from previous page)

```
....:         atexit._run_exitfuncs()  # Run just registered handler
....:         atexit._run_exitfuncs()  # Handler should be run again
<function handler at 0x...>
((1, 2), {'c': 3})
((1, 2), {'c': 3})
```

```
>>> from sage.all import *
>>> import atexit
>>> from sage.cpython.atexit import restore_atexit
>>> def handler(*args, **kwargs):
...     import sys
...     # see https://github.com/sagemath/sage/issues/25270#comment:56
...     sys.stdout.write(str((args, kwargs)))
...     sys.stdout.write('\n')
>>> atexit.register(handler, Integer(1), Integer(2), c=Integer(3))
<function handler at 0x...>
>>> atexit.register(handler, Integer(4), Integer(5), d=Integer(6))
<function handler at 0x...>
>>> with restore_atexit(clear=True):
...     atexit._run_exitfuncs()  # Should be none registered
...     atexit.register(handler, Integer(1), Integer(2), c=Integer(3))
...     with restore_atexit():
...         atexit._run_exitfuncs()  # Run just registered handler
...         atexit._run_exitfuncs()  # Handler should be run again
<function handler at 0x...>
((1, 2), {'c': 3})
((1, 2), {'c': 3})
```

We test the `run` option:

```
sage: with restore_atexit(run=True):
....:     # this handler is run when exiting the context
....:     _ = atexit.register(handler, 7, 8, e=9)
((7, 8), {'e': 9})
sage: with restore_atexit(clear=False, run=True):
....:     # original handlers are run when exiting the context
....:     pass
((4, 5), {'d': 6})
((1, 2), {'c': 3})
```

```
>>> from sage.all import *
>>> with restore_atexit(run=True):
...     # this handler is run when exiting the context
...     _ = atexit.register(handler, Integer(7), Integer(8), e=Integer(9))
((7, 8), {'e': 9})
>>> with restore_atexit(clear=False, run=True):
...     # original handlers are run when exiting the context
...     pass
((4, 5), {'d': 6})
((1, 2), {'c': 3})
```

The original handlers are still in place:

```
sage: atexit._run_exitfuncs()
((4, 5), {'d': 6})
((1, 2), {'c': 3})
```

```
>>> from sage.all import *
>>> atexit._run_exitfuncs()
((4, 5), {'d': 6})
((1, 2), {'c': 3})
```



---

CHAPTER  
TWO

---

## STRING <-> BYTES ENCODING/DECODING

```
sage.cpython.string.bytes_to_str(b, encoding=None, errors=None)
```

Convert bytes to str.

This decodes the given bytes to a Python 3 unicode str using the specified encoding. It is a no-op on str input.

EXAMPLES:

```
sage: from sage.cpython.string import bytes_to_str
sage: s = bytes_to_str(b'\xcf\x80')
sage: s == u' '
True
sage: bytes_to_str([])
Traceback (most recent call last):
...
TypeError: expected bytes, list found
```

```
>>> from sage.all import *
>>> from sage.cpython.string import bytes_to_str
>>> s = bytes_to_str(b'\xcf\x80')
>>> s == u' '
True
>>> bytes_to_str([])
Traceback (most recent call last):
...
TypeError: expected bytes, list found
```

```
sage.cpython.string.str_to_bytes(s, encoding=None, errors=None)
```

Convert str or unicode to bytes.

It encodes the given str to a Python 3 bytes using the specified encoding. It is a no-op on bytes input.

EXAMPLES:

```
sage: from sage.cpython.string import str_to_bytes
sage: bs = [str_to_bytes(u' ')]
sage: all(b == b'\xcf\x80' for b in bs)
True
sage: str_to_bytes([])
Traceback (most recent call last):
...
TypeError: expected str... list found
```

```
>>> from sage.all import *
>>> from sage.cpython.string import str_to_bytes
>>> bs = [str_to_bytes(u'\u00c0')]
>>> all(b == b'\xc0\x80' for b in bs)
True
>>> str_to_bytes([])
Traceback (most recent call last):
...
TypeError: expected str... list found
```

## VARIOUS FUNCTIONS TO DEBUG PYTHON INTERNALS

```
sage.cpython.debug.getattr_debug(obj, name, default='no_default')
```

A re-implementation of `getattr()` with lots of debugging info.

This will correctly use `__getattr__` if needed. On the other hand, it assumes a generic (not overridden) implementation of `__getattribute__`. Note that Cython implements `__getattr__` for a cdef class using `__getattribute__`, so this will not detect a `__getattr__` in that case.

INPUT:

- `obj` – the object whose attribute is requested
- `name` – string, the name of the attribute
- `default` – default value to return if attribute was not found

EXAMPLES:

```
sage: _ = getattr_debug(list, "reverse") # not tested - broken in python 3.12
getattr_debug(obj=<class 'list'>, name='reverse'):
    type(obj) = <class 'type'>
    object has __dict__ slot (<class 'dict'>)
    did not find 'reverse' in MRO classes
    found 'reverse' in object __dict__
    returning <method 'reverse' of 'list' objects> (<class 'method_descriptor'>)
sage: _ = getattr_debug([], "reverse")
getattr_debug(obj=[], name='reverse'):
    type(obj) = <class 'list'>
    object does not have __dict__ slot
    found 'reverse' in dict of <class 'list'>
    got <method 'reverse' of 'list' objects> (<class 'method_descriptor'>)
    attribute is ordinary descriptor (has __get__)
    calling __get__()
    returning <built-in method reverse of list object at 0x... (<class 'builtin_
        function_or_method'>)
sage: _ = getattr_debug([], "__doc__")
getattr_debug(obj=[], name='__doc__'):
    type(obj) = <class 'list'>
    object does not have __dict__ slot
    found '__doc__' in dict of <class 'list'>
    got ... 'str'>
    returning ... 'str'>
sage: _ = getattr_debug(gp(1), "log") #_
needs sage.libs.pari
```

(continues on next page)

(continued from previous page)

```

getattr_debug(obj=1, name='log'):
    type(obj) = <class 'sage.interfaces.gp.GpElement'>
    object has __dict__ slot (<class 'dict'>)
    did not find 'log' in MRO classes
    object __dict__ does not have 'log'
    calling __getattr__()
    returning log (<class 'sage.interfaces.expect.FunctionElement'>)

sage: from ipywidgets import IntSlider
sage: _ = getattr_debug(IntSlider(), "value")
getattr_debug(obj=IntSlider(value=0), name='value'):
    type(obj) = <class 'ipywidgets.widgets.widget_int.IntSlider'>
    object has __dict__ slot (<class 'dict'>)
    found 'value' in dict of <class 'ipywidgets.widgets.widget_int._Int'>
    got <traitlets.traitlets.CInt object at ... (<class 'traitlets.traitlets.CInt'>)
    attribute is data descriptor (has __get__ and __set__)
    ignoring __dict__ because we have a data descriptor
    calling __get__()
    returning 0 (<class 'int'>)

sage: _ = getattr_debug(1, "foo")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'foo'...
sage: _ = getattr_debug(1, "foo", "xyz")
getattr_debug(obj=1, name='foo'):
    type(obj) = <class 'sage.rings.integer.Integer'>
    object does not have __dict__ slot
    did not find 'foo' in MRO classes
    class does not have __getattr__
    attribute not found
    returning default 'xyz'
```

```

>>> from sage.all import *
>>> _ = getattr_debug(list, "reverse") # not tested - broken in python 3.12
getattr_debug(obj=<class 'list'>, name='reverse'):
    type(obj) = <class 'type'>
    object has __dict__ slot (<class 'dict'>)
    did not find 'reverse' in MRO classes
    found 'reverse' in object __dict__
    returning <method 'reverse' of 'list' objects> (<class 'method_descriptor'>)

>>> _ = getattr_debug([], "reverse")
getattr_debug(obj=[], name='reverse'):
    type(obj) = <class 'list'>
    object does not have __dict__ slot
    found 'reverse' in dict of <class 'list'>
    got <method 'reverse' of 'list' objects> (<class 'method_descriptor'>)
    attribute is ordinary descriptor (has __get__)
    calling __get__()
    returning <built-in method reverse of list object at 0x... (<class 'builtin_
    function_or_method'>)

>>> _ = getattr_debug([], "__doc__")
getattr_debug(obj=[], name='__doc__'):
    type(obj) = <class 'list'>
```

(continues on next page)

(continued from previous page)

```

object does not have __dict__ slot
found '__doc__' in dict of <class 'list'>
got ... 'str'>
returning ... 'str'>
>>> _ = getattr_debug(gp(Integer(1)), "log")
→   # needs sage.libs.pari
getattr_debug(obj=1, name='log'):
    type(obj) = <class 'sage.interfaces.gp.GpElement'>
    object has __dict__ slot (<class 'dict'>)
    did not find 'log' in MRO classes
    object __dict__ does not have 'log'
    calling __getattr__()
    returning log (<class 'sage.interfaces.expect.FunctionElement'>)
>>> from ipywidgets import IntSlider
>>> _ = getattr_debug(IntSlider(), "value")
getattr_debug(obj=IntSlider(value=0), name='value'):
    type(obj) = <class 'ipywidgets.widgets.widget_int.IntSlider'>
    object has __dict__ slot (<class 'dict'>)
    found 'value' in dict of <class 'ipywidgets.widgets.widget_int._Int'>
    got <traitlets.traitlets.CInt object at ... (<class 'traitlets.traitlets.CInt'>)
    attribute is data descriptor (has __get__ and __set__)
    ignoring __dict__ because we have a data descriptor
    calling __get__()
    returning 0 (<class 'int'>)
>>> _ = getattr_debug(Integer(1), "foo")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'foo'...
>>> _ = getattr_debug(Integer(1), "foo", "xyz")
getattr_debug(obj=1, name='foo'):
    type(obj) = <class 'sage.rings.integer.Integer'>
    object does not have __dict__ slot
    did not find 'foo' in MRO classes
    class does not have __getattr__
    attribute not found
    returning default 'xyz'
```

sage.cpython.debug.**shortrepr**(obj, max=50)

Return `repr(obj)` bounded to `max` characters. If the string is too long, it is truncated and `~~~` is added to the end.

#### EXAMPLES:

```

sage: from sage.cpython.debug import shortrepr
sage: print(shortrepr("Hello world!"))
'Hello world!'
sage: print(shortrepr("Hello world!" * 4))
'Hello world!Hello world!Hello world!Hello world!'
sage: print(shortrepr("Hello world!" * 5))
'Hello world!Hello world!Hello world!Hello worl~~~'
```

```
>>> from sage.all import *
```

(continues on next page)

(continued from previous page)

```
>>> from sage.cpython.debug import shortrepr
>>> print(shortrepr("Hello world!"))
'Hello world!'
>>> print(shortrepr("Hello world!" * Integer(4)))
'Hello world!Hello world!Hello world!Hello world!'
>>> print(shortrepr("Hello world!" * Integer(5)))
'Hello world!Hello world!Hello world!Hello worl~~~
```

`sage.cpython.debug.type_debug(cls)`

Print all internals of the type `cls`.

EXAMPLES:

```
sage: type_debug(object) # random
<class 'object'> (0x7fc57da7f040)
ob_refcnt: 9739
ob_type: <class 'type'>
tp_name: object
tp_basicsize: 16
tp_itemsize: 0
tp_dictoffset: 0
tp_weaklistoffset: 0
tp_base (__base__): NULL
tp_bases (__bases__): tuple:
tp_mro (__mro__): tuple:
<class 'object'>
tp_dict (__dict__): dict:
    '__setattr__': <slot wrapper '__setattr__' of 'object' objects>
    '__reduce_ex__': <method '__reduce_ex__' of 'object' objects>
    '__new__': <built-in method __new__ of type object at 0x7fc57da7f040>
    '__reduce__': <method '__reduce__' of 'object' objects>
    '__str__': <slot wrapper '__str__' of 'object' objects>
    '__format__': <method '__format__' of 'object' objects>
    '__getattribute__': <slot wrapper '__getattribute__' of 'object' objects>
    '__class__': <attribute '__class__' of 'object' objects>
    '__delattr__': <slot wrapper '__delattr__' of 'object' objects>
    '__subclasshook__': <method '__subclasshook__' of 'object' objects>
    '__repr__': <slot wrapper '__repr__' of 'object' objects>
    '__hash__': <slot wrapper '__hash__' of 'object' objects>
    '__sizeof__': <method '__sizeof__' of 'object' objects>
    '__doc__': 'The most base type'
    '__init__': <slot wrapper '__init__' of 'object' objects>
tp_alloc: PyType_GenericAlloc
tp_new (__new__): 0x7fc57d7594f0
tp_init (__init__): 0x7fc57d758ee0
tp_dealloc (__dealloc__): 0x7fc57d757010
tp_free: PyObject_Del
tp_repr (__repr__): 0x7fc57d75b990
tp_print: NULL
tp_hash (__hash__): _Py_HashPointer
tp_call (__call__): NULL
tp_str (__str__): 0x7fc57d757020
```

(continues on next page)

(continued from previous page)

```

tp_compare (__cmp__): NULL
tp_richcompare (__richcmp__): NULL
tp_getattr (__getattribute__): NULL
tp_setattr (__setattribute__): NULL
tp_getattro (__getattribute__): PyObject_GenericGetAttr
tp_setattro (__setattribute__): PyObject_GenericSetAttr
tp_iter (__iter__): NULL
tp_iternext (__next__): NULL
tp_descr_get (__get__): NULL
tp_descr_set (__set__): NULL
tp_cache: NULL
tp_weaklist: NULL
tp_traverse: NULL
tp_clear: NULL
tp_is_gc: NULL
tp_as_number: NULL
tp_as_sequence: NULL
tp_as_mapping: NULL
tp_as_buffer: NULL
tp_flags:
    HAVE_GETCHARBUFFER
    HAVE_SEQUENCE_IN
    HAVE_INPLACEOPS
    HAVE_RICHCOMPARE
    HAVE_WEAKREFS
    HAVE_ITER
    HAVE_CLASS
    BASETYPE
    READY
    HAVE_INDEX
    HAVE_VERSION_TAG
    VALID_VERSION_TAG
    tp_version_tag: 2
sage: type_debug(None)
Traceback (most recent call last):
...
TypeError: None is not a type

```

```

>>> from sage.all import *
>>> type_debug(object) # random
<class 'object'> (0x7fc57da7f040)
ob_refcnt: 9739
ob_type: <class 'type'>
tp_name: object
tp_basicsize: 16
tp_itemsize: 0
tp_dictoffset: 0
tp_weaklistoffset: 0
tp_base (__base__): NULL
tp_bases (__bases__): tuple:
tp_mro (__mro__): tuple:
<class 'object'>

```

(continues on next page)

(continued from previous page)

```
tp_dict (__dict__): dict:  
    '__setattr__': <slot wrapper '__setattr__' of 'object' objects>  
    '__reduce_ex__': <method '__reduce_ex__' of 'object' objects>  
    '__new__': <built-in method __new__ of type object at 0x7fc57da7f040>  
    '__reduce__': <method '__reduce__' of 'object' objects>  
    '__str__': <slot wrapper '__str__' of 'object' objects>  
    '__format__': <method '__format__' of 'object' objects>  
    '__getattribute__': <slot wrapper '__getattribute__' of 'object' objects>  
    '__class__': <attribute '__class__' of 'object' objects>  
    '__delattr__': <slot wrapper '__delattr__' of 'object' objects>  
    '__subclasshook__': <method '__subclasshook__' of 'object' objects>  
    '__repr__': <slot wrapper '__repr__' of 'object' objects>  
    '__hash__': <slot wrapper '__hash__' of 'object' objects>  
    '__sizeof__': <method '__sizeof__' of 'object' objects>  
    '__doc__': 'The most base type'  
    '__init__': <slot wrapper '__init__' of 'object' objects>  
tp_alloc: PyType_GenericAlloc  
tp_new (__new__): 0x7fc57d7594f0  
tp_init (__init__): 0x7fc57d758ee0  
tp_dealloc (__dealloc__): 0x7fc57d757010  
tp_free: PyObject_Del  
tp_repr (__repr__): 0x7fc57d75b990  
tp_print: NULL  
tp_hash (__hash__): _Py_HashPointer  
tp_call (__call__): NULL  
tp_str (__str__): 0x7fc57d757020  
tp_compare (__cmp__): NULL  
tp_richcompare (__richcmp__): NULL  
tp_getattr (__getattribute__): NULL  
tp_setattr (__setattribute__): NULL  
tp_getattro (__getattribute__): PyObject_GenericGetAttr  
tp_setattro (__setattribute__): PyObject_GenericSetAttr  
tp_iter (__iter__): NULL  
tp_iternext (__next__): NULL  
tp_descr_get (__get__): NULL  
tp_descr_set (__set__): NULL  
tp_cache: NULL  
tp_weaklist: NULL  
tp_traverse: NULL  
tp_clear: NULL  
tp_is_gc: NULL  
tp_as_number: NULL  
tp_as_sequence: NULL  
tp_as_mapping: NULL  
tp_as_buffer: NULL  
tp_flags:  
    HAVE_GETCHARBUFFER  
    HAVE_SEQUENCE_IN  
    HAVE_INPLACEOPS  
    HAVE_RICHCOMPARE  
    HAVE_WEAKREFS  
    HAVE_ITER
```

(continues on next page)

(continued from previous page)

```
HAVE_CLASS
BASETYPE
READY
HAVE_INDEX
HAVE_VERSION_TAG
VALID_VERSION_TAG
tp_version_tag: 2
>>> type_debug(None)
Traceback (most recent call last):
...
TypeError: None is not a type
```



## VARIANTS OF GETATTR()

```
class sage.cpythongetattr.AttributeErrorMessage
```

Bases: object

Try to emulate the standard Python `AttributeError` message.

 Note

The typical fate of an attribute error is being caught. Hence, under normal circumstances, nobody will ever see the error message. The idea for this class is to provide an object that is fast to create and whose string representation is an attribute error's message. That string representation is only created if someone wants to see it.

### EXAMPLES:

```
sage: 1.bla #indirect doctest
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'bla'...
sage: x = polygen(ZZ, 'x')
sage: QQ[x].gen().bla #_
˓needs sage.libs.flint
Traceback (most recent call last):
...
AttributeError: 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_
˓rational_flint' object has no attribute 'bla'...
```

```
>>> from sage.all import *
>>> Integer(1).bla #indirect doctest
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'bla'...
>>> x = polygen(ZZ, 'x')
>>> QQ[x].gen().bla #_
˓needs sage.libs.flint
Traceback (most recent call last):
...
AttributeError: 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_
˓rational_flint' object has no attribute 'bla'...
```

```
sage: from sage.cpythongetattr import AttributeErrorMessage
sage: AttributeErrorMessage(int(1), 'bla')
'int' object has no attribute 'bla'
```

```
>>> from sage.all import *
>>> from sage.cpythongetattr import AttributeErrorMessage
>>> AttributeErrorMessage(Integer(1), 'bla')
'int' object has no attribute 'bla'
```

### AUTHOR:

- Simon King (2011-05-21)

`cls`

`name`

`sage.cpythongetattr.dir_with_other_class(self, *cls)`

Emulates `dir(self)`, as if `self` was also an instance `cls`, right after `caller_class` in the method resolution order (`self.__class__.mro()`)

### EXAMPLES:

```
sage: class A():
....:     a = 1
....:     b = 2
....:     c = 3
sage: class B():
....:     b = 2
....:     c = 3
....:     d = 4
sage: x = A()
sage: x.c = 1; x.e = 1
sage: from sage.cpythongetattr import dir_with_other_class
sage: dir_with_other_class(x, B)
[..., 'a', 'b', 'c', 'd', 'e']
sage: class C():
....:     f = 6
sage: dir_with_other_class(x, B, C)
[..., 'a', 'b', 'c', 'd', 'e', 'f']
```

```
>>> from sage.all import *
>>> class A():
...     a = Integer(1)
...     b = Integer(2)
...     c = Integer(3)
>>> class B():
...     b = Integer(2)
...     c = Integer(3)
...     d = Integer(4)
>>> x = A()
>>> x.c = Integer(1); x.e = Integer(1)
>>> from sage.cpythongetattr import dir_with_other_class
>>> dir_with_other_class(x, B)
```

(continues on next page)

(continued from previous page)

```
[..., 'a', 'b', 'c', 'd', 'e']
>>> class C():
...     f = Integer(6)
>>> dir_with_other_class(x, B, C)
[..., 'a', 'b', 'c', 'd', 'e', 'f']
```

Check that objects without dicts are well handled:

```
sage: # needs sage.misc.cython
sage: cython("cdef class A:\n    cdef public int a")
sage: cython("cdef class B:\n    cdef public int b")
sage: x = A()
sage: x.a = 1
sage: hasattr(x, '__dict__')
False
sage: dir_with_other_class(x, B)
[..., 'a', 'b']
```

```
>>> from sage.all import *
>>> # needs sage.misc.cython
>>> cython("cdef class A:\n    cdef public int a")
>>> cython("cdef class B:\n    cdef public int b")
>>> x = A()
>>> x.a = Integer(1)
>>> hasattr(x, '__dict__')
False
>>> dir_with_other_class(x, B)
[..., 'a', 'b']
```

`sage.cpython.getattr.getattr_from_other_class(self, cls, name)`

Emulate `getattr(self, name)`, as if `self` was an instance of `cls`.

INPUT:

- `self` – some object
- `cls` – a new-style class
- `name` – string

If `self` is an instance of `cls`, raises an `AttributeError`, to avoid a double lookup. This function is intended to be called from `__getattr__`, and so should not be called if `name` is an attribute of `self`.

EXAMPLES:

```
sage: from sage.cpython.getattr import getattr_from_other_class
sage: class A():
....:     def inc(self):
....:         return self + 1
....:
....:     @staticmethod
....:     def greeting():
....:         print("Hello World!")
....:
....:     @lazy_attribute
```

(continues on next page)

(continued from previous page)

```
....:     def lazy_attribute(self):
....:         return repr(self)
sage: getattr_from_other_class(1, A, "inc")
<bound method A.inc of 1>
sage: getattr_from_other_class(1, A, "inc")()
2
```

```
>>> from sage.all import *
>>> from sage.cpython.getattr import getattr_from_other_class
>>> class A():
...     def inc(self):
...         return self + Integer(1)
....:
>>>     @staticmethod
...     def greeting():
...         print("Hello World!")
....:
>>>     @lazy_attribute
...     def lazy_attribute(self):
...         return repr(self)
>>> getattr_from_other_class(Integer(1), A, "inc")
<bound method A.inc of 1>
>>> getattr_from_other_class(Integer(1), A, "inc")()
2
```

Static methods work:

```
sage: getattr_from_other_class(1, A, "greeting")()
Hello World!
```

```
>>> from sage.all import *
>>> getattr_from_other_class(Integer(1), A, "greeting")()
Hello World!
```

Caveat: lazy attributes work with extension types only if they allow attribute assignment or have a public attribute `_cached_methods` of type `<dict>`. This condition is satisfied, e.g., by any class that is derived from `Parent`:

```
sage: getattr_from_other_class(1, A, "lazy_attribute")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'lazy_
attribute'...
```

```
>>> from sage.all import *
>>> getattr_from_other_class(Integer(1), A, "lazy_attribute")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'lazy_
attribute'...
```

The integer ring is a parent, so, lazy attributes work:

```
sage: getattr_from_other_class(ZZ, A, "lazy_attribute")
'Integer Ring'
sage: getattr_from_other_class(PolynomialRing(QQ, name='x', sparse=True).one(), A,
    ↪ "lazy_attribute")
'1'
sage: getattr_from_other_class(17, A, "lazy_attribute")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'lazy_
attribute'...
```

```
>>> from sage.all import *
>>> getattr_from_other_class(ZZ, A, "lazy_attribute")
'Integer Ring'
>>> getattr_from_other_class(PolynomialRing(QQ, name='x', sparse=True).one(), A,
    ↪ "lazy_attribute")
'1'
>>> getattr_from_other_class(Integer(17), A, "lazy_attribute")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute 'lazy_
attribute'...
```

In general, descriptors are not yet well supported, because they often do not accept to be cheated with the type of their instance:

```
sage: A.__weakref__.__get__(1)
Traceback (most recent call last):
...
TypeError: descriptor '__weakref__' for 'A' objects doesn't apply
to ...'sage.rings.integer.Integer' object
```

```
>>> from sage.all import *
>>> A.__weakref__.__get__(Integer(1))
Traceback (most recent call last):
...
TypeError: descriptor '__weakref__' for 'A' objects doesn't apply
to ...'sage.rings.integer.Integer' object
```

When this occurs, an `AttributeError` is raised:

```
sage: getattr_from_other_class(1, A, "__weakref__")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute '__weakref__
↪'...
```

```
>>> from sage.all import *
>>> getattr_from_other_class(Integer(1), A, "__weakref__")
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute '__weakref__
↪'...
```

This was caught by Issue #8296 for which we do a couple more tests:

```
sage: "__weakref__" in dir(A)
True
sage: 1.__weakref__
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute '__weakref__'
↪'...

sage: n = 1
sage: ip = get_ipython()                               # not tested: only works in interactive
↪shell
sage: ip.magic_psearch('n.N')                         # not tested: only works in interactive
↪shell
n.N
sage: ip.magic_psearch('n.__weakref__')   # not tested: only works in interactive
↪shell
```

```
>>> from sage.all import *
>>> "__weakref__" in dir(A)
True
>>> Integer(1).__weakref__
Traceback (most recent call last):
...
AttributeError: 'sage.rings.integer.Integer' object has no attribute '__weakref__'
↪'...

>>> n = Integer(1)
>>> ip = get_ipython()                               # not tested: only works in interactive
↪shell
>>> ip.magic_psearch('n.N')                         # not tested: only works in interactive
↪shell
n.N
>>> ip.magic_psearch('n.__weakref__')   # not tested: only works in interactive
↪shell
```

Caveat: When `__call__` is not defined for instances, using `A.__call__` yields the method `__call__` of the class. We use a workaround but there is no guarantee for robustness.

```
sage: getattr_from_other_class(1, A, " __call__ ")
Traceback (most recent call last): ...
AttributeError: 'sage.rings.integer.Integer' object has no attribute '__call__' ...
```

```
sage.cpython.getattr.raw_getattr(obj, name)
```

Like `getattr(obj, name)` but without invoking the binding behavior of descriptors under normal attribute access. This can be used to easily get unbound methods or other descriptors.

This ignores `__getattribute__` hooks but it does support `__getattr__`.

### Note

For Cython classes, `__getattr__` is actually implemented as `__getattribute__`, which means that it is not supported by `raw_getattr`.

## EXAMPLES:

```
sage: class X:
....:     @property
....:     def prop(self):
....:         return 42
....:     def method(self):
....:         pass
....:     def __getattr__(self, name):
....:         return "magic " + name
sage: raw_getattr(X, "prop")
<property object at ...>
sage: raw_getattr(X, "method")
<function ...method at ...>
sage: raw_getattr(X, "attr")
Traceback (most recent call last):
...
AttributeError: '...' object has no attribute 'attr'...
sage: x = X()
sage: raw_getattr(x, "prop")
<property object at ...>
sage: raw_getattr(x, "method")
<function ...method at ...>
sage: raw_getattr(x, "attr")
'magic attr'
sage: x.__dict__["prop"] = 'no'
sage: x.__dict__["method"] = 'yes'
sage: x.__dict__["attr"] = 'ok'
sage: raw_getattr(x, "prop")
<property object at ...>
sage: raw_getattr(x, "method")
'yes'
sage: raw_getattr(x, "attr")
'ok'
```

```
>>> from sage.all import *
>>> class X:
...     @property
...     def prop(self):
...         return Integer(42)
...     def method(self):
...         pass
...     def __getattr__(self, name):
...         return "magic " + name
>>> raw_getattr(X, "prop")
<property object at ...>
>>> raw_getattr(X, "method")
<function ...method at ...>
>>> raw_getattr(X, "attr")
Traceback (most recent call last):
...
AttributeError: '...' object has no attribute 'attr'...
>>> x = X()
```

(continues on next page)

(continued from previous page)

```
>>> raw_getattr(x, "prop")
<property object at ...>
>>> raw_getattr(x, "method")
<function ...method at ...>
>>> raw_getattr(x, "attr")
'magic attr'
>>> x.__dict__["prop"] = 'no'
>>> x.__dict__["method"] = 'yes'
>>> x.__dict__["attr"] = 'ok'
>>> raw_getattr(x, "prop")
<property object at ...>
>>> raw_getattr(x, "method")
'yes'
>>> raw_getattr(x, "attr")
'ok'
```

The same tests with an inherited new-style class:

```
sage: class Y(X, object):
....:     pass
sage: raw_getattr(Y, "prop")
<property object at ...>
sage: raw_getattr(Y, "method")
<function ...method at ...>
sage: raw_getattr(Y, "attr")
Traceback (most recent call last):
...
AttributeError: '...' object has no attribute 'attr'...
sage: y = Y()
sage: raw_getattr(y, "prop")
<property object at ...>
sage: raw_getattr(y, "method")
<function ...method at ...>
sage: raw_getattr(y, "attr")
'magic attr'
sage: y.__dict__["prop"] = 'no'
sage: y.__dict__["method"] = 'yes'
sage: y.__dict__["attr"] = 'ok'
sage: raw_getattr(y, "prop")
<property object at ...>
sage: raw_getattr(y, "method")
'yes'
sage: raw_getattr(y, "attr")
'ok'
```

```
>>> from sage.all import *
>>> class Y(X, object):
....:     pass
>>> raw_getattr(Y, "prop")
<property object at ...>
>>> raw_getattr(Y, "method")
<function ...method at ...>
```

(continues on next page)

(continued from previous page)

```
>>> raw_getattr(Y, "attr")
Traceback (most recent call last):
...
AttributeError: '...' object has no attribute 'attr'...
>>> y = Y()
>>> raw_getattr(y, "prop")
<property object at ...>
>>> raw_getattr(y, "method")
<function ...method at ...>
>>> raw_getattr(y, "attr")
'magic attr'
>>> y.__dict__["prop"] = 'no'
>>> y.__dict__["method"] = 'yes'
>>> y.__dict__["attr"] = 'ok'
>>> raw_getattr(y, "prop")
<property object at ...>
>>> raw_getattr(y, "method")
'yes'
>>> raw_getattr(y, "attr")
'ok'
```



## METACLASSES FOR CYTHON EXTENSION TYPES

Cython does not support metaclasses, but this module can be used to implement metaclasses for extension types.

### ⚠ Warning

This module has many caveats and you can easily get segfaults if you make a mistake. It relies on undocumented Python and Cython behaviour, so things might break in future versions.

### 5.1 How to use

To enable this metaclass mechanism, you need to put `cimport sage.cpython.cython_metaclass` in your module (in the `.pxd` file if you are using one).

In the extension type (a.k.a. `cdef class`) for which you want to define a metaclass, define a method `__getmetaclass__` with a single unused argument, and turn off the Cython directive `always_allow_keywords`. This method should return a type to be used as metaclass:

```
cimport cython
cimport sage.cpython.cython_metaclass
cdef class MyCustomType():
    @cython.always_allow_keywords(False)
    def __getmetaclass__(_):
        from foo import MyMetaclass
        return MyMetaclass
```

### ⚠ Warning

`__getmetaclass__` must be defined as an ordinary method taking a single argument, but this argument should not be used in the method (it will be `None`).

When a type `cls` is being constructed with metaclass `meta`, then `meta.__init__(cls, None, None, None)` is called from Cython. In Python, this would be `meta.__init__(cls, name, bases, dict)`.

### ⚠ Warning

The `__getmetaclass__` method is called while the type is being created during the import of the module. Therefore, `__getmetaclass__` should not refer to any global objects, including the type being created or other types

defined or imported in the module (unless you are very careful). Note that non-imported `cdef` functions are not Python objects, so those are safe to call.

The same warning applies to the `__init__` method of the metaclass.

### ⚠ Warning

The `__new__` method of the metaclass (including the `__cinit__` method for Cython extension types) is never called if you're using this from Cython. In particular, the metaclass cannot have any attributes or virtual methods.

## EXAMPLES:

```
sage: cython(                                     #
    ↪needs sage.misc.cython
....: """
....: cimport cython
....: cimport sage.cpython.cython_metaclass
....: cdef class MyCustomType():
....:     @cython.always_allow_keywords(False)
....:     def __getmetaclass__(_):
....:         class MyMetaclass(type):
....:             def __init__(*args):
....:                 print("Calling MyMetaclass.__init__{}".format(args))
....:             return MyMetaclass
....:
....: cdef class MyDerivedType(MyCustomType):
....:     pass
....: """
Calling MyMetaclass.__init__(<class '...MyCustomType'>, None, None, None)
Calling MyMetaclass.__init__(<class '...MyDerivedType'>, None, None, None)
sage: MyCustomType.__class__                           #
    ↪needs sage.misc.cython
<class '...MyMetaclass'>
sage: class MyPythonType(MyDerivedType):              #
    ↪needs sage.misc.cython
....:     pass
Calling MyMetaclass.__init__(<class '...MyPythonType'>, 'MyPythonType', (<class '...
    ↪MyDerivedType'>,), {...})
```

```
>>> from sage.all import *
>>> cython(                                     #
    ↪needs sage.misc.cython
... """
... cimport cython
... cimport sage.cpython.cython_metaclass
... cdef class MyCustomType():
...     @cython.always_allow_keywords(False)
...     def __getmetaclass__(_):
...         class MyMetaclass(type):
...             def __init__(*args):
...                 print("Calling MyMetaclass.__init__{}".format(args))
```

(continues on next page)

(continued from previous page)

```

...
    return MyMetaclass
....:
>>> cdef class MyDerivedType(MyCustomType):
...     pass
... """
Calling MyMetaclass.__init__(<class '...MyCustomType'>, None, None, None)
Calling MyMetaclass.__init__(<class '...MyDerivedType'>, None, None, None)
>>> MyCustomType.__class__                                     #_
↳needs sage.misc.cython
<class '...MyMetaclass'>
>>> class MyPythonType(MyDerivedType):                         #_
↳needs sage.misc.cython
...
    pass
Calling MyMetaclass.__init__(<class '...MyPythonType'>, 'MyPythonType', (<class '...
↳MyDerivedType'>,), {...})

```

## 5.2 Implementation

All this is implemented by defining

```
#define PyTypeReady(t)  Sage_PyType_Ready(t)
```

and then implementing the function `Sage_PyType_Ready(t)` which first calls `PyType_Ready(t)` and then handles the metaclass stuff.



## SLOT WRAPPERS

A slot wrapper is installed in the dict of an extension type to access a special method implemented in C. For example, `object.__init__` or `Integer.__lt__`. Note that slot wrappers are always unbound (there is a bound variant called method-wrapper).

EXAMPLES:

```
sage: int.__add__
<slot wrapper '__add__' of 'int' objects>
```

```
>>> from sage.all import *
>>> int.__add__
<slot wrapper '__add__' of 'int' objects>
```

Pure Python classes have normal methods, not slot wrappers:

```
sage: class X():
....:     def __add__(self, other):
....:         return NotImplemented
sage: X.__add__
<function X.__add__ at ...>
```

```
>>> from sage.all import *
>>> class X():
...     def __add__(self, other):
...         return NotImplemented
>>> X.__add__
<function X.__add__ at ...>
```

```
sage.cpython.wrapperdescr.wrapperdescr_call(slotwrapper, self, *args, **kwds)
```

Call a slot wrapper without any type checks.

The main reason to use this is to call arithmetic slots like `__mul__` without having to worry about whether to call `T.__mul__(a, b)` or `T.__rmul__(b, a)`.

INPUT:

- `slotwrapper` – a slot wrapper (for example `int.__add__`)
- `self` – the first positional argument. Normally, this should be of the correct type (an `int` when calling `int.__add__`). However, this check is skipped: you can pass an arbitrary object.
- `*args, **kwds` – further arguments

 **Warning**

Since this skips type checks, it can easily crash Python if used incorrectly.

### EXAMPLES:

```
sage: from sage.cpython.wrapperdescr import wrapperdescr_call
sage: wrapperdescr_call(Integer.__mul__, 6, 9)
54
sage: wrapperdescr_call(Integer.__mul__, 7/5, 9)
63/5
sage: from sage.structure.element import Element
sage: wrapperdescr_call(Element.__mul__, 6, 9)
54
sage: wrapperdescr_call(Element.__mul__, 7/5, 9)
63/5
sage: from sage.numerical.mip import MixedIntegerLinearProgram      #_
↳needs sage.numerical.mip
sage: wrapperdescr_call(type.__call__,                                     #_
↳needs sage.numerical.mip
....:                           MixedIntegerLinearProgram, maximization=False)
Mixed Integer Program (no objective, 0 variables, 0 constraints)
```

```
>>> from sage.all import *
>>> from sage.cpython.wrapperdescr import wrapperdescr_call
>>> wrapperdescr_call(Integer.__mul__, Integer(6), Integer(9))
54
>>> wrapperdescr_call(Integer.__mul__, Integer(7)/Integer(5), Integer(9))
63/5
>>> from sage.structure.element import Element
>>> wrapperdescr_call(Element.__mul__, Integer(6), Integer(9))
54
>>> wrapperdescr_call(Element.__mul__, Integer(7)/Integer(5), Integer(9))
63/5
>>> from sage.numerical.mip import MixedIntegerLinearProgram      #_
↳needs sage.numerical.mip
>>> wrapperdescr_call(type.__call__,                                     #_
↳needs sage.numerical.mip
...
                           MixedIntegerLinearProgram, maximization=False)
Mixed Integer Program (no objective, 0 variables, 0 constraints)
```

## DELETE ITEM FROM PYDICT BY EXACT VALUE AND HASH

Beware that the implementation of the routine here relies on implementation details of CPython's dict that go beyond the published API.

AUTHORS:

- Nils Bruin (2017-05)

```
sage.cpython.dict_del_by_value.test_del_dictitem_by_exact_value(D, value, h)
```

This function helps testing some cdef function used to delete dictionary items.

INPUT:

- D – a Python <dict>
- value – an object that is value D
- h – the hash of the key under which to find value in D

The underlying cdef function deletes an item from D that is in the hash bucket determined by h and whose value is identic with value. Of course, this only makes sense if the pairs (h, value) corresponding to items in D are pair-wise distinct.

If a matching item cannot be found, the function does nothing and silently returns.



---

**CHAPTER  
EIGHT**

---

## **INDICES AND TABLES**

- [Index](#)
- [Module Index](#)
- [Search Page](#)



## PYTHON MODULE INDEX

### C

sage.cpython.atexit, 3  
sage.cpython.cython\_metaclass, 27  
sage.cpython.debug, 9  
sage.cpython.dict\_del\_by\_value, 33  
sage.cpython.getattr, 17  
sage.cpython.string, 7  
sage.cpython.wrapperdescr, 31



# INDEX

## A

AttributeErrorMessage (*class in sage.cpythongetattr*), 17

## B

bytes\_to\_str () (*in module sage.cpython.string*), 7

## C

cls (*sage.cpythongetattr.AttributeErrorMessage attribute*), 18

## D

dir\_with\_other\_class () (in module sage.cpythongetattr), 18

## G

getattr\_debug () (*in module sage.cpython.debug*), 9  
getattr\_from\_other\_class () (in module sage.cpythongetattr), 19

## M

module  
    sage.cpython.atexit, 3  
    sage.cpython.cython\_metaclass, 27  
    sage.cpython.debug, 9  
    sage.cpython.dict\_del\_by\_value, 33  
    sage.cpythongetattr, 17  
    sage.cpython.string, 7  
    sage.cpython.wrapperdescr, 31

## N

name (*sage.cpythongetattr.AttributeErrorMessage attribute*), 18

## R

raw\_getattr () (*in module sage.cpythongetattr*), 22  
restore\_atexit (*class in sage.cpython.atexit*), 3

## S

sage.cpython.atexit  
    module, 3

sage.cpython.cython\_metaclass  
    module, 27  
sage.cpython.debug  
    module, 9  
sage.cpython.dict\_del\_by\_value  
    module, 33  
sage.cpythongetattr  
    module, 17  
sage.cpython.string  
    module, 7  
sage.cpython.wrapperdescr  
    module, 31  
shortrepr () (*in module sage.cpython.debug*), 11  
str\_to\_bytes () (*in module sage.cpython.string*), 7

## T

test\_del\_dictitem\_by\_exact\_value () (*in module sage.cpython.dict\_del\_by\_value*), 33  
type\_debug () (*in module sage.cpython.debug*), 12

## W

wrapperdescr\_call () (*in module sage.cpython.wrapperdescr*), 31